



Home Subscription Agent (HSA) Specification

Candidate Version 1.0 – 17 Sep 2009

Open Mobile Alliance

OMA-TS-Presence_SIMPLE_HSA-V1_0-20090917-C

Use of this document is subject to all of the terms and conditions of the Use Agreement located at <http://www.openmobilealliance.org/UseAgreement.html>.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile Alliance™ specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the “OMA IPR Declarations” list at <http://www.openmobilealliance.org/ipr.html>. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE “OMA IPR DECLARATIONS” LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.

THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.

© 2009 Open Mobile Alliance Ltd. All Rights Reserved.

Used with the permission of the Open Mobile Alliance Ltd. under the terms set forth above.

Contents

1. SCOPE	4
2. REFERENCES	5
2.1 NORMATIVE REFERENCES	5
2.2 INFORMATIVE REFERENCES	5
3. TERMINOLOGY AND CONVENTIONS	6
3.1 CONVENTIONS	6
3.2 DEFINITIONS	6
3.3 ABBREVIATIONS	7
4. INTRODUCTION	8
4.1 VERSION 1.0	8
5. FUNCTIONAL DESCRIPTION OF THE HOME SUBSCRIPTION AGENT	9
5.1 SUBSCRIPTION SERVICE AUTHORIZATION	9
5.2 LIMITING THE NUMBER OF SUBSCRIPTIONS	9
5.3 HANDLING OF EVENT NOTIFICATION SUPPRESSION	9
5.3.1 Handling of event notification suppression conditions	9
5.3.2 Direct Event Notification Suppression	10
APPENDIX A. CHANGE HISTORY (INFORMATIVE)	11
A.1 APPROVED VERSION HISTORY	11
A.2 DRAFT/CANDIDATE VERSION 1.0 HISTORY	11
APPENDIX B. STATIC CONFORMANCE REQUIREMENTS (NORMATIVE)	12
B.1 HOME SUBSCRIPTION AGENT	12
APPENDIX C. COMMON CONTENT TYPES (NORMATIVE)	13
C.1 PRESENCE-BASED EVENT NOTIFICATION SUPPRESSION FILTER	13
C.1.1 MIME Type	13
C.1.2 XML Schema	13
C.1.3 Structure and Data Semantics	13
C.1.4 Evaluation	14
C.1.5 Examples (Informative)	14

Figures

No table of figures entries found.

Tables

No table of figures entries found.

1. Scope

This document provides the specification for the Home Subscription Agent (HSA) in the OMA Presence SIMPLE 2.0 Enabler.

2. References

2.1 Normative References

OMA

[PRS_AD] “Presence SIMPLE Architecture”, Version 2.0, Open Mobile Alliance™, OMA-AD-Presence_SIMPLE-V2_0, URL: <http://www.openmobilealliance.org/>

[PRS_Spec] “Presence SIMPLE Specification”, Version 2.0, Open Mobile Alliance™, OMA-TS-Presence_SIMPLE-V2_0, URL: <http://www.openmobilealliance.org/>

IETF

[IETF-EventThrottle] IETF draft-niemi-sipping-event-throttle-07 “Session Initiation Protocol (SIP) Event Notification Extension for Notification Throttling”, A. Niemi et al., Oct 22, 2008, URL: <http://www.ietf.org/internet-drafts/draft-niemi-sipping-event-throttle-07.txt>

Note: IETF Draft work in progress

[IETF-SubNotEtag] IETF draft-ietf-sip-subnot-etags-03 “An Extension to Session Initiation Protocol (SIP) Events for Conditional Event Notification”, A. Niemi, Jul 14, 2008, URL: <http://www.ietf.org/internet-drafts/draft-ietf-sip-subnot-etags-03.txt>

Note: IETF Draft work in progress

[RFC3265] IETF RFC 3265 “Session Initiation Protocol (SIP)-Specific Event Notification”, A. B. Roach, Jun 2002, URL: <http://www.ietf.org/rfc/rfc3265.txt>

[RFC4661] IETF RFC 4661 “An Extensible Markup Language (XML) Based Format for Event Notification Filtering”, H. Khartabil et al., Sep 2006, URL: <http://www.ietf.org/rfc/rfc4661.txt>

[RFC4662] IETF RFC 4662 “A Session Initiation Protocol (SIP) Event Notification Extension for Resource Lists”, A. B. Roach et al., Aug 2006, URL: <http://www.ietf.org/rfc/rfc4662.txt>

[RFC5367] IETF RFC 5367 “Subscriptions to Request-Contained Resource Lists in the Session Initiation Protocol (SIP)”, G. Camarillo et al., Oct 2008, URL: <http://www.ietf.org/rfc/rfc5367.txt>

3GPP/3GPP2

[3GPP-TS_23.141] 3GPP TS 23.141 “Presence Service; Architecture and functional description”, URL: http://www.3gpp.org/ftp/Specs/archive/23_series/23.141/

[3GPP2-X.S0027-001] 3GPP2 X.S0027-001 “Presence Service; Architecture and functional description”, URL: http://www.3gpp2.org/Public_html/specs/index.cfm

2.2 Informative References

Void.

3. Terminology and Conventions

3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

3.2 Definitions

Notifier	Use definition from [PRS_AD].
Presence Information	Use definition from [PRS_AD].
Presence Information Element	Use definition from [PRS_AD].
Subscriber	Use definition from [PRS_AD].
Subscription Service	A service that makes use of the SIP event notification mechanism as defined in [RFC3265].

3.3 Abbreviations

AD	Architecture Document
HSA	Home Subscription Agent
IETF	Internet Engineering Task Force
IMS	IP Multimedia Subsystem
IP	Internet Protocol
MIME	Multipurpose Internet Mail Extensions
MMD	Multimedia Domain
OMA	Open Mobile Alliance
PRS	Presence SIMPLE
RD	Requirement Document
RFC	Request For Comments
SIMPLE	SIP for Instant Messaging and Presence Leveraging Extensions
SIP	Session Initiation Protocol
UE	User Equipment
XML	eXtensible Markup Language

4. Introduction

This document provides the specification for the Home Subscription Agent (HSA) in the OMA Presence SIMPLE 2.0 Enabler.

4.1 Version 1.0

The OMA Presence SIMPLE 2.0 enabler separates the functions for entity that controls the Subscriber's service use in the Subscriber's home domain into a specification of its own to simplify reuse by other enablers. The functions included in this specification are:

- Subscription service authorization;
- Limiting the number of subscriptions; and
- Regulation of event notifications.

5. Functional Description of the Home Subscription Agent

The HSA is an entity that controls the Subscriber's access to the Subscription Service and optimizes the notification traffic based on the Subscriber's preferences or local policy.

5.1 Subscription Service Authorization

Upon receiving the SUBSCRIBE request from a Subscriber, the HSA:

- 1) SHALL, if a local policy for Subscription Service authorization exists, check whether the Subscriber is authorized to use the Subscription Service per the local policy and generate a 403 (Forbidden) response to the Subscriber if authorization fails;
- 2) SHALL, if limiting the number of subscriptions is supported, perform the procedures of section 5.2;
- 3) SHALL, if event notification suppression is supported, perform the procedures of section 5.3; and
- 4) SHALL, if event notification suppression is not supported, forward the received SUBSCRIBE request to the SIP/IP Core.

When the SIP/IP Core corresponds with 3GPP IMS or 3GPP2 MMD networks, the above functionalities of the HSA MAY be implemented in the P-CSCF and/or S-CSCF as defined in [3GPP-TS_23.141] and [3GPP2-X.S0027-001] respectively.

NOTE: The method how the SUBSCRIBE request is routed to the HSA depends on the underlying SIP/IP Core and is out of scope of this specification.

5.2 Limiting the Number of Subscriptions

The HSA MAY have a local policy to limit the maximum number of simultaneous subscriptions for a Subscriber. If the HSA determines to reject an initial subscription due to the current number of active subscriptions initiated by the Subscriber being equal to or greater than the maximum, the HSA SHALL send a 480 (Maximum number of subscriptions exceeded) response. The response MAY include the Retry-After header field (e.g. based on the expiry of active subscriptions initiated by the Subscriber) in order to suggest to the Subscriber not to retry the subscription prior to the Retry-After time.

5.3 Handling of Event Notification Suppression

The HSA MAY support event notification suppression. If supported, the HSA:

- SHALL support the handling of event notification suppression conditions. These conditions MAY be based on a local policy, or supplied by the event notification suppression filters set by the Subscriber as described in Appendix C.1, or the combination of local policy and the event notification suppression filters; and
- SHALL support direct event notification suppression to suppress notifications at the Notifier.

5.3.1 Handling of event notification suppression conditions

Upon successful authorization of the SUBSCRIBE request from a Subscriber, the HSA:

- 1) SHALL check whether the body contains a valid 'application/vnd.oma.suppnot+xml' content as described in Appendix C.1 or whether there is any other event notification suppression conditions set by the local policy. In case of invalid content and no local policy the HSA SHALL forward the SUBSCRIBE request targeted to the Notifier;
- 2) SHALL, in case of a valid 'application/vnd.oma.suppnot+xml' content or event notification suppression conditions by local policy, terminate the SUBSCRIBE request, install the subscription and send a 202 (Accepted) response to the Subscriber as described in [RFC3265]. The HSA SHALL also extract the event notification suppression filters from the 'application/vnd.oma.suppnot+xml' content;
- 3) SHALL generate a back-end subscription request targeted to the Notifier according to the subscriber procedures described in [RFC3265], [RFC4662] or [RFC5367], depending on the incoming subscription. The HSA SHALL

preserve all headers and payloads except the 'application/vnd.oma.sppnot+xml' content from the received SUBSCRIBE request into the back-end SUBSCRIBE request;

- 4) SHALL generate a presence subscription request to the Subscriber's Presence Information according to the procedures described in section [PRS_Spec] "*Subscription to Presence Information*"; and
- 5) SHALL, upon receiving a response for the back-end subscription from the Notifier, send a NOTIFY request to the Subscriber containing a Subscription-State header with the value of 'active'.

During the Subscriber's subscription lifetime, the HSA:

- 1) SHALL evaluate the presence-based event notification suppression filters against the Subscriber's Presence Information; and
- 2) SHALL, if a match is found, request the Notifier to suppress the notifications according to the procedures described in section 5.3.2.

5.3.2 Direct Event Notification Suppression

Direct event notification suppression is a mechanism that enables the HSA to request the Notifier to suppress event notifications while keeping the corresponding event subscription state active.

Direct event notification suppression can be requested using one of the following options:

- If the HSA supports conditional event notification procedures as described in [IETF-SubNotEtag], the HSA SHALL issue a SUBSCRIBE request to refresh the subscription and include a wildcarded Suppress-If-Match header field using the special "*" entity-tag value as described in [IETF-SubNotEtag] "*Generating SUBSCRIBE Requests*"; or
- If the HSA supports event notification throttling procedures as described in [IETF-EventThrottle], the HSA SHALL issue a SUBSCRIBE request to refresh the subscription and include a throttle parameter set to the remaining subscription expiration value as described in [IETF-EventThrottle] "*Selecting the Throttle Interval*".

If the HSA supports both of the above options, the HSA SHALL indicate the presence notification suppression request using the conditional event notification procedure.

Appendix A. Change History (Informative)

A.1 Approved Version History

Reference	Date	Description
n/a	n/a	No prior version

A.2 Draft/Candidate Version 1.0 History

Document Identifier	Date	Sections	Description
Draft Versions OMA-TS-Presence_SIMPLE_HSA-V1_0	04 Aug 2009	All	First version as agreed in OMA-PAG-2009-0129R01- INP_PRS2_new_HSA_TS. Application of 2009 template.
	14 Aug 2009	4	CR incorporated: OMA-PAG-2009-0235
Candidate Version OMA-TS-Presence_SIMPLE_HSA-V1_0	17 Sep 2009	N/A	Status changed to Candidate by TP TP ref # OMA-TP-2009-0438- INP_PRS_V2_0_ERP_for_Notification

Appendix B. Static Conformance Requirements (Normative)

The notation used in this appendix is specified in [SCRRULES].

The SCR's defined in the following table include SCR for the HSA.

The following tags are used in the Function column to identify the release of the Presence SIMPLE enabler that the requirement was introduced:

- PRSv2.0 – Requirement was introduced in Presence SIMPLE 2.0.

B.1 Home Subscription Agent

Item	Function	Reference	Requirement
PRS-HSA-S-001-O	Subscription Service authorization (PRSv2.0)	5.1	
PRS-HSA-S-002-O	Limiting number of subscriptions (PRSv2.0)	5.2	
PRS-HSA-S-003-O	Handling of event notification suppression (PRSv2.0)	5.3	
PRS-HSA-S-004-O	Handling of event notification suppression conditions (PRSv2.0)	5.3.15.3	PRS-HSA-S-003-O
PRS-HSA-S-005-O	Direct event notification suppression (PRSv2.0)	5.3.2	PRS-HSA-S-003-O

Appendix C. Common Content Types (Normative)

The common content types for this specification are described in this Appendix.

C.1 Presence-based Event Notification Suppression Filter

The presence-based event notification suppression filter specifies the conditions when the Subscriber wishes not to receive event notifications based on its Presence Information. A condition is evaluated by comparing the values of the condition with the Subscriber's Presence Information. If they match, the condition evaluates to true.

C.1.1 MIME Type

The MIME type for the presence-based event notification suppression filter SHALL be "application/vnd.oma.suppnot+xml".

Editor's Note: The MIME type shall be OMNA registered.

C.1.2 XML Schema

The presence-based event notification suppression filter SHALL conform to the XML schema described in [XSD_suppNot].

C.1.3 Structure and Data Semantics

The presence-based event notification suppression filter SHALL conform to the structure and semantics as described in this subclause.

The root element <suppnot-filter-set>:

- a) MAY include any other attributes for the purposes of extensibility;
- b) MAY include a <ns-bindings> element that contains the namespace bindings according to [RFC4661] "*The <ns-bindings> Element*";
- c) SHALL include zero or more <suppnot-filter> elements that contain the conditions for event notification suppression.

The <ns-bindings> element:

- a) SHALL include one or more <ns-binding> elements, each of which SHALL contain the binding between the prefix and the namespace in a "prefix" attribute and a "namespace" attribute, respectively. This is used to express the XPATH formed Presence Information Elements or Presence Information Element attributes under <presattrib> elements.

The <suppnot-filter> element:

- a) SHALL include a "id" attribute that contains the unique identification for the filter;
- b) MAY include any other attribute for the purposes of extensibility;
- c) MAY include one or more <presattrib> elements that contain the Presence Information Elements or Presence Information Element attributes that decide the suppression of the notifications;
- d) MAY include any other elements from other namespaces for the purposes of extensibility.

The <presattrib> element:

- a) MAY include any other attribute for the purposes of extensibility;

- b) MAY include one or more <suppress-if-match> elements, each of which contains the XPATH expression according to [RFC4661] “Syntax for Referencing XML Items and Making Logical Expressions”, that identifies the Presence Information Elements or Presence Information Element attributes to be matched;
- c) MAY include any other elements from other namespaces for the purposes of extensibility.

The <suppress-if-match> element:

- a) MAY include a “type” attribute that contains the expression type of the Presence Information Elements or Presence Information Element attributes in a <suppress-if-match> element. The default value is “xpath” in case of the absence of this attribute;
- b) MAY include any other attribute for the purposes of extensibility.

C.1.4 Evaluation

The evaluation of the presence-based event notification suppression filter is achieved as following:

- The empty <suppnot-filter-set> element SHALL remove any existing filters set in the HSA;
- The evaluation of each <suppnot-filter> element under the root element <suppnot-filter-set> SHALL be logically ORed;
- The evaluation of each <presattrib> child element under a <suppnot-filter> element SHALL be logically ANDed;
- The evaluation of each <suppress-if-match> child element under a <presattrib> element SHALL be logically ANDed;
- The evaluation of a <suppress-if-match> element SHALL be TRUE if the corresponding expression in the content results in identification of one or more elements in the Watcher’s Presence Information;
- The evaluation of an empty <suppress-if-match> element SHALL be FALSE.

C.1.5 Examples

(Informative)

The following is an example of the presence-based event notification suppression filter.

```
<?xml version="1.0" encoding="UTF-8"?>
<suppnot-filter-set xmlns="urn:oma:xml:prs:pidf:oma-suppnotfilter"
  xmlns:sf="urn:ietf:params:xml:ns:simple-filter">

  <ns-bindings>
    <sf:ns-binding prefix="pdm" urn="urn:ietf:params:xml:ns:pidf:data-model"/>
    <sf:ns-binding prefix="rpid" urn="urn:ietf:params:xml:ns:pidf:rpid"/>
    <sf:ns-binding prefix="op" urn="urn:oma:xml:prs:pidf:oma-pres"/>
    <sf:ns-binding prefix="pde" urn="urn:oma:xml:pde:pidf:ext"/>
  </ns-bindings>

  <!-- Condition1: Event Notification will be suppressed if the Subscriber's device is
  participating in PoC session -->
  <suppnot-filter id="45i0s">
    <presattrib>
      <suppress-if-match>//pdm:tuple[*]/op:service-id="org.openmobilealliance:PoC-session" and
      pdm:deviceID="urn:uuid:d27459b7-8213-4395-aa77-ed859a3e5b3a"]/op:session-
      participation[op:basic="open"]</suppress-if-match>
    </presattrib>
  </suppnot-filter>

  <!--Condition2: Event Notification will be suppressed if the Subscriber's presence is 'away' -->
  <suppnot-filter id="fe23de">
    <presattrib>
      <suppress-if-match>//pdm:person/rpid:activities/rpid:away</suppress-if-match>
    </presattrib>
  </suppnot-filter>

  <!-- Condition3: Event Notification will be suppressed if the Subscriber's device is under
  roaming -->
```

```
<suppnot-filter id="we34is">
  <presattrib>
    <suppress-if-match>//pdm:device[pdm:deviceID="urn:uuid:d27459b7-8213-4395-aa77-ed859a3e5b3a"
and op:network-availability/op:network/pde:visited]</suppress-if-match>
  </presattrib>
</suppnot-filter>
</suppnot-filter-set>
```