



SyncML Implementation Conformance Statement Proforma

Version 0.5

Abstract

The SyncML Implementation Conformance Statement is designed to be used by vendors to show their level of conformance with SyncML specifications.

Note that if your product can perform as both a client and a server, you will need to fill out both sets of forms.



Consortium

The following companies are sponsors in the SyncML initiative:

Ericsson

IBM

Lotus

Motorola

Nokia

Palm, Inc.

Matsushita Communications Industrial Co.

Psion

Starfish Software

Revision History

| Revision | Date | Comments |
|----------|------------|---|
| 0.1 | 2000-11-17 | 1 st pass |
| 0.2 | 2000-12-14 | Incorporate initial comments – such as adding in Protocol SCR, Authentication, and Transport section. |
| 0.3 | 2001-01-15 | Incorporated transport conformance tables. |
| 0.4 | 2001-02-20 | Corrected MIME type. |
| 0.5 | 2001-03-08 | Updated SCR tables to match errata. Updated Copyright. |

Copyright Notice

Copyright (c) **Ericsson, IBM, Lotus, Matsushita Communication Industrial Co., LTD, Motorola, Nokia, Palm, Inc., Psion, Starfish Software** (2000-2001).

All Rights Reserved.

Implementation of all or part of any Specification may require licenses under third party intellectual property rights, including without limitation, patent rights (such a third party may or may not be a Supporter). The Sponsors of the Specification are not responsible and shall not be held responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE PROVIDED ON AN "AS IS" BASIS WITHOUT WARRANTY OF ANY KIND AND ERICSSON, IBM, LOTUS, MATSUSHITA COMMUNICATION INDUSTRIAL CO. LTD, MOTOROLA, NOKIA, PALM INC., PSION, STARFISH SOFTWARE AND ALL OTHER SYNCML SPONSORS DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ERICSSON, IBM, LOTUS, MATSUSHITA COMMUNICATION INDUSTRIAL CO., LTD, MOTOROLA, NOKIA,



PALM INC., PSION, STARFISH SOFTWARE OR ANY OTHER SYNCML SPONSOR BE LIABLE TO ANY PARTY FOR ANY LOSS OF PROFITS, LOSS OF BUSINESS, LOSS OF USE OF DATA, INTERRUPTION OF BUSINESS, OR FOR DIRECT, INDIRECT, SPECIAL OR EXEMPLARY, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY KIND IN CONNECTION WITH THIS DOCUMENT OR THE INFORMATION CONTAINED HEREIN, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The above notice and this paragraph must be included on all copies of this document that are made.



Table of Contents

| | | |
|----------|--|-----------|
| 1 | Introduction | 5 |
| 2 | Product Information | 6 |
| 3 | Server Conformance Tables | 7 |
| 3.1 | Representation Common Use Elements..... | 7 |
| 3.2 | Representation Message container elements..... | 7 |
| 3.3 | Data description elements | 7 |
| 3.4 | Representation Protocol command elements | 8 |
| 3.5 | Device Info | 8 |
| 3.6 | Meta Info | 9 |
| 3.7 | Protocol | 9 |
| 3.8 | Authentication..... | 10 |
| 3.9 | MIME header types | 10 |
| 4 | Client Conformance Tables..... | 11 |
| 4.1 | Representation Common Use Elements..... | 11 |
| 4.2 | Representation Message container elements..... | 11 |
| 4.3 | Data description elements | 11 |
| 4.4 | Representation Protocol command elements | 12 |
| 4.5 | Device Info | 12 |
| 4.6 | Meta Info | 13 |
| 4.7 | Protocol | 13 |
| 4.8 | Authentication..... | 14 |
| 4.9 | MIME header types | 14 |
| 5 | Transport Conformance..... | 15 |
| 5.1 | HTTP Transport | 15 |
| 5.2 | OBEX Transport..... | 15 |
| 5.3 | WSP Transport..... | 16 |
| 6 | References..... | 17 |



1 Introduction

The purpose of this statement is to define a methodology for showing conformance with the SyncML Representation protocol [1], SyncML Sync Protocol [2] and appropriate transport. Vendors filling in this form will mark the items with either YES or NO, indicating whether the items are implemented or not. Mandatory items marked NO MUST have explanatory text.

NOTE: Server must be able to deal with with the two cases or packages 1 & 3 being sent seperately and combined.



2 Product Information

| | |
|------------------------|---|
| Device Name & Version | Neosteps SyncLE Client |
| Company | Neosteps Inc. |
| Contact Name | Kyung Nyong Kim, Shi Won Ryu |
| Contact Phone | +82-31-712-5080 |
| Contact Email | knkim@neosteps.com wonrs@neosteps.com |
| Transports supported | OBEX [<input type="checkbox"/>] WSP [<input type="checkbox"/>] HTTP [<input checked="" type="checkbox"/>] |
| Product is | Client [<input checked="" type="checkbox"/>] Server [<input type="checkbox"/>] |
| Datatypes product uses | vCard2.1 and vCalendar 1.0 |
| | |
| | |



3 Server Conformance Tables

NOTE: Server SHOULD be able to log the XML and WBXML documents sent between the server and a client.

3.1 Representation Common Use Elements

| Command | Required of Server | | Implemented in Server | |
|-----------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| Archive | MAY | MUST | | |
| Chal | MUST | MUST | | |
| Cmd | MUST | MUST | | |
| CmdID | MUST | MUST | | |
| CmdRef | MUST | MUST | | |
| Cred | MUST | MUST | | |
| Final | MUST | MUST | | |
| Lang | MAY | MAY | | |
| LocName | MAY | MAY | | |
| LocURI | MUST | MUST | | |
| MsgID | MUST | MUST | | |
| MsgRef | MUST | MUST | | |
| NoResp | MUST | MUST | | |
| NoResults | MAY | MAY | | |
| RespURI | MAY | MUST | | |
| SessionID | MUST | MUST | | |
| SftDel | MAY | MAY | | |
| Source | MUST | MUST | | |
| SourceRef | MUST | MUST | | |
| Target | MUST | MUST | | |
| TargetRef | MUST | MUST | | |
| VerDTD | MUST | MUST | | |
| VerProto | MUST | MUST | | |

3.2 Representation Message container elements

| Command | Required of Server | | Implemented in Server | |
|----------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| SyncML | MUST | MUST | | |
| SyncHdr | MUST | MUST | | |
| SyncBody | MUST | MUST | | |

3.3 Data description elements

| Command | Required of Server | | Implemented in Server | |
|---------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| Data | MUST | MUST | | |



| | | | | |
|------|------|------|--|--|
| Item | MUST | MUST | | |
| Meta | MUST | MUST | | |

3.4 Representation Protocol command elements

| Command | Required of Server | | Implemented in Server | |
|----------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| Add | MUST | MUST | | |
| Alert | MUST | MUST | | |
| Atomic | MAY | MAY | | |
| Copy | MAY | MUST | | |
| Delete | MUST | MUST | | |
| Exec | MAY | SHOULD | | |
| Get | MUST | MUST | | |
| Map | MAY | MUST | | |
| MapItem | MAY | MUST | | |
| Put | MUST | MUST | | |
| Replace | MUST | MUST | | |
| Result | MUST | MUST | | |
| Search | MAY | MAY | | |
| Sequence | MAY | MUST | | |
| Status | MUST | MUST | | |
| Sync | MUST | MUST | | |

3.5 Device Info

| Element Type | Required of Server | | Implemented in Server | |
|--------------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| CTCap | SHOULD | MUST | | |
| CTType | MUST | MUST | | |
| DataStore | MUST | MUST | | |
| DataType | MAY | MUST | | |
| DevId | MUST | MUST | | |
| DevInf | MUST | MUST | | |
| DevTyp | MUST | MUST | | |
| DisplayName | MAY | MAY | | |
| DSMem | MAY | SHOULD | | |
| Ext | MAY | MAY | | |
| FreeID | MAY | MUST | | |
| FreeMem | MAY | MUST | | |
| FwV | MAY | SHOULD | | |
| HwV | MAY | SHOULD | | |
| Man | MAY | SHOULD | | |
| MaxGUIDSize | MUST NOT | MUST | | |
| MaxID | MAY | SHOULD | | |
| MaxMem | MAY | SHOULD | | |
| Mod | MAY | MAY | | |
| OEM | MAY | MAY | | |



| | | | | |
|-----------|--------|--------|--|--|
| ParamName | SHOULD | MUST | | |
| PropName | SHOULD | MUST | | |
| Rx | MAY | MUST | | |
| Rx-Pref | MUST | MUST | | |
| SharedMem | SHOULD | MUST | | |
| Size | MAY | MUST | | |
| SourceRef | MUST | MUST | | |
| SwV | MAY | SHOULD | | |
| SyncCap | MUST | MUST | | |
| SyncType | MUST | MUST | | |
| Tx | MAY | MUST | | |
| Tx-Pref | MUST | MUST | | |
| ValEnum | SHOULD | MUST | | |
| VerCT | MUST | MUST | | |
| Xnam | MAY | MAY | | |
| Xval | MAY | MAY | | |

3.6 Meta Info

| Element Type | Required of Server | | Implemented in Server | |
|--------------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| Anchor | MUST | MUST | | |
| Format | MUST | MUST | | |
| Last | MUST | MUST | | |
| Mark | MAY | MAY | | |
| MaxMsgSize | MAY | MUST | | |
| MetInf | MUST | MUST | | |
| Next | MUST | MUST | | |
| NextNonce | MUST | MUST | | |
| Size | MAY | MAY | | |
| Type | MUST | MUST | | |
| Version | MUST | MUST | | |

3.7 Protocol

| Element Type | Server Requirements | |
|--|---------------------|-------------|
| | Required | Implemented |
| Support of 'two-way sync' | MUST | |
| Support of 'slow two-way sync' | MUST | |
| Support of 'one-way sync from client only' | MAY | |
| Support of 'refresh sync from client only' | MAY | |
| Support of 'one-way sync from server only' | MAY | |
| Support of 'refresh sync from server only' | MAY | |
| Support of 'sync alert' | MAY | |
| Support of multiple messages per package | MUST | |
| Support of combined package 1 and 3 | MUST | |



3.8 Authentication

| Authentication Type | Server Requirements | |
|---------------------------|---------------------|-------------|
| | Required | Implemented |
| Basic (name and password) | MUST | |
| MD5 | MUST | |

3.9 MIME header types

| MIME Header Type | Server Requirements | |
|--------------------------------|---------------------|-------------|
| | Required | Implemented |
| "application/vnd.syncml+xml" | MUST | |
| "application/vnd.syncml+wbxml" | MUST | |



4 Client Conformance Tables

4.1 Representation Common Use Elements

| Command | Required of Client | | Implemented in Client | |
|-----------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| Archive | MAY | MAY | | |
| Chal | MAY | MUST | | Yes |
| Cmd | MUST | MUST | Yes | Yes |
| CmdID | MUST | MUST | Yes | Yes |
| CmdRef | MUST | MUST | Yes | Yes |
| Cred | MUST | MUST | Yes | Yes |
| Final | MUST | MUST | Yes | Yes |
| Lang | MAY | MAY | | |
| LocName | MAY | MAY | | |
| LocURI | MUST | MUST | Yes | Yes |
| MsgID | MUST | MUST | Yes | Yes |
| MsgRef | MUST | MUST | Yes | Yes |
| NoResp | SHOULD | MUST | | Yes |
| NoResults | MAY | MAY | | |
| RespURI | MAY | MUST | | Yes |
| SessionID | MUST | MUST | Yes | Yes |
| SftDel | MAY | MAY | | |
| Source | MUST | MUST | Yes | Yes |
| SourceRef | MUST | MUST | Yes | Yes |
| Target | MUST | MUST | Yes | Yes |
| TargetRef | MUST | MUST | Yes | Yes |
| VerDTD | MUST | MUST | Yes | Yes |
| VerProto | MUST | MUST | Yes | Yes |

4.2 Representation Message container elements

| Command | Required of Client | | Implemented in Client | |
|----------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| SyncML | MUST | MUST | Yes | Yes |
| SyncHdr | MUST | MUST | Yes | Yes |
| SyncBody | MUST | MUST | Yes | Yes |

4.3 Data description elements

| Command | Required of Client | | Implemented in Client | |
|---------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| Data | MUST | MUST | Yes | Yes |
| Item | MUST | MUST | Yes | Yes |
| Meta | MUST | MUST | Yes | Yes |



4.4 Representation Protocol command elements

| Command | Required of Client | | Implemented in Client | |
|----------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| Add | SHOULD | MUST | | Yes |
| Alert | MUST | MUST | Yes | Yes |
| Atomic | MAY | MAY | | |
| Copy | MAY | MAY | | |
| Delete | MUST | MUST | Yes | Yes |
| Exec | MAY | MAY | | |
| Get | SHOULD | MUST | | Yes |
| Map | MUST | MAY | Yes | |
| MapItem | MUST | MAY | Yes | |
| Put | MUST | MUST | Yes | Yes |
| Replace | MUST | MUST | Yes | Yes |
| Result | MUST | SHOULD | Yes | |
| Search | MAY | MAY | | |
| Sequence | MAY | MAY | | |
| Status | MUST | MUST | Yes | Yes |
| Sync | MUST | MUST | Yes | Yes |

4.5 Device Info

| Element Type | Required of Client | | Implemented in Client | |
|--------------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| CTCap | MUST | SHOULD | Yes | |
| CTType | MUST | MUST | Yes | Yes |
| DataStore | MUST | MUST | Yes | Yes |
| DataType | MAY | MAY | | |
| DevId | MUST | MUST | Yes | Yes |
| DevInf | MUST | MUST | Yes | Yes |
| DevTyp | MUST | MUST | Yes | Yes |
| DisplayName | MAY | MAY | | |
| DSMem | SHOULD | MAY | | |
| Ext | MAY | MAY | | |
| FreeID 1) | MUST | MAY | | |
| FreeMem 2) | MUST | MAY | | |
| FwV | SHOULD | MAY | | |
| HwV | SHOULD | MAY | | |
| Man | SHOULD | MAY | | |
| MaxGUIDSize | MUST | MUST NOT | Yes | |
| MaxID | SHOULD | MAY | | |
| MaxMem | SHOULD | MAY | | |
| Mod | MAY | MAY | | |
| OEM | MAY | MAY | | |
| ParamName | SHOULD | SHOULD | | |
| PropName | MUST | SHOULD | Yes | |
| Rx | MAY | MUST | | Yes |
| Rx-Pref | MUST | MUST | Yes | Yes |



| | | | | |
|-----------|--------|--------|-----|-----|
| SharedMem | SHOULD | MUST | | Yes |
| Size | MAY | MAY | | |
| SourceRef | MUST | MUST | Yes | Yes |
| SwV | SHOULD | MAY | | |
| SyncCap | MUST | MUST | Yes | Yes |
| SyncType | MUST | MUST | Yes | Yes |
| Tx | MAY | MUST | | Yes |
| Tx-Pref | MUST | MUST | Yes | Yes |
| ValEnum | MUST | SHOULD | Yes | |
| VerCT | MUST | MUST | Yes | Yes |
| Xnam | MAY | MAY | | |
| Xval | MAY | MAY | | |

- 1) This element is moved to Meta Info DTD and changed to SHOULD / MAY.
- 2) This element is moved to Meta Info DTD and changed to SHOULD / MAY.

4.6 Meta Info

| Element Type | Required of Client | | Implemented in Client | |
|--------------|--------------------|-----------|-----------------------|-----------|
| | Sending | Receiving | Sending | Receiving |
| Anchor | MUST | MUST | Yes | Yes |
| Format | MUST | MUST | Yes | Yes |
| FreeID | SHOULD | MAY | | |
| FreeMem | SHOULD | MAY | | |
| Last | MUST | MUST | Yes | Yes |
| Mark | MAY | MAY | | |
| MaxMsgSize | MAY | MUST | | Yes |
| MetInf | MUST | MUST | Yes | Yes |
| Next | MUST | MUST | Yes | Yes |
| NextNonce | MUST 3) | MUST | | Yes |
| Size | MAY | MAY | | |
| Type | MUST | MUST | Yes | Yes |
| Version | MAY | MAY | | |

- 3) This should be MAY, because it is optional for a client to send the Chal element, and this information is carried within Chal element.

4.7 Protocol

| Element Type | Client Requirements | |
|--|---------------------|-------------|
| | Required | Implemented |
| Support of 'two-way sync' | MUST | Yes |
| Support of 'slow two-way sync' | MUST | Yes |
| Support of 'one-way sync from client only' | MAY | |
| Support of 'refresh sync from client only' | MAY | |
| Support of 'one-way sync from server only' | MAY | |
| Support of 'refresh sync from server only' | MAY | |
| Support of 'sync alert' | MAY | |
| Support of multiple messages per package | MUST | Yes |
| Support of combined package 1 and 3 | MAY | |



4.8 Authentication

Note that authentication is only required for SyncHdr, optional for datastore.

TODO: build this up to have separate levels (SyncHdr, datastore, etc).

| Authentication Type | Client Requirements | |
|---------------------------|---------------------|-------------|
| | Required | Implemented |
| Basic (name and password) | MUST | Yes |
| MD5 | MUST | Yes |

4.9 MIME header types

NOTE: the client MUST support one of the two MIME header types.

| MIME Header Type | Client Requirements | |
|--------------------------------|---------------------|-------------|
| | Required | Implemented |
| "application/vnd.syncml+xml" | MUST if no wbxml | Yes |
| "application/vnd.syncml+wbxml" | MUST if no xml | |



5 Transport Conformance

5.1 HTTP Transport

Vendors should fill this section out ONLY if their product uses the HTTP Transport. The specification for HTTP Transport is fully described in [4].

NOTE that the tables only indicate the required data.

| Method | Requirements | |
|--------|--------------|-------------|
| | Required | Implemented |
| POST | MUST | Yes |

| General Headers | Requirements | |
|----------------------------------|--------------|-------------|
| | Required | Implemented |
| Cache-Control: no-store, private | MUST | Yes |
| Transfer-Encoding: chunked | MUST | Yes |

| Request Headers | Requirements | |
|---------------------|------------------------|-------------|
| | Required | Implemented |
| Accept | MUST | Yes |
| Accept-Charset | MUST | Yes |
| Authorization | MUST | Yes |
| Proxy-Authorization | MUST if a proxy client | |
| User-Agent | MUST | Yes |

| Response Headers | Requirements | |
|---------------------|----------------------|-------------|
| | Required | Implemented |
| Authentication-Info | MUST | Yes |
| Proxy-Authenticate | MUST if proxy client | |
| WWW-Authenticate | MUST | Yes |

5.2 OBEX Transport

Vendors should fill this section out ONLY if their product uses the OBEX Transport. The specification for OBEX Transport is fully described in [6]. Note that these definitions of client and server are the OBEX definition, not the SyncML definition.

NOTE that the tables only indicate the required data.

| Method | OBEX Server Requirements | |
|--------|--------------------------|-------------|
| | Required | Implemented |
| GET | MUST | |



| | | |
|------------|------|--|
| PUT | MUST | |
| CONNECT | MUST | |
| DISCONNECT | MUST | |
| ABORT | MUST | |

| Method | OBEX Client Requirements | |
|------------|--------------------------|-------------|
| | Required | Implemented |
| GET | MUST | |
| PUT | MUST | |
| CONNECT | MUST | |
| DISCONNECT | MUST | |

5.3 WSP Transport

Vendors should fill this section out ONLY if their product uses the WSP Transport. The specification for WSP Transport is fully described in [7].

NOTE that the tables only indicate the required data.

TBD.



6 References

- [1] SyncML Representation Protocol Specification
- [2] SyncML Sync Protocol
- [3] Meta Information Specification and DTD
- [4] Device Information Specification and DTD
- [5] SyncML HTTP Binding
- [6] SyncML OBEX Binding
- [7] SyncML WSP Binding