

1 of 17 Pages Version 1.0 2001-11-02

# SyncML Implementation Conformance Statement Proforma

# Version 1.0

#### Abstract

The SyncML Implementation Conformance Statement is designed to be used by vendors to show their level of conformance with SyncML specifications.

Note that if your product can perform as both a client and a server, you will need to fill out both sets of forms.



2 of 17 Pages Version 1.0 2001-11-02

### SyncML Initiative

The following companies are Sponsors of the SyncML Initiative:

Ericsson IBM Lotus Matsushita Communications Industrial Co., Ltd. Motorola Nokia Openwave Palm, Inc. Psion Starfish Software Symbian

#### **Revision History**

Revision	Date	Comments
1.0	2001-11-02	Finalized for release.



http://www.syncml.org/docs/syncml\_ics\_v10\_20011102.doc

3 of 17 Pages Version 1.0 2001-11-02

## **Copyright Notice**

Copyright (c) Ericsson, IBM, Lotus, Matsushita Communication Industrial Co., LTD, Motorob, Nokia, Openwave, Palm, Inc., Psion, Starfish Software, Symbian (2000-2001).

All Rights Reserved.

Implementation of all or part of any Specification may require licenses under third party intellectual property rights, including without limitation, patent rights (such a third party may or may not be a Supporter). The Sponsors of the Specification are not responsible and shall not be held responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE PROVIDED ON AN "AS IS" BASIS WITHOUT WARRANTY OF ANY KIND AND ERICSSON, IBM, LOTUS, MATSUSHITA COMMUNICATION INDUSTRIAL CO. LTD, MOTOROLA, NOKIA, PALM INC., PSION, STARFISH SOFTWARE AND ALL OTHER SYNCML SPONSORS DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ERICSSON, IBM, LOTUS, MATSUSHITA COMMUNICATION INDUSTRIAL CO., LTD, MOTOROLA, NOKIA, PALM INC., PSION, STARFISH SOFTWARE OR ANY OTHER SYNCML SPONSOR BE LIABLE TO ANY PARTY FOR ANY LOSS OF PROFITS, LOSS OF BUSINESS, LOSS OF USE OF DATA, INTERRUPTION OF BUSINESS, OR FOR DIRECT, INDIRECT, SPECIAL OR EXEMPLARY, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY KIND IN CONNECTION WITH THIS DOCUMENT OR THE INFORMATION CONTAINED HEREIN, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The above notice and this paragraph must be included on all copies of this document that are made.



http://www.syncml.org/docs/syncml\_ics\_v10\_20011102.doc

4 of 17 Pages Version 1.0 2001-11-02

## **Table of Contents**

1	Intro	duction	5
2	Prod	uct Information	6
	2.1	Device and Contact Information	6
	2.2	Content Formats Supported	6
3	Serve	er Conformance Tables	7
	3.1	Representation Common Use Elements	7
	3.2	Representation Message container elements	
	3.3	Data description elements	7
	3.4	Representation Protocol command elements	8
	3.5	Device Info	8
	3.6	Meta Info	9
	3.7	Protocol	9
	3.8	Authentication	10
	3.9	MIME header types	10
4	Clien	t Conformance Tables	11
	4.1	Representation Common Use Elements	11
	4.2	Representation Message container elements	
	4.3	Data description elements	11
	4.4	Representation Protocol command elements	12
	4.5	Device Info	12
	4.6	Meta Info	13
	4.7	Protocol	13
	4.8	Authentication	14
	4.9	MIME header types	14
5	Trans	sport Conformance	15
	5.1	HTTP Transport	15
	5.2	OBEX Transport	15
	5.3	WSP Transport	16
6	Refer	ences	17



## 1 Introduction

The purpose of this statement is to define a methodology for showing conformance with the SyncML Representation protocol [1], SyncML Sync Protocol [2] and appropriate transport. Vendors filling in this form will mark the items with either YES or NO, indicating whether the items are implemented or not. Mandatory items marked NO MUST have explanatory text.

NOTE: Server must be able to deal with with the two cases or packages 1 & 3 being sent seperately and combined.



## 2 **Product Information**

#### 2.1 Device and Contact Information

Device Name & Version	Magical SyncClient v1.0 for Windows CE
Company	Magically Asia Ltd.
Contact Name	Bill Klein
Contact Phone	1-514-583-0403
Contact Email	bill@magically.com
Transports supported	OBEX[] WSP[] HTTP[X]
Product is	Client [ X ] Server []

#### 2.2 Content Formats Supported

NOTE: If a server supports a data type listed below, it must also support the associated content format.

Data Type	Content Format	Supported (Y/N)
Contact	vCard 2.1	Y
	vCard 3.0 (optional)	Ν
Calendar	vCalendar 1.0	Ν
	iCalendar 2.0 (optional)	Ν
Memos	text/plain	Ν
Tasks	vTodo 1.0	Ν
Email	message/rfc822	N
	message/rfc2822	Ν
	Message/rfc2045	Ν



# **3** Server Conformance Tables

NOTE: Server SHOULD be able to log the XML and WBXML documents sent between the server and a client.

#### 3.1 Representation Common Use Elements

Command	Command Required of Server		Implement	ted in Server
	Sending	Receiving	Sending	Receiving
Archive	MAY	MUST		
Chal	MUST	MUST		
Cmd	MUST	MUST		
CmdID	MUST	MUST		
CmdRef	MUST	MUST		
Cred	MUST	MUST		
Final	MUST	MUST		
Lang	MAY	MAY		
LocName	МАҮ	MAY		
LocURI	MUST	MUST		
MsgID	MUST	MUST		
MsgRef	MUST	MUST		
NoResp	MAY	MUST		
NoResults	MAY	MAY		
RespURI	MAY	MUST		
SessionID*	MUST	MUST		
SftDel	MAY	MAY		
Source	MUST	MUST		
SourceRef	MUST	MUST		
Target	MUST	MUST		
TargetRef	MUST	MUST		
VerDTD	MUST	MUST		
VerProto	MUST	MUST		

\*The maximum length of a SessionID is 4 bytes. Note that a client having an 8 bit incrementing SessionID counter is enough for practical implementations.

#### 3.2 Representation Message container elements

	Command	Required of Server		Implemen	ted in Server
		Sending	Receiving	Sending	Receiving
	SyncML	MUST	MUST		
	SyncHdr	MUST	MUST		
ľ	SyncBody	MUST	MUST		

#### 3.3 Data description elements

Command	Required of Server		Implemented in Server	
	Sending Receiving		Sending	Receiving

**Sync**ML

SyncML Implementation Conformance Statement

http://www.syncml.org/docs/syncml\_ics\_v10\_20011102.doc

Version 1.0 2001-11-02

Data	MUST	MUST	
Item	MUST	MUST	
Meta	MUST	MUST	

#### **3.4 Representation Protocol command elements**

Command	Required of Server		Implemen	ted in Server
	Sending	Receiving	Sending	Receiving
Add	MUST	MUST		
Alert	MUST	MUST		
Atomic	MAY	MAY		
Сору	МАҮ	MUST		
Delete	MUST	MUST		
Exec	МАҮ	SHOULD		
Get*	MUST	MUST		
Мар	МАҮ	MUST		
MapItem	MAY	MUST		
Put*	MUST	MUST		
Replace	MUST	MUST		
Result*	MUST	MUST		
Search	MAY	MAY		
Sequence	MAY	MUST		
Status	MUST	MUST		
Sync	MUST	MUST		

\*Minimum requirement for a SyncML device is to support Put, Get, and Result when exchanging device information.

#### 3.5 Device Info

Element Type	Required	d of Server	Implemen	ted in Server
	Sending	Receiving	Sending	Receiving
CTCap	SHOULD	MUST		
СТТуре	MUST	MUST		
DataStore	MUST	MUST		
DataType	MAY	MUST		
DevID	MUST	MUST		
DevInf	MUST	MUST		
DevTyp	MUST	MUST		
DisplayName	MAY	MAY		
DSMem	MAY	SHOULD		
Ext	MAY	MAY		
FwV	MAY	SHOULD		
HwV	MAY	SHOULD		
Man	MAY	SHOULD		
MaxGUIDSize	MUST NOT	MUST		
MaxID	MAY	SHOULD		
MaxMem	MAY	SHOULD		
Mod	MAY	MAY		
OEM	MAY	MAY		

#### http://www.syncml.org/docs/syncml\_ics\_v10\_20011102.doc

9 of 17 Pages Version 1.0 2001-11-02

Descention		MUGH	
ParamName	SHOULD	MUST	
PropName	SHOULD	MUST	
Rx	MAY	MUST	
Rx-Pref	MUST	MUST	
SharedMem	SHOULD	MAY	
Size	МАҮ	MUST	
SourceRef	MUST	MUST	
SwV	MAY	SHOULD	
SyncCap	MUST	MUST	
SyncType	MUST	MUST	
Tx	МАҮ	MUST	
Tx-Pref	MUST	MUST	
ValEnum	SHOULD	MUST	
VerCT	MUST	MUST	
VerDTD	MUST	MUST	
Xnam	МАҮ	MAY	
Xval	МАҮ	MAY	

#### 3.6 Meta Info

Element Type	Required	l of Server	Implemen	ted in Server
	Sending	Receiving	Sending	Receiving
Anchor	MUST	MUST		
EMI	MAY	MAY		
Format	MUST	MUST		
FreeID	MAY	MUST		
FreeMem	MAY	MUST		
Last	MUST	MUST		
Mark	MAY	MAY		
MaxMsgSize	MAY	MUST		
Mem	MAY	MUST		
MetInf	MUST	MUST		
Next	MUST	MUST		
NextNonce	MUST	MUST		
SharedMem	MAY	MUST		
Size	MAY	MAY		
Туре	MUST	MUST		
Version	MUST	MUST		

#### 3.7 Protocol

Element Type	Server Requirements	
	Required	Implemented
Support of 'two-way sync'	MUST	
Support of 'slow two-way sync'	MUST	
Support of 'one -way sync from client only'	MAY	
Support of 'refresh sync from client only'	MAY	

2001-11-02

Support of 'one -way sync from server only'	MAY	
Support of 'refresh sync from server only'	MAY	
Support of 'sync alert'	MAY	
Support of multiple messages per package	MUST	
Support of combined package 1 and 3	MUST	

#### 3.8 Authentication

Authentication Type	Server Requirements	
	Required	Implemented
Basic (name and password)	MUST	
MD5	MUST	

#### 3.9 MIME header types

MIME Header Type	Server Requirements	
	Required	Implemented
"application/vnd.syncml+xml"	MUST	
"application/vnd.syncml+wbxml"	MUST	



## 4 Client Conformance Tables

## 4.1 Representation Common Use Elements

Command	Required	d of Client	Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
Archive	MAY	MAY	N	N
Chal	MAY	MUST	N	Y
Cmd	MUST	MUST	Y	Y
CmdID	MUST	MUST	Y	Y
CmdRef	MUST	MUST	Y	Y
Cred	MUST	MUST	Y	Y
Final	MUST	MUST	Y	Y
Lang	MAY	MAY	N	N
LocName	MAY	MAY	Y	Y
LocURI	MUST	MUST	Y	Y
MsgID	MUST	MUST	Y	Y
MsgRef	MUST	MUST	Y	Y
NoResp	MAY	MUST	Y	Y
NoResults	MAY	MAY	N	N
RespURI	MAY	MUST	N	Y
SessionID*	MUST	MUST	Y	Y
SftDel	MAY	MAY	N	N
Source	MUST	MUST	Y	Y
SourceRef	MUST	MUST	Y	Y
Target	MUST	MUST	Y	Y
TargetRef	MUST	MUST	Y	Y
VerDTD	MUST	MUST	Y	Y
VerProto	MUST	MUST	Y	Y

\*The maximum length of a SessionID is 4 bytes. Note that a client having an 8 bit incrementing SessionID counter is enough for practical implementations.

#### 4.2 Representation Message container elements

Command	Required of Client		Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
SyncML	MUST	MUST	Y	Y
SyncHdr	MUST	MUST	Y	Y
SyncBody	MUST	MUST	Y	Y

#### 4.3 Data description elements

	Command	Required of Client		Implemen	ted in Client
		Sending	Receiving	Sending	Receiving
	Data	MUST	MUST	Y	Y
	Item	MUST	MUST	Y	Y
ľ	Meta	MUST	MUST	Y	Y



### 4.4 Representation Protocol command elements

Command	Required	d of Client	Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
Add	SHOULD	MUST	Y	Y
Alert	MUST	MUST	Y	Y
Atomic	МАҮ	MAY	N	N
Сору	MAY	MAY	N	N
Delete	MUST	MUST	Y	Y
Exec	MAY	MAY	N	N
Get*	SHOULD	MUST	N	Y
Map	MUST	MAY	Y	N
MapItem	MUST	MAY	Y	N
Put*	MUST	MUST	Y	Y
Replace	MUST	MUST	Y	Y
Result*	MUST	SHOULD	Y	N
Search	МАҮ	MAY	N	N
Sequence	МАҮ	MAY	N	N
Status	MUST	MUST	Y	Y
Sync	MUST	MUST	Y	Y

\*Minimum requirement for a SyncML device is to support Put, Get, and Result when exchanging device information.

#### 4.5 Device Info

Element Type	Require	d of Client	Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
CTCap	MUST	SHOULD	Y	N
СТТуре	MUST	MUST	Y	Y
DataStore	MUST	MUST	Y	Y
DataType	MAY	MAY	N	N
DevId	MUST	MUST	Y	Y
DevInf	MUST	MUST	Y	Y
DevTyp	MUST	MUST	Y	Y
DisplayName	MAY	MAY	Y	N
DSMem	SHOULD	MAY	N	N
Ext	MAY	MAY	N	N
FwV	SHOULD	MAY	N	N
HwV	SHOULD	MAY	N	N
Man	SHOULD	MAY	N	N
MaxGUIDSize	MUST	MUST NOT	Y	N
MaxID	SHOULD	MAY	N	N
MaxMem	SHOULD	MAY	N	N
Mod	MAY	MAY	N	N
OEM	MAY	MAY	N	N
ParamName	SHOULD	SHOULD	Y	N
PropName	MUST	SHOULD	Y	N
Rx	MAY	MUST	Y	Y



#### http://www.syncml.org/docs/syncml\_ics\_v10\_20011102.doc

2001-11-02

Rx-Pref	MUST	MUST	Y	Y
SharedMem	SHOULD	MAY	N	N
Size	МАҮ	MAY	N	N
SourceRef	MUST	MUST	Y	Y
SwV	SHOULD	MAY	N	N
SyncCap	MUST	MUST	Y	Y
SyncType	MUST	MUST	Y	Y
Tx	MAY	MUST	Y	Y
Tx-Pref	MUST	MUST	Y	Y
ValEnum	MUST	SHOULD	Y	N
VerCT	MUST	MUST	Y	Y
VerDTD	MUST	MUST	Y	Y
Xnam	МАҮ	MAY	N	N
Xval	MAY	MAY	N	N

#### 4.6 Meta Info

Element Type	Required of Client		Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
Anchor	MUST	MUST	Y	Y
EMI	МАҮ	MAY	N	N
Format	MUST	MUST	Y	Y
FreeID	SHOULD	MAY	N	N
FreeMem	SHOULD	MAY	N	N
Last	MUST	MUST	Y	Y
Mark	MAY	MAY	N	N
MaxMsgSize	МАҮ	MUST	Y	Y
Mem	SHOULD	MAY	N	N
MetInf	MUST	MUST	Y	Y
Next	MUST	MUST	Y	Y
NextNonce	МАҮ	MUST	N	Y
SharedMem	SHOULD	MAY	N	N
Size	МАҮ	MAY	N	N
Туре	MUST	MUST	Y	Y
Version	MAY	МАҮ	N	N

### 4.7 Protocol

Element Type	Client Re	Client Requirements	
	Required	Implemented	
Support of 'two-way sync'	MUST	Y	
Support of 'slow two-way sync'	MUST	Y	
Support of 'one -way sync from client only'	MAY	N	
Support of 'refresh sync from client only'	MAY	N	
Support of 'one -way sync from server only'	MAY	N	
Support of 'refresh sync from server only'	MAY	N	
Support of 'sync alert'	МАҮ	N	



http://www.syncml.org/docs/syncml\_ics\_v10\_20011102.doc

Version 1.0 2001-11-02

Support of multiple messages per package	MUST	Y
Support of combined package 1 and 3	MAY	N

#### 4.8 Authentication

Note that authentication is only required for SyncHdr, optional for datastore.

Authentication Type	Client Requirements	
	Required	Implemented
Basic (name and password)	MUST	Y
MD5	MUST	Y

#### 4.9 MIME header types

NOTE: the client MUST support one of the two MIME header types.

MIME Header Type	Client Requirements	
	Required	Implemented
"application/vnd.syncml+xml"	MUST if no wbxml	Y
"application/vnd.syncml+wbxml"	MUST if no xml	N



## **5** Transport Conformance

#### 5.1 HTTP Transport

Vendors should fill this section out ONLY if their product uses the HTTP Transport. The specification for HTTP Transport is fully described in 0.

NOTE that the tables only indicate the required data.

Method	Requirements	
	Required	Implemented
POST	MUST	Y

General Headers	Requirements	
	Required	Implemented
Cache-Control: no-store, private	MUST	Y
Transfer-Encoding: chunked	MUST	Y

Request Headers	aders Requiremen	
	Required	Implemented
Accept	MUST	Y
AcceptCharset	MUST	Y
Authorization	MUST	Y
Proxy-Authorization	MUST if a proxy client	N
User-Agent	MUST	Y

Response Headers	Requirements	
	Required	Implemented
AuthenticationInfo	MUST	Y
Proxy-Authenticate	MUST if proxy client	N
WWW-Authenticate	MUST	Y

## 5.2 **OBEX Transport**

Vendors should fill this section out ONLY if their product uses the OBEX Transport. The specification for OBEX Transport is fully described in 0. Note that these definitions of client and server are the OBEX definition, not the SyncML definition.

NOTE that the tables only indicate the required data.

Method	OBEX Server Requirements	
	Required	Implemented
GET	MUST	

-1

http://www.syncml.org/docs/syncml\_ics\_v10\_20011102.doc

2001-11-02

PUT	MUST	
CONNECT	MUST	
DISCONNECT	MUST	
ABORT	MUST	

Method	OBEX Client Requirements	
	Required	Implemented
GET	MUST	
PUT	MUST	
CONNECT	MUST	
DISCONNECT	MUST	

#### **WSP** Transport 5.3

Vendors should fill this section out ONLY if their product uses the WSP Transport. The specification for WSP Transport is fully described in 0.

NOTE that the tables only indicate the required data.

Method	Requirements	
	Required	Implemented
POST	MUST	





17 of 17 Pages Version 1.0 2001-11-02

## 6 References

- [1] SyncML Representation Protocol Specification
- [2] SyncML Sync Protocol
- [3] Meta Information Specification and DTD
- [4] Device Information Specification and DTD
- [5] SyncML HTTP Binding
- [6] SyncML OBEX Binding
- [7] SyncML WSP Binding