

2002-10-22

SyncML Implementation Conformance Statement Proforma SyncML DataSync V1.0.1

Abstract

The SyncML Implementation Conformance Statement is designed to be used by vendors to show their level of conformance with SyncML specifications.

Note that if you are submitting both a client and a server, you will need to fill out two separate forms.

2 of 18 Pages Version 2.0

2002-10-22

SyncML Initiative

The following companies are Sponsors of the SyncML Initiative:

Ericsson
IBM
Lotus
Matsushita Communication Industrial Co., Ltd.
Motorola
Nokia
Openwave
Palm, Inc.
Psion
Starfish Software
Symbian

Revision History

Date	Comments
2002-10-22	Signed off for integration into OMA.



3 of 18 Pages Version 2.0

2002-10-22

Copyright Notice

Copyright (c) Ericsson, IBM, Lotus, Matsushita Communication Industrial Co., LTD, Motorola, Nokia, Openwave, Palm, Inc., Psion, Starfish Software, Symbian (2000-2002).

All Rights Reserved.

Implementation of all or part of any Specification may require licenses under third party intellectual property rights, including without limitation, patent rights (such a third party may or may not be a Supporter). The Sponsors of the Specification are not responsible and shall not be held responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE PROVIDED ON AN "AS IS" BASIS WITHOUT WARRANTY OF ANY KIND AND ERICSSON, IBM, LOTUS, MATSUSHITA COMMUNICATION INDUSTRIAL CO. LTD, MOTOROLA, NOKIA, PALM INC., PSION, STARFISH SOFTWARE AND ALL OTHER SYNCML SPONSORS DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ERICSSON, IBM, LOTUS, MATSUSHITA COMMUNICATION INDUSTRIAL CO., LTD, MOTOROLA, NOKIA, PALM INC., PSION, STARFISH SOFTWARE OR ANY OTHER SYNCML SPONSOR BE LIABLE TO ANY PARTY FOR ANY LOSS OF PROFITS, LOSS OF BUSINESS, LOSS OF USE OF DATA, INTERRUPTION OF BUSINESS, OR FOR DIRECT, INDIRECT, SPECIAL OR EXEMPLARY, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY KIND IN CONNECTION WITH THIS DOCUMENT OR THE INFORMATION CONTAINED HEREIN, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The above notice and this paragraph must be included on all copies of this document that are made.

2002-10-22



Table of Contents

1	Intro	oduction	5
2	Pro	duct Information	6
	2.1	Device and Contact Information	
	2.2	Content Formats Supported	6
3	Serv	ver Conformance Tables	7
	3.1	Representation Common Use Elements	7
	3.2	Representation Message container elements	
	3.3	Data description elements	
	3.4	Representation Protocol command elements	8
	3.5	Device Info	
	3.6	Meta Info	9
	3.7	Protocol	10
	3.8	Authentication	10
	3.9	MIME header types	10
4	Clie	nt Conformance Tables	11
	4.1	Representation Common Use Elements	11
	4.2	Representation Message container elements	11
	4.3	Data description elements	12
	4.4	Representation Protocol command elements	
	4.5	Device Info	12
	4.6	Meta Info	13
	4.7	Protocol	14
	4.8	Authentication	14
	4.9	MIME header types	14
5	Trar	nsport Conformance	15
	5.1	HTTP Transport	15
	5.2	OBEX Transport	16
	5.3	WSP Transport	16
6	Add	litional Information	17
7	Rofe	arancas	19



5 of 18 Pages Version 2.0

2002-10-22

1 Introduction

The purpose of this statement is to define a methodology for showing conformance with the SyncML Representation protocol [1], SyncML Sync Protocol [2] and appropriate transport. Vendors filling in this form will mark the items with either YES or NO, indicating whether the items are implemented or not. Mandatory items marked NO MUST have explanatory text.

NOTE: Server must be able to deal with the two cases of packages 1 & 3 being sent separately and combined.

Please use section 6 to provide any additional information with regards to your Implementation Conformance Statement. Please do not annotate the SCR items in the following sections.



2 Product Information

2.1 Device and Contact Information

Device Name & Version:	P800
Company:	Sony Ericsson Mobile Communications AB
Contact Name:	Pär Eriksson
Contact Phone:	+46 8 585 337 64
Contact Email:	Par.Eriksson@SonyEricsson.com
Product is:	CLIENT[x]
	SERVER[]
Transports supported:	HTTP[x]
	WSP[]
	OBEX[]
OBEX support:	IrDA[]
	Bluetooth[]

Note s:

- The contents of the [Device Name & Version] field will appear in the List of compliant products on the SyncML web page.
- OBEX support for RS232 and USB is not defined scoped out within the SyncML bindings specifications. Devices cannot claim these transports until the specifications have been updated.

2.2 Content Formats Supported

NOTE: If a server supports a data type listed below, it must also support the associated content format

Data Type	Content Format	Supported (Y/N)
Contact	vCard 2.1	Y
	vCard 3.0 (optional)	N
Calendar	vCalendar 1.0	Y
	iCalendar 2.0 (optional)	N
Memos	text/plain	N
Tasks	vTodo 1.0	Y
Email	message/rfc822	N
	message/rfc2822	N
	message/rfc2045	N
Other (Please specify any other supported data types)		



3 Server Conformance Tables

NOTE: Server SHOULD be able to log the XML and WBXML documents sent between the server and a client.

3.1 Representation Common Use Elements

This section contains the ICS proforma for the Static Conformance Requirements for the Representation Common Use Elements.

Command	Required	l of Server	Implement	ted in Server
	Sending	Receiving	Sending	Receiving
Archive	MAY	MUST		
Chal	MUST	MUST		
Cmd	MUST	MUST		
CmdID	MUST	MUST		
CmdRef	MUST	MUST		
Cred	MUST	MUST		
Final	MUST	MUST		
Lang	MAY	MAY		
LocName	MAY	MAY		
LocURI	MUST	MUST		
MsgID	MUST	MUST		
MsgRef	MUST	MUST		
NoResp	MAY	MUST		
NoResults	MAY	MAY		
RespURI	MAY	MUST		
SessionID*	MUST	MUST		
SftDel	MAY	MAY		
Source	MUST	MUST		
SourceRef	MUST	MUST		
Target	MUST	MUST		
TargetRef	MUST	MUST		
VerDTD	MUST	MUST		
VerProto	MUST	MUST		

^{*}The maximum length of a SessionID is 4 bytes. Note that a client having an 8 bit incrementing SessionID counter is enough for practical implementations.

3.2 Representation Message container elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Message Container elements.

Command	Required of Server		Implemen	ted in Server
	Sending	Receiving	Sending	Receiving
SyncML	MUST	MUST		
SyncHdr	MUST	MUST		
SyncBody	MUST	MUST		

8 of 18 Pages Version 2.0

2002-10-22

3.3 Data description elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Data Description elements.

Command	Required of Server		Implement	ted in Server
	Sending	Receiving	Sending	Receiving
Data	MUST	MUST		
Item	MUST	MUST		
Meta	MUST	MUST		

3.4 Representation Protocol command elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Protocol Command elements.

Command	Required	l of Server	Implemented in Server	
	Sending	Receiving	Sending	Receiving
Add	MUST	MUST		
Alert	MUST	MUST		
Atomic	MAY	MAY		
Copy	MAY	MUST		
Delete	MUST	MUST		
Exec	MAY	SHOULD		
Get*	MUST	MUST		
Map	MAY	MUST		
MapItem	MAY	MUST		
Put*	MUST	MUST		
Replace	MUST	MUST		
Result*	MUST	MUST		
Search	MAY	MAY		
Sequence	MAY	MUST		
Status	MUST	MUST		
Sync	MUST	MUST		

^{*}Minimum requirement for a SyncML device is to support Put, Get, and Result when exchanging device information.

3.5 Device Info

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Device Information.

Element Type	Required of Server		Implemented in Server	
	Sending	Receiving	Sending	Receiving
CTCap	SHOULD	MUST		
CTType	MUST	MUST		
DataStore	MUST	MUST		
DataType	MAY	MUST		
DevID	MUST	MUST		
DevInf	MUST	MUST		
DevTyp	MUST	MUST		
DisplayName	MAY	MAY		
DSMem	MAY	SHOULD		

Copyright © 2000-2002 Ericsson, IBM, Lotus, Matsus hita Communication Industrial Co., Ltd., Motorola, Nokia, Openwave, Palm, Inc., Psion, Starfish Software, Symbian. All Rights Reserved.

9 of 18 Pages Version 2.0

2002-10-22

Ext	MAY	MAY	
FwV	MAY	SHOULD	
HwV	MAY	SHOULD	
Man	MAY	SHOULD	
MaxGUIDSize	MUST NOT	MUST	
MaxID	MAY	SHOULD	
MaxMem	MAY	SHOULD	
Mod	MAY	MAY	
OEM	MAY	MAY	
ParamName	SHOULD	MUST	
PropName	SHOULD	MUST	
Rx	MAY	MUST	
Rx-Pref	MUST	MUST	
SharedMem	SHOULD	MAY	
Size	MAY	MUST	
SourceRef	MUST	MUST	
SwV	MAY	SHOULD	
SyncCap	MUST	MUST	
SyncType	MUST	MUST	
Tx	MAY	MUST	
Tx-Pref	MUST	MUST	
ValEnum	SHOULD	MUST	
VerCT	MUST	MUST	
VerDTD	MUST	MUST	
Xnam	MAY	MAY	
Xval	MAY	MAY	

3.6 Meta Info

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Meta Information.

Element Type	Required	l of Server	Implemented in Server	
	Sending	Receiving	Sending	Receiving
Anchor	MUST	MUST		
EMI	MAY	MAY		
Format	MUST	MUST		
FreeID	MAY	MUST		
FreeMem	MAY	MUST		
Last	MUST	MUST		
Mark	MAY	MAY		
MaxMsgSize	MAY	MUST		
Mem	MAY	MUST		
MetInf	MUST	MUST		
Next	MUST	MUST		
NextNonce	MUST	MUST		
SharedMem	MAY	MUST		
Size	MAY	MAY		
Type	MUST	MUST		
Version	MUST	MUST		



3.7 **Protocol**

This section contains the ICS Proforma for the Static Conformance Requirements for the Sync Protocol.

Element Type	Server Re	equirements
	Required	Implemented
Support of 'two-way sync'	MUST	
Support of 'slow two-way sync'	MUST	
Support of 'one -way sync from client only'	MAY	
Support of 'refresh sync from client only'	MAY	
Support of 'one -way sync from server only'	MAY	
Support of 'refresh sync from server only'	MAY	
Support of 'sync alert'	MAY	
Support of multiple messages per package	MUST	
Support of combined package 1 and 3	MUST	

3.8 **Authentication**

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Authentication.

Authentication Type	Server Requirements	
	Required	Implemented
Basic (name and password)	MUST	
MD5	MUST	

MIME header types 3.9

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML MIME Media Types.

MIME Header Type	Server Ro	equirements
	Required	Implemented
"application/vnd.syncml+xml"	MUST	
"application/vnd.svncml+wbxml"	MUST	



4 Client Conformance Tables

4.1 Representation Common Use Elements

This section contains the ICS proforma for the Static Conformance Requirements for the Representation Common Use Elements.

Command	Required of Client		Implemented in Client	
	Sending	Receiving	Sending	Receiving
Archive	MAY	MAY	NO	NO
Chal	MAY	MUST	NO	YES
Cmd	MUST	MUST	YES	YES
CmdID	MUST	MUST	YES	YES
CmdRef	MUST	MUST	YES	YES
Cred	MUST	MUST	YES	YES
Final	MUST	MUST	YES	YES
Lang	MAY	MAY	NO	NO
LocName	MAY	MAY	NO	NO
LocURI	MUST	MUST	YES	YES
MsgID	MUST	MUST	YES	YES
MsgRef	MUST	MUST	YES	YES
NoResp	MAY	MUST	NO	YES
NoResults	MAY	MAY	NO	NO
RespURI	MAY	MUST	NO	YES
SessionID*	MUST	MUST	YES	YES
SftDel	MAY	MAY	NO	NO
Source	MUST	MUST	YES	YES
SourceRef	MUST	MUST	YES	YES
Target	MUST	MUST	YES	YES
TargetRef	MUST	MUST	YES	YES
VerDTD	MUST	MUST	YES	YES
VerProto	MUST	MUST	YES	YES

^{*}The maximum length of a SessionID is 4 bytes. Note that a client having an 8 bit incrementing SessionID counter is enough for practical implementations.

4.2 Representation Message container elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Message Container elements.

Command	Required of Client		Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
SyncML	MUST	MUST	YES	YES
SyncHdr	MUST	MUST	YES	YES
SyncBody	MUST	MUST	YES	YES



4.3 Data description elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Data Description elements.

Command	Required of Client		Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
Data	MUST	MUST	YES	YES
Item	MUST	MUST	YES	YES
Meta	MUST	MUST	YES	YES

4.4 Representation Protocol command elements

This section contains the ICS Proforma for the Static Conformance Requirements for the Protocol Command elements.

Command	Required of Client		Implemented in Client	
	Sending	Receiving	Sending	Receiving
Add	SHOULD	MUST	YES	YES
Alert	MUST	MUST	YES	YES
Atomic	MAY	MAY	NO	NO
Copy	MAY	MAY	NO	NO
Delete	MUST	MUST	YES	YES
Exec	MAY	MAY	NO	NO
Get*	SHOULD	MUST	YES	YES
Map	MUST	MAY	YES	NO
MapItem	MUST	MAY	YES	NO
Put*	MUST	MUST	YES	YES
Replace	MUST	MUST	YES	YES
Result*	MUST	SHOULD	YES	YES
Search	MAY	MAY	NO	NO
Sequence	MAY	MAY	NO	NO
Status	MUST	MUST	YES	YES
Sync	MUST	MUST	YES	YES

^{*}Minimum requirement for a SyncML device is to support Put, Get, and Result when exchanging device information.

4.5 Device Info

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Device Information.

Element Type	Required of Client		Implemen	ted in Client
	Sending	Receiving	Sending	Receiving
CTCap	MUST	SHOULD	YES	NO
CTType	MUST	MUST	YES	YES
DataStore	MUST	MUST	YES	YES
DataType	MAY	MAY	NO	NO
DevId	MUST	MUST	YES	YES
DevInf	MUST	MUST	YES	YES
DevTyp	MUST	MUST	YES	YES
DisplayName	MAY	MAY	NO	NO
DSMem	SHOULD	MAY	YES	NO

Copyright © 2000-2002 Ericsson, IBM, Lotus, Matsus hita Communication Industrial Co., Ltd., Motorola, Nokia, Openwave, Palm, Inc., Psion, Starfish Software, Symbian. All Rights Reserved.

13 of 18 Pages Version 2.0

2002-10-22

Ext	MAY	MAY	NO	NO
FwV	SHOULD	MAY	NO	NO
HwV	SHOULD	MAY	NO	NO
Man	SHOULD	MAY	NO	NO
MaxGUIDSize	MUST	MUST NOT	YES	YES
MaxID	SHOULD	MAY	NO	NO
MaxMem	SHOULD	MAY	NO	NO
Mod	MAY	MAY	NO	NO
OEM	MAY	MAY	NO	NO
ParamName	SHOULD	SHOULD	YES	NO
PropName	MUST	SHOULD	YES	NO
Rx	MAY	MUST	NO	YES
Rx-Pref	MUST	MUST	YES	YES
SharedMem	SHOULD	MAY	NO	YES
Size	MAY	MAY	NO	NO
SourceRef	MUST	MUST	YES	YES
SwV	SHOULD	MAY	NO	NO
SyncCap	MUST	MUST	YES	YES
SyncType	MUST	MUST	YES	YES
Tx	MAY	MUST	NO	YES
Tx-Pref	MUST	MUST	YES	YES
ValEnum	MUST	SHOULD	YES	NO
VerCT	MUST	MUST	YES	YES
VerDTD	MUST	MUST	YES	YES
Xnam	MAY	MAY	NO	NO
Xval	MAY	MAY	NO	NO

4.6 Meta Info

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Meta Information.

Element Type	Required	Required of Client		ted in Client
	Sending	Receiving	Sending	Receiving
Anchor	MUST	MUST	YES	YES
EMI	MAY	MAY	NO	NO
Format	MUST	MUST	YES	YES
FreeID	SHOULD	MAY	NO	NO
FreeMem	SHOULD	MAY	NO	NO
Last	MUST	MUST	YES	YES
Mark	MAY	MAY	NO	NO
MaxMsgSize	MAY	MUST	YES	YES
Mem	SHOULD	MAY	NO	NO
MetInf	MUST	MUST	YES	YES
Next	MUST	MUST	YES	YES
NextNonce	MAY	MUST	NO	YES
SharedMem	SHOULD	MAY	NO	NO
Size	MAY	MAY	NO	NO
Type	MUST	MUST	YES	YES
Version	MAY	MAY	NO	NO



4.7 Protocol

This section contains the ICS Proforma for the Static Conformance Requirements for the Sync Protocol.

Element Type	Client Requirements	
	Required	Implemented
Support of 'two-way sync'	MUST	YES
Support of 'slow two-way sync'	MUST	YES
Support of 'one -way sync from client only'	MAY	NO
Support of 'refresh sync from client only'	MAY	NO
Support of 'one -way sync from server only'	MAY	NO
Support of 'refresh sync from server only'	MAY	NO
Support of 'sync alert'	MAY	NO
Support of multiple messages per package	MUST	YES
Support of combined package 1 and 3	MAY	NO

4.8 Authentication

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML Authentication.

Note: that authentication is only required for SyncHdr, optional for datastore.

Authentication Type	Client Requirements	
	Required Implemente	
Basic (name and password)	MUST	YES
MD5	MUST	YES

4.9 MIME header types

This section contains the ICS Proforma for the Static Conformance Requirements for SyncML MIME Media Types.

Note: the client MUST support one of the two MIME header types.

MIME Header Type	Client Requirements	
	Required	Implemented
"application/vnd.syncml+xml"	MUST if no wbxml	YES
"application/vnd.syncml+wbxml"	MUST if no xml	NO



5 Transport Conformance

5.1 HTTP Transport

Vendors should fill this section out ONLY if their product uses the HTTP Transport.

NOTE that the tables only indicate the required data.

Method	Requirements	
	Required	Implemented
POST	MUST	YES

General Headers	Requi	Requirements	
	Required	Implemented	
Cache-Control: no-store, private	MUST	YES	
Transfer-Encoding: chunked	MUST	YES	

Request Headers	Requ	Requirements	
	Required	Implemented	
Accept	MUST	YES	
Accept-Charset	MUST	YES	
Authorization	MUST	YES	
Proxy-Authorization	MUST if a proxy client	NO	
User-Agent	MUST	YES	

Response Headers	Requi	Requirements	
	Required	Implemented	
Authentication-Info	MUST	YES	
Proxy-Authenticate	MUST if proxy client	NO	
WWW-Authenticate	MUST	YES	



5.2 **OBEX Transport**

Vendors should fill this section out ONLY if their product uses the OBEX Transport

Note that these definitions of client and server are the OBEX definition, not the SyncML definition.

NOTE that the tables only indicate the required data.

Method	OBEX Serve	OBEX Server Requirements	
	Required	Implemented	
GET	MUST		
PUT	MUST		
CONNECT	MUST		
DISCONNECT	MUST		
ABORT	MUST		

Method	OBEX Client Requirements	
	Required	Implemented
GET	MUST	
PUT	MUST	
CONNECT	MUST	
DISCONNECT	MUST	

5.3 WSP Transport

Vendors should fill this section out ONLY if their product uses the WSP Transport.

NOTE that the tables only indicate the required data.

Method	Requi	Requirements	
	Required	Implemented	
POST	MUST		

17 of 18 Pages Version 2.0 2002-10-22

6 Additional Information

Please use this section to provide any additional information with regards to your Implement Conformance Statement. Please do not annotate the previous sections.	ation

18 of 18 Pages Version 2.0 2002-10-22

7 References

- [1] SyncML Representation Protocol, version 1.0.1
- [2] SyncML Sync Protocol, version 1.0.1
- [3] SyncML Meta-Information DTD, version 1.0.1
- [4] SyncML Device Information DTD, version 1.0.1
- [5] SyncML HTTP Binding, version 1.0.1
- [6] SyncML OBEX Binding, version 1.0.1
- [7] SyncML WSP Binding, version 1.0.1