



**WAP-120-UACACH-20010413-a**

Version 013-APR-2001

---

for

Wireless Application Protocol  
WAP-120-UACACH-19990211-a

User Agent Caching Model

Version 011-FEB-1999

WAP Forum™ members have agreed to use reasonable endeavors to disclose in a timely manner to the WAP Forum the existence of all intellectual property rights (IPR's) essential to the present document. The members do not have an obligation to conduct IPR searches. This information is publicly available to members and non-members of the WAP Forum and may be found on the "WAP IPR Declarations" list at <http://www.wapforum.org>. Essential IPR is available for license on the basis set out in the schedule to the WAP Forum Application Form.

No representations or warranties (whether express or implied) are made by the WAP Forum™ or any WAP Forum member or its affiliates regarding any of the IPR's represented on this list, including but not limited to the accuracy, completeness, validity or relevance of the information or whether or not such rights are essential or non-essential.

A list of errata and updates to this document is available from the WAP Forum™ Web site (<http://www.wapforum.org/>) in the form of SIN documents, which are subject to revision or removal without notice.

© 2001, Wireless Application Forum, Ltd. All rights reserved.

Terms and conditions of use are available from the WAP Forum™ Web site at <http://www.wapforum.org/docs/copyright.htm>.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. You may not use this document in any other manner without the prior written permission of the WAP Forum™. The WAP Forum™ authorises you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services offered by you.

The WAP Forum™ assumes no responsibility for errors or omissions in this document. In no event shall the WAP Forum™ be liable for any special, indirect or consequential damages or any damages whatsoever arising out of or in connection with the use of this information.

This document is available online in PDF format at <http://www.wapforum.org/>.

Known problems associated with this document are published at <http://www.wapforum.org/>.

Comments regarding this document can be submitted to the WAP Forum™ in the manner published at <http://www.wapforum.org/>.

<b>Document History</b>		
WAP-120-UACACH	11-FEB-1999	June 2000 release
WAP-120.100-UACACH	14-SEP-2000	
WAP-120.101-UACACH	13-DEC-2000	
<b>WAP-120-UACACH</b>	13-APR-2001	Current – rolls up 100,101 and reformats SCR table to match WIG format

# Contents

<b>1. SCOPE</b> .....	<b>5</b>
<b>2. REFERENCES</b> .....	<b>6</b>
2.1. NORMATIVE REFERENCES .....	6
2.2. INFORMATIVE REFERENCES.....	6
<b>3. DEFINITIONS AND ABBREVIATIONS</b> .....	<b>7</b>
3.1. DEFINITIONS.....	7
3.2. ABBREVIATIONS.....	7
<b>4. CACHING MODEL</b> .....	<b>8</b>
4.1. WAP USER AGENT RESPONSIBILITIES .....	8
4.1.1. <i>Interaction with the User Agent History Mechanism</i> .....	8
4.1.2. <i>Intra-Resource Navigation</i> .....	8
4.2. WAP GATEWAY RESPONSIBILITIES .....	8
4.2.1. <i>Time-of-Day</i> .....	8
4.2.2. <i>Caching Proxy</i> .....	8
<b>5. TIME OF DAY CLOCK</b> .....	<b>9</b>
5.1. TOD REQUESTS .....	9
5.2. USER AGENT TOD CLOCK.....	9
<b>6. SECURITY CONSIDERATIONS</b> .....	<b>10</b>
<b>APPENDIX A. STATIC CONFORMANCE REQUIREMENTS</b> .....	<b>11</b>
<b>APPENDIX B. CHANGE HISTORY</b> .....	<b>12</b>

# 1. Scope

Wireless Application Protocol (WAP) is a result of continuous work by the WAP Forum to define an industry-wide specification for developing applications that operate over wireless communication networks. The scope of the WAP Forum is to define a set of specifications to be used by wireless communication device service applications. The wireless market is growing very quickly and reaching new customers and services. To enable operators and manufacturers to meet the challenges in advanced services, differentiation and fast/flexible service creation, WAP defines a set of protocols in transport, session and application layers. For additional information on the WAP architecture, refer to "*Wireless Application Protocol Architecture Specification*" [WAP].

This specification defines the caching model for the WAP user agent. The WAP user agent caching model is an implementation of the HTTP/1.1 caching model used on the World Wide Web. The design is intended to allow the adoption of the HTTP/1.1 caching model with no loss of semantics or function while providing support for low-end WAP phones. See [RFC2616] for more information on HTTP/1.1 caching.

This specification addresses the following issues:

- User agent caching of resources fetched from the network. This may include WML decks, WMLScript compilation units, or any other resources named with a URL and fetched over WSP.
- WAP Gateway behavior – the role and responsibility of the WAP Gateway in the implementation of reliable caching.
- Support infrastructure needed to implement HTTP/1.1 caching on a WAP user agent.

## 2. References

### 2.1. Normative References

- [CREQ] "Specification of WAP Conformance Requirements". WAP Forum™. WAP-221-CREQ.  
URL:<http://www.wapforum.org/>
- [RFC2119] "Key words for use in RFCs to Indicate Requirement Levels". S. Bradner. March 1997.  
URL:<http://www.ietf.org/rfc/rfc2119.txt>
- [RFC2234] "Augmented BNF for Syntax Specifications: ABNF". D. Crocker, Ed., P. Overell. November 1997. URL:<http://www.ietf.org/rfc/rfc2234.txt>
- [RFC2616] "Hypertext Transfer Protocol - HTTP/1.1", R. Fielding, et al., June 1999.  
URL: <http://www.ietf.org/rfc/rfc2616.txt>
- [NTP] "Network Time Protocol, Version 3, Specification Implementation and Analysis", D. Mills, University of Delaware, March 1992. URL: <ftp://ftp.isi.edu/in-notes/rfc1305.txt>
- [WAE] "Wireless Application Environment Specification", WAP-190-WAESPEC, WAP Forum, 29-MAR-2000. URL: <http://www.wapforum.org/>
- [WSP] "Wireless Session Protocol", WAP-203-WSP, WAP Forum, 4-MAY-2000. URL: <http://www.wapforum.org/>

### 2.2. Informative References

- [WML] "Wireless Markup Language", WAP-191-WML, WAP Forum, 19-FEB-2000.  
URL:<http://www.wapforum.org/>

## 3. Definitions and Abbreviations

### 3.1. Definitions

The following are terms and conventions used throughout this specification.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY" and "OPTIONAL" in this document are to be interpreted as described in [RFC2119]. In the absence of any such terms, the specification is to be interpreted as "MUST".

**Cache** - a device's local store of response messages and the subsystem that controls its message storage, retrieval and deletion. A cache stores cachable responses in order to reduce the response time and network bandwidth consumption on future, equivalent requests.

**Content** - subject matter (data) stored or generated at an origin server. Content is typically displayed or interpreted by a user agent in response to a user request.

**Origin Server** - the server on which a given resource resides or is to be created. Often referred to as a web server or an HTTP server.

**Request** - a WSP request (see [WSP]). Also known as a "WSP method request".

**Response** - a WSP response (see [WSP]).

**Resource** - a network data object or service that can be identified by a URL. Resources may be available in multiple representations (eg, multiple languages, data formats, size and resolutions) or vary in other ways.

**User** - a user is a person who interacts with a user agent to view, hear or otherwise use a resource.

**User Agent** - a user agent is any software or device that interprets resources. This may include textual browsers, voice browsers and search engines.

### 3.2. Abbreviations

<b>HTTP</b>	Hypertext Transfer Protocol [RFC2616]
<b>RFC</b>	Request For Comments
<b>TOD</b>	Time Of Day
<b>URI</b>	Universal Resource Identifier
<b>URL</b>	Universal Resource Locator
<b>W3C</b>	World Wide Web Consortium
<b>WAE</b>	Wireless Application Environment [WAE]
<b>WAP</b>	Wireless Application Protocol <b>Error! Reference source not found.</b>
<b>WSP</b>	Wireless Session Protocol [WSP]
<b>WML</b>	Wireless Markup Language [WML]

>>

## 4. Caching Model

The WAP caching model is based on HTTP/1.1 caching as defined in [RFC2616]. In addition, a number of extensions and clarifications have been specified to facilitate the operation of HTTP/1.1 caching on limited function devices.

This document applies to all WAP user agents, including those with no cache (i.e., a zero byte cache).

### 4.1. WAP User Agent Responsibilities

The user agent MUST faithfully implement resource caching as described in [RFC2616].

#### 4.1.1. Interaction with the User Agent History Mechanism

The interaction between the user agent cache and the WML history is controlled by the `Cache-control: must-revalidate` header. When going "back" to a URI (e.g., a WML `PREV` task), the user agent should attempt to use the cached resource. The browser must support the following interaction between cached resources and the WML history:

- If the cached resource has the `must-revalidate` cache control attribute set, and the cached resource is stale, then the user agent must revalidate the resource when going "back" in the history. The original request must be made in precisely the same way (e.g., the same method, the same request entity if a `POST`, etc.). This re-fetch must occur without any user interaction.
- If the cached resource does not have the `must-revalidate` cache control attribute, and the cached resource is stale, the user agent must not revalidate the entity when doing "back" in the history.

In other words, the history normally shows the way things were at the time the user retrieved the resource. If the `must-revalidate` attribute is set on a resource, the history will show the "up-to-date" version of the resource.

#### 4.1.2. Intra-Resource Navigation

Navigation and processing within a single cached resource does not require revalidation unless the content type specifies some other cache validation model. For example:

- Function calls within a single WMLScript compilation unit may occur without revalidation. Only the initial fetch of the compilation unit requires a check of the resource validity.
- Intra-deck navigation within a single WML deck may occur without revalidation. Only the initial fetch of the deck requires a check of the resource validity.

### 4.2. WAP Gateway Responsibilities

The WAP Gateway must faithfully implement the role of an HTTP/1.1 proxy with respect to caching and cache header transmission. See [RFC2616] for more information.

#### 4.2.1. Time-of-Day

The HTTP/1.1 caching model is somewhat sensitive to a loss of time synchronisation. The WAP Gateway should maintain a reliable time-of-day clock, and it is recommended that NTP (or an equivalent) be used by the WAP Gateway to maintain a reliable real-time base. See [NTP] for more information.

#### 4.2.2. Caching Proxy

If the WAP Gateway caches its WSP responses, it will fulfil the role of an HTTP/1.1 caching proxy.



## 5. Time of Day Clock

The HTTP/1.1 caching model has built-in assumptions about the existence of a time-of-day (TOD) clock in the user agent, and even suggests in section 13.2.3 of [RFC2616] that the client should use NTP [NTP] to synchronise its clock with the origin server. It is clear that many WAP user agents will not have access to a time-of-day clock, and even fewer will have need of a high-quality time synchronisation protocol such as NTP. However, nearly all wireless communication devices have a real-time clock, and are capable of maintaining a reasonable sense of the TOD when given a means to synchronise their clocks to an outside source.

### 5.1. TOD Requests

The WAP Gateway must support requests for the current time of day. When the gateway receives a WSP method request that includes a header named `X-WAP-TOD`, it will include that header in the response, with the header value set to the Gateway's current time of day. See [WSP] for the format of the `X-WAP-TOD` header.

### 5.2. User Agent TOD Clock

If the user agent lacks an accurate TOD clock, it should use the response from a TOD request as the basis for synchronising its real-time clock with the WAP Gateway. For further accuracy, the user agent should estimate the round-trip time of the request, and add one-half of this value from the TOD response value.

It is recommended that user agents containing a TOD clock use this mechanism as a means of determining the skew between the device clock and the network time base.

## 6. Security Considerations

The storage of sensitive information in non-volatile storage raises a variety of security considerations. Implementers must ensure that private information in the user agent cache is protected from unintended or malicious access. WAP Gateways implementing a caching function must obey all security-related considerations defined in [RFC2616].

## Appendix A. Static Conformance Requirements

### Client

Item	Function	Reference	Status	Requirement
UACache-C-001	Implement HTTP caching model, as described in [RFC2616]	4.1	M	
UACache-C-002	Revalidate stale cache resources when Cache Control header has a value of must-revalidate.	4.1.1	M	
UACache-C-003	Does not revalidate stale cache resources when Cache-Control header does not have a value of must-revalidate.	4.1.1	M	
UACache-C-004	No revalidation on intra resource navigation, including WMLScript intra-compilation unit function call, WML intra-deck navigation.	4.1.2	M	
UACache-C-005	Time base is synchronized with Gateway.	5.2	O	
UACache-C-006	Cache contents protected from malicious or unintended access.	6	M	

### Server

Item	Function	Reference	Status	Requirement
UACache-S-007	Implement HTTP caching model, as described in [RFC2616]	4.2	M	
UACache-S-008	Time base is synchronized with NTP.	4.2.1	O	
UACache-S-009	Caching of WSP responses in WAP gateway follow HTTP proxy semantics	4.2.2	M	
UACache-S-010	Gateway support for x-wap-tod header in WSP requests.	5.1	M	
UACache-S-011	Gateway obeys security considerations for caching outlined in [RFC2616].	6	M	

## Appendix B. Change History

This appendix is informative.

Change Request	Title	Comments	SIN/SCD
WAG-IBM-20000209-MustDefinition	Add to Definition of Key Words	Clarifies use of [RFC2119] terminology in section 4.1.	WAP-120.100-UACACH
UACache-IBM-20000912-xwaptod	Point to [WSP] Definition of X-WAP.TOD Header	Modifies section 6.1 to point to [WSP] for the format of the header.	WAP-120.100-UACACH
	Static Conformance Requirements	The WAE Caching Static Conformance Requirements document, previously known as PROTO-WAPCachingModSCR11-19990602, is incorporated into this document.	WAP-120.100-UACACH
	TOD Requests	TOD Requests	WAP-120.100-UACACH
WAEALL13-IBM-20001107-HTTPPref	HTTP Normative Reference	<ul style="list-style-type: none"> <li>Updates the WAE 1.x suite to refer to [RFC2616] instead of RFC2068.</li> </ul>	WAP-120.101-UACACH
	Request from WIG to update SCRs in line with Conformance Requirements defined in WAP-221-CREQ [CREQ]	Changes consist of <ul style="list-style-type: none"> <li>Adding Interspec dependency requirement boxes.</li> <li>Using [RFC2616] in SCRs as required from WAP-120.101-UACaching-20001213</li> </ul>	WAP-120.101-UACACH

