



# **Device Management Meta Information**

## **Candidate Version 1.3 – 06 Mar 2012**

---

**Open Mobile Alliance**  
OMA-TS-DM\_MetalInfo-V1\_3-20120306-C

Use of this document is subject to all of the terms and conditions of the Use Agreement located at <http://www.openmobilealliance.org/UseAgreement.html>.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile Alliance™ specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the “OMA IPR Declarations” list at <http://www.openmobilealliance.org/ipr.html>. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

**NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE “OMA IPR DECLARATIONS” LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.**

**THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.**

© 2012 Open Mobile Alliance Ltd. All Rights Reserved.

Used with the permission of the Open Mobile Alliance Ltd. under the terms set forth above.

# Contents

1. SCOPE .....	4
2. REFERENCES .....	5
2.1 NORMATIVE REFERENCES .....	5
2.2 INFORMATIVE REFERENCES .....	5
3. TERMINOLOGY AND CONVENTIONS .....	6
3.1 CONVENTIONS .....	6
3.2 DEFINITIONS .....	6
3.3 ABBREVIATIONS .....	6
4. INTRODUCTION .....	7
5. META INFORMATION .....	8
5.1 XML USAGE .....	8
5.2 ELEMENT TYPE DESCRIPTIONS .....	8
5.2.1 Anchor .....	8
5.2.2 EMI .....	8
5.2.3 FieldLevel .....	9
5.2.4 Format .....	9
5.2.5 FreeID .....	9
5.2.6 FreeMem .....	10
5.2.7 Last .....	10
5.2.8 Mark .....	10
5.2.9 MaxMsgSize .....	10
5.2.10 MaxObjSize .....	11
5.2.11 Mem .....	11
5.2.12 MetInf .....	11
5.2.13 Next .....	12
5.2.14 NextNonce .....	12
5.2.15 SharedMem .....	12
5.2.16 Size .....	12
5.2.17 Type .....	13
5.2.18 Version .....	13
6. DTD DEFINITION .....	14
7. WBXML DEFINITION .....	16
7.1 CODE SPACE AND CODE PAGE DEFINITIONS .....	16
7.2 TOKEN DEFINITIONS .....	16
APPENDIX A. CHANGE HISTORY (INFORMATIVE) .....	17
A.1 APPROVED VERSION HISTORY .....	17
A.2 DRAFT/CANDIDATE VERSION 1.3 HISTORY .....	17
APPENDIX B. STATIC CONFORMANCE REQUIREMENTS (NORMATIVE) .....	18
B.1 SCR FOR CLIENT META INFORMATION .....	18
B.2 SCR FOR SERVER META INFORMATION .....	18

# 1. Scope

This document outlines the DM Meta Information Specification and the respective conformance requirements for DM Clients and DM Servers.

## 2. References

### 2.1 Normative References

- [DMDICT] “OMA Device Management Dictionary, Version 1.0”. Open Mobile Alliance™.  
OMA-SUP-DM\_Dictionary-v1\_0.  
[URL:http://www.openmobilealliance.org/](http://www.openmobilealliance.org/)
- [DMREPRO] “DM Representation Protocol”, Open Mobile Alliance™,  
OMA-TS-DM\_RepPro-V1\_3,  
[URL:http://www.openmobilealliance.org/](http://www.openmobilealliance.org/)
- [ISO8601] “Data elements and interchange formats -- Information interchange -- Representation of dates and times”,  
ISO 8601:2000,  
[URL:http://www.iso.ch](http://www.iso.ch)
- [RFC2045] “Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies”, N. Freed  
& N. Borenstein, November 1996,  
[URL:http://www.ietf.org/rfc/rfc2045.txt](http://www.ietf.org/rfc/rfc2045.txt)
- [RFC2119] “Key words for use in RFCs to Indicate Requirement Levels”, S. Bradner, March 1997,  
[URL:http://www.ietf.org/rfc/rfc2119.txt](http://www.ietf.org/rfc/rfc2119.txt)
- [SCRRULES] “SCR Rules and Procedures”, Open Mobile Alliance™, OMA-ORG-SCR\_Rules\_and\_Procedures,  
[URL:http://www.openmobilealliance.org/](http://www.openmobilealliance.org/)
- [SYNCMLMETA] “SyncML Meta Information”, Open Mobile Alliance™,  
OMA-TS-SyncML\_Meta-V1\_2,  
[URL:http://www.openmobilealliance.org/](http://www.openmobilealliance.org/)
- [WBXML] “WAP Binary XML Content Format Specification”, WAP Forum™, WAP-154-WBXML,  
[URL:http://www.openmobilealliance.org/](http://www.openmobilealliance.org/)
- [XML] “Extensible Markup Language (XML) 1.0”, World Wide Web Consortium Recommendation,  
[URL:http://www.w3.org/TR/REC-xml](http://www.w3.org/TR/REC-xml)
- [XMLSCHEMADT] “XML Schema Part 2: Datatypes Second Edition”, World Wide Web Consortium Recommendation,  
[URL:http://www.w3.org/TR/REC-xml](http://www.w3.org/TR/REC-xml)

### 2.2 Informative References

- [METADTD] “SyncML Meta Information, Document Type Definition”, Open Mobile Alliance™,  
OMA-TS-SyncML\_MetaInfo\_DTD-V1\_3,  
[URL:http://www.openmobilealliance.org/](http://www.openmobilealliance.org/)

## 3. Terminology and Conventions

### 3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

Any reference to components of the DM DTD or XML snippets is specified in this typeface.

### 3.2 Definitions

Kindly consult [DMDICT] for all definitions used in this document.

### 3.3 Abbreviations

Kindly consult [DMDICT] for all abbreviations used in this document.

## 4. Introduction

The meta-information associated with a DM command or data item is represented in a mark-up language defined by [XML]. The meta-information is identifiable as an XML name space. The DM Meta-Information DTD (Document Type Definition) defines the XML document type used to represent meta-information used in the DM representation protocol [DMREPRO].

## 5. Meta Information

### 5.1 XML Usage

The DM Meta-Information XML documents are specified using well-formed XML. However, they need not be valid XML. That is, they do not need to specify the XML prolog. They only need to specify properly identified name space element types from the DM Meta-Information DTD. This restriction allows for the DM Meta-Information to be specified with greater terseness than would be possible if a well-formed, valid XML document was REQUIRED.

This DTD makes heavy use of XML name spaces. Name spaces MUST be declared on the first element type that uses an element type from the name space. Element types from the DM Meta-Information DTD can be used in other XML documents, including a DM Message.

Names in XML are case sensitive. By convention in the DM Meta-Information DTD, the element type and attribute list names are specified with a "Hungarian" like notation of the first character in each word of the name in upper case text and remainder of the characters in each word of the names specified in lower case text. For example, `MetInf` for the Sync meta-information root element type or `Type` for the content type tag.

The element types in the DM Meta-Information DTD [METADTD] are defined within a namespace associated with the URI or the URN `syncml:metinf`.

DM also makes use of XML standard attributes, such as `xml:lang`. Any XML standard attribute can be used in a XML document conforming to this DTD.

XML can be viewed as more verbose than alternative binary representations. This is often cited as a reason why it might not be appropriate for low bandwidth network protocols. In most cases, this DTD uses shortened element type and attribute names. This provides a minor reduction in verbosity. Additionally, the DM Meta-Information can be encoded in a tokenized, binary format defined by [WBXML]. The use of [WBXML] format is external to specification of the DTD and transparent to any XML application

One of the main advantages of XML is that it is a widely accepted International recommendation for text document mark-up. It provides for both human readability and machine processability. In addition, XML allows the originator to capture the structure of a document, not just its content. This is extremely useful for applications such as data synchronization, where not just content, but structure semantics is often exchanged.

## 5.2 Element Type Descriptions

### 5.2.1 Anchor

**Restrictions by DM:** This element is not used in OMA Device Management Protocol. Please refer to [SYNCMLMETA] for detail information.

### 5.2.2 EMI

**Usage:** Specifies the non-standard, experimental meta information (EMI) extensions supported by the device. The extensions are specified in terms of the XML element type name and the value.

**Parent Elements:** `MetInf`

**Restrictions:** The EMI element type MUST specify the extension element name. It MAY also specify one or more enumerated values. Multiple non-standard extensions can be specified by specifying the EMI element type multiple times. This element type is OPTIONAL.

**Content Model:**



```
(#PCDATA)
```

**Attributes:** None.

**Example:** The following example specifies a non-standard extension with a value of "Confidential".

```
<EMI xmlns='syncml:metinf'>Confidential</EMI>
```

### 5.2.3 FieldLevel

**Restrictions by DM:** This element is not used in OMA Device Management Protocol. Please refer to [SYNCMLMETA] for detail information.

### 5.2.4 Format

**Usage:** Specifies the encoding format of the content information in the Data element.

**Parent Elements:** MetInf

**Restrictions:** The value of this element SHOULD be one of bin, bool, b64, chr, int, node, null, xml, date, time, or float. If the element type is missing, the default value is chr. If the value is bin, then the format of the content is binary data. If the value is bool, then the encoding of the content is either case sensitive "true" or case sensitive "false." If the value is b64, then the format of the content information is binary data that has been character encoded using the Base64 transfer encoding defined by [RFC2045]. If the value is chr, then the format of the content information is clear-text in the character set specified on either the transport protocol, the MIME content type header or the XML prolog. If the value is int, then the format of the content information is numeric text representing the integer. If the value is node, then the content represents an interior object in the management tree. If the value is null, then there is no content information. This value is used by some synchronization data models to delete the content, but not the presence of the property. If the value is xml, then the format of the content information is XML structured mark-up data. If the value is date, then the format of the content is in ISO 8601 format with the century being included in the year [ISO8601]. If the value is time, then the format of the content is in ISO 8601 format. If the value is float, then the format of the content is standard concept of real numbers corresponding to a single precision 32 bit floating point type as defined in XML Schema 1.0 as the float primitive type [XMLSCHEMADT].

In case a Meta element containing a Format element contains meta-information about a Data object, this Meta element MUST have the same parent as the Data object it refers to.

The target object is the one in which the meta-information appears.

**Content Model:**

```
(#PCDATA)
```

**Attributes:** None.

**Example:** The following example illustrates how the element type is used within the DM DTD to specify format meta-information for data in the Item element type.

```
<Item>
  <Meta>
    <Format xmlns='syncml:metinf'>int</Format>
  </Meta>
  <Data>1024</Data>
</Item>
```

### 5.2.5 FreeID

**Restrictions by DM:** This element is not used in OMA Device Management Protocol. Please refer to [SYNCMLMETA] for detail information.

## 5.2.6 FreeMem

**Restrictions by DM:** This element is not used in OMA Device Management Protocol. Please refer to [SYNCMLMETA] for detail information.

## 5.2.7 Last

**Restrictions by DM:** This element is not used in OMA Device Management Protocol. Please refer to [SYNCMLMETA] for detail information.

## 5.2.8 Mark

**Usage:** Specifies the importance level of the content information in the Data element.

**Parent Elements:** MetInf

**Restrictions:** The value of this element SHOULD be one of “fatal”, “critical”, “minor”, “warning”, “informational”, “harmless”, “indeterminate”. Their order indicates the importance level with “fatal” being the most important and “indeterminate” being the least important.

**Content Model:**

```
(#PCDATA)
```

**Attributes:** None.

**Example:**

```
<Mark xmlns='syncml:metinf'>critical</Mark>
```

## 5.2.9 MaxMsgSize

**Usage:** Specifies the maximum byte size of any response message to a given SyncML request.

**Parent Elements:** MetInf .

**Restrictions:** The element type appears in the Meta element in the SyncHdr of a SyncML request to specify the maximum size of any subsequent response messages. The element type is usually specified by a SyncML client, but can also be specified by a SyncML server.

This element type value is applicable for the remainder of the synchronization session, unless it is specified again.

The element type value is the text string representation of the maximum, decimal byte size of any response message.

In order to use the elements from the MetInf name space, the root element does not need to be specified.

**Content Model:**

```
(#PCDATA)
```

**Attributes:** None.

**Example:** Normally, the root element type does not appear in a SyncML Meta element type.

```
<MaxMsgSize xmlns='syncml:metinf'>1023</MaxMsgSize>
```

## 5.2.10 MaxObjSize

**Usage:** Specifies the maximum size in bytes of a data object that the device is able to receive.

**Parent Elements:** MetInf.

**Restrictions:** The element type appears in the Meta element of a SyncML request to specify the maximum size of the largest object it is capable of receiving in any subsequent response messages. This element type value is applicable for the remainder of the synchronization session.

The element type value is the text string representation of the maximum, decimal byte size without leading zeroes of any object.

In order to use the elements from the MetInf name space, the root element does not need to be specified.

**Content Model:**

```
(#PCDATA)
```

**Attributes:** None.

**Example:** Device that can receive a maximum object of 10K bytes.

```
<MaxObjSize xmlns='syncml:metinf'>10240</MaxObjSize>
```

## 5.2.11 Mem

**Restrictions by DM:** This element is not used in OMA Device Management Protocol. Please refer to [SYNCMLMETA] for detail information.

## 5.2.12 MetInf

**Usage:** Specifies the root element for the SyncML meta-information document.

**Parent Elements:** Root element type.

**Restrictions:** In order to use the elements from the MetInf name space, the root element does not need to be specified. The element type can appear in the Meta element of a SyncML document to allow for declaring a default name space.

**Content Model:**

```
MetInf (FieldLevel?, Format?, Type?, Size?, Anchor?, Version?, NextNonce?,
MaxMsgSize?, MaxObjSize?, EMI*, Mem?)
```

**Attributes:** None.

**Example:** Normally, the root element type does not appear in a SyncML Meta element type.

```
<MetInf xmlns='syncml:metinf'>
  <FieldLevel/>
  <Type xmlns='syncml:metinf'>x-type/x-subtype</Type>
  <Format xmlns='syncml:metinf'>chr</Format>
  <Size xmlns='syncml:metinf'>877566</Size>
  <Version xmlns='syncml:metinf'>20000714T082300Z</Version>
</MetInf>
```

### 5.2.13 Next

**Restrictions by DM:** This element is not used in OMA Device Management Protocol. Please refer to [SYNCMLMETA] for detail information.

### 5.2.14 NextNonce

**Usage:** Specifies the nonce string to be used in any subsequent communication.

**Parent Elements:** `MetInf`

**Restrictions:** The nonce string **MUST** be further re-formatted using the Base64 algorithm. Terminators or length of Nonce String **MUST NOT** be included in this re-formatting. The Nonce string **MUST** be treated as opaque data.

This element type is used to specify the next nonce string that is to be used in any subsequent SyncML message. For example, a SyncML server specifies this element type to tell the SyncML client to change its nonce to a new value.

Nonce strings are used in the SyncML “SHA-256 Digest” or “MD5 Digest” scheme of authentication credentials.

**Content Model:**

```
(#PCDATA)
```

**Attributes:** None.

**Example:**

```
<Meta>
  <NextNonce
    xmlns='syncml:metinf'>QWxhZGRpbjpvcmVudHJlc2FtZQ==</NextNonce> </Meta>
```

### 5.2.15 SharedMem

**Restrictions by DM:** This element is not used in OMA Device Management Protocol. Please refer to [SYNCMLMETA] for detail information.

### 5.2.16 Size

**Usage:** Specifies the byte size of a data object.

**Parent Elements:** `MetInf`

**Restrictions:** The byte size is specified as the numeric text equivalent of the byte count of the data object. In case a `Meta` element containing a `Size` element contains meta-information about a `Data` object, this `Meta` element **MUST** have the same parent as the `Data` object it refers to

**Content Model:**

```
(#PCDATA)
```

**Attributes:** None

**Example:** The following example illustrates how the element type is used within the SyncML DTD to specify meta-information about the byte size of the `Item` element type.

```
<Item>
  <Target><LocURI>4</LocURI>
  <Meta>
    <Size xmlns='syncml:metinf'>10</Size>
```

```

</Meta>
<Data>John Smith</Data>
</Item>

```

### 5.2.17 Type

**Usage:** Specifies the media type of the content information in the Data element.

**Parent Elements:** MetInf

**Restrictions:** If this element is missing, then the default content-type is text/plain. The content information for this element type SHOULD BE a registered MIME content-type. Alternatively, a URN can be used to specify the media type. In case a Meta element containing a Type element contains meta-information about a Data object, this Meta element MUST have the same parent as the Data object it refers to.

**Content Model:**

```
(#PCDATA)
```

**Attributes:** None

**Example:** The following example illustrates how the element type is used within a SyncML message to specify meta-information about the media type of the content information in the Item element type.

```

<Item>
  <Target><LocURI>3</LocURI></Target>
  <Meta>
    <Type xmlns='syncml:metinf'>text/directory;profile=vCard</Type>
  </Meta>
  <Data>BEGIN:VCARD
VERSION:3.0 FN:Jim Smith N:Smith;Jim TEL;TYPE=WORK,VOICE,FAX:+1-919-555-
1234 EMAIL;TYPE=INTERNET,WORK:Jim_Smith@mail.host.com
END:VCARD
  </Data>
</Item>

```

### 5.2.18 Version

**Restrictions by DM:** This element is not used in OMA Device Management Protocol. Please refer to [SYNCMLMETA] for detail information.

## 6. DTD Definition

```

<!--
OMA DM Meta Information (SYNCML-METINF) V1.2 Document Type

This DTD defines a sequence of meta-information that is used within
the DM Representation Protocol DTD. Typical usage:

    <!DOCTYPE MetInf PUBLIC "-//OMA//DTD SYNCML-METINF 1.2//EN"
        "http://www.openmobilealliance.org/tech/DTD/OMA-TS-
DM_MetaInfo_DTD-V1_3.dtd"
        [<?oma-syncml-metinf-ver supported-versions="1.2"?>]>

    <element>
        ...
    </element>

Terms and conditions of use are available from the
Open Mobile Alliance Ltd. web site at
http://www.openmobilealliance.org/useterms.html
-->

<!-- Root Element -->
<!ELEMENT MetInf (FieldLevel?, Format?, Type?, Mark?, Size?, Anchor?,
Version?, NextNonce?, MaxMsgSize?, MaxObjSize?, EMI*, Mem?)>
<!-- FieldLevel change flag -->
<!ELEMENT FieldLevel EMPTY>
<!-- Format or encoding type -->
<!ELEMENT Format (#PCDATA)>
<!-- Element specific type specification -->
<!ELEMENT Type (#PCDATA)>
<!-- Mark -->
<!ELEMENT Mark (#PCDATA)>
<!-- Byte count -->

```

```
<!ELEMENT Size (#PCDATA)>
<!-- Data versioning info -->
<!ELEMENT Anchor (Last?, Next)>
<!ELEMENT Last (#PCDATA)>
<!ELEMENT Next (#PCDATA)>
<!ELEMENT Version (#PCDATA)>
<!ELEMENT NextNonce (#PCDATA)>
<!ELEMENT MaxMsgSize (#PCDATA)>
<!ELEMENT MaxObjSize (#PCDATA)>
<!-- Experimental Meta Information extension -->
<!ELEMENT EMI (#PCDATA)>
<!-- Dynamic Memory -->
<!ELEMENT Mem (SharedMem?, FreeMem, FreeID)>
<!-- Free Memory in the number of identifiers -->
<!ELEMENT FreeID (#PCDATA)>
<!-- Free Memory in bytes -->
<!ELEMENT FreeMem (#PCDATA)>
<!-- Shared Memory -->
<!ELEMENT SharedMem EMPTY>
<!-- End of DTD -->
```

## 7. WBXML Definition

The following tables define the token assignments for the mapping of the Meta-Information DTD element types into WBXML as defined by [WBXML].

### 7.1 Code Space and Code Page Definitions

This version of the SyncML representation protocol specification maps all the SyncML related DTDs into WBXML code spaces.

DTD Name	WBXML PUBLICID Token (Hex Value)	Formal public Identifier
SyncML1.2	0x01201	--//SYNCML//DTD SyncML 1.2//EN

The SyncML DTD is assigned the WBXML document public identifier (i.e., the "publicid" WBXML BNF production) associated with the 0x1201 token.

The element types from the Meta-Information DTD utilize the code page x01 (one) within the SyncML Code Space.

DTD Name	WBXML Code Page Token (Hex Value)	Formal Public Identifier
SyncML	00	--//SYNCML//DTD SyncML 1.2//EN
MetaInf	01	--//SYNCML//DTD MetInf 1.2//EN

### 7.2 Token Definitions

The following WBXML token codes represent element types (i.e., tags) form code page x01 (one), Meta-Information DTD.

Element Type Name	WBXML Tag Token (Hex Value)
Anchor	05
EMI	06
Format	07
FreeID	08
FreeMem	09
Last	0A
Mark	0B
MaxMsgSize	0C
Mem	0D
MetInf	0E
Next	0F
NextNonce	10
SharedMem	11
Size	12
Type	13
Version	14
MaxObjSize	15
FieldLevel	16



## Appendix A. Change History

(Informative)

### A.1 Approved Version History

Reference	Date	Description
N/A	N/A	No prior 1.3 version

### A.2 Draft/Candidate Version 1.3 History

Document Identifier	Date	Sections	Description
Draft Versions OMA-TS-SyncML_MetaInfo-V1_3	27 Aug 2009	All	New baseline using OMA-TS-SyncML-MetaInfo-V1_2_1
	25 Nov 2009	All	Applied OMA-DM-DM13-2009-0099R02-CR_MetaInfo_cleanup
Draft Versions OMA-TS-DM_MetaInfo-V1_3	08 Jan 2010	All	General editorial clean-up by DSO
	04 May 2010	5.1, App B	Correction of a misspelling error. Fixed one reference in App B
	05 May 2010	All	Changed snippets front from Courier to Courier New to harmonize with the rest of the document Fixed broken cross-references
Candidate Version OMA-TS-DM_MetaInfo-V1_3	25 May 2010	N/A	Status changed to Candidate by TP Ref # OMA-TP-2010-0221- INP_DM_V1.3_ERP_and_ETR_for_Candidate_approval
Draft Versions OMA-TS-DM_MetaInfo-V1_3	13 Jan 2012	2, 3	Applied OMA-DM-DM13-2011-0129R02-CR_CONR_Meta
	31 Jan 2012	2, 4, App B	Applied OMA-DM-DM13-2012-0015-CR_CONRR_MetaInfo_round_2 Applied 2012 template to introduction section. Restored cross-references in the whole document.
	23 Feb 2012	4.1	Header removed by DSO according to Action Item DM-2012-A030
Candidate Version OMA-TS-DM_MetaInfo-V1_3	06 Mar 2012	N/A	Status changed to Candidate by TP Ref # OMA-TP-2012-0084- INP_DM_V1_3_ERP_and_ETR_for_Candidate_re_approval

## Appendix B. Static Conformance Requirements (Normative)

The notation used in this appendix is specified in [SCRRULES].

### B.1 SCR for Client Meta Information

Item	Function	Reference	Requirement
DSDM-METINF-C-001-M	Support for Anchor element	Section 5.2.1	DSDM-METINF-C-007-M AND DSDM-METINF-C-013-M
DSDM-METINF-C-002-O	Support for EMI element	Section 5.2.2	
DSDM-METINF-C-003-O	Support for FieldLevel element	Section 5.2.3	
DSDM-METINF-C-004-M	Support for Format element	Section 5.2.4	
DSDM-METINF-C-005-O	Support for FreeID element	Section 5.2.5	
DSDM-METINF-C-006-O	Support for FreeMem element	Section 5.2.6	
DSDM-METINF-C-007-M	Support for Last element	Section 5.2.7	
DSDM-METINF-C-008-O	Support for Mark element	Section 5.2.8	
DSDM-METINF-C-009-O	Support for MaxMsgSize element	Section 5.2.9	
DSDM-METINF-C-010-O	Support for MaxObjSize element	Section 5.2.10	
DSDM-METINF-C-011-O	Support for Mem element	Section 5.2.11	DSDM-METINF-C-005-O AND DSDM-METINF-C-006-O AND DSDM-METINF-C-015-O
DSDM-METINF-C-012-M	Support for MetInf element	Section 5.2.12	DSDM-METINF-C-001-M AND DSDM-METINF-C-004-M AND DSDM-METINF-C-014-M AND DSDM-METINF-C-017-M AND DSDM-METINF-C-018-M
DSDM-METINF-C-013-M	Support for Next element	Section 5.2.13	
DSDM-METINF-C-014-M	Support for NextNonce element	Section 5.2.14	
DSDM-METINF-C-015-O	Support for SharedMem element	Section 5.2.15	
DSDM-METINF-C-016-O	Support for Size element	Section 5.2.16	
DSDM-METINF-C-017-M	Support for Type element	Section 5.2.17	
DSDM-METINF-C-018-M	Support for Version element	Section 5.2.18	

### B.2 SCR for Server Meta Information

Item	Function	Reference	Requirement
DSDM-METINF-S-001-M	Support for Anchor element	Section 5.2.1	DSDM-METINF-S-007-M AND DSDM-METINF-S-013-M
DSDM-METINF-S-002-O	Support for EMI element	Section 5.2.2	
DSDM-METINF-S-003-O	Support for FieldLevel element	Section 5.2.3	
DSDM-METINF-S-004-M	Support for Format element	Section 5.2.4	
DSDM-METINF-S-005-M	Support for FreeID element	Section 5.2.5	
DSDM-METINF-S-006-M	Support for FreeMem element	Section 5.2.6	
DSDM-METINF-S-007-M	Support for Last element	Section 5.2.7	
DSDM-METINF-S-008-O	Support for Mark element	Section 5.2.8	
DSDM-METINF-S-009-M	Support for MaxMsgSize element	Section 5.2.9	
DSDM-METINF-S-010-M	Support for MaxObjSize element	Section 5.2.10	
DSDM-METINF-S-011-M	Support for Mem element	Section 5.2.11	DSDM-METINF-S-005-M AND DSDM-METINF-S-006-M AND DSDM-METINF-S-015-M
DSDM-METINF-S-012-M	Support for MetInf element	Section 5.2.12	DSDM-METINF-S-001-M AND DSDM-METINF-S-004-M AND DSDM-METINF-S-009-M AND DSDM-METINF-S-010-M AND DSDM-METINF-S-011-M AND DSDM-METINF-S-014-M AND DSDM-METINF-S-017-M AND DSDM-METINF-S-018-M
DSDM-METINF-S-013-M	Support for Next element	Section 5.2.13	
DSDM-METINF-S-014-M	Support for NextNonce element	Section 5.2.14	
DSDM-METINF-S-015-M	Support for SharedMem element	Section 5.2.15	
DSDM-METINF-S-016-O	Support for Size element	Section 5.2.16	
DSDM-METINF-S-017-M	Support for Type element	Section 5.2.17	
DSDM-METINF-S-018-M	Support for Version element	Section 5.2.18	