



Lightweight M2M – Connectivity Management Object (LwM2M Object – ConnMgmt)

Candidate Version 1.0 – 13 Jan 2015

Open Mobile Alliance
OMA-TS-LWM2M_ConnMgmt-V1_0-20150113-C

Use of this document is subject to all of the terms and conditions of the Use Agreement located at <http://www.openmobilealliance.org/UseAgreement.html>.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile Alliance™ specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the “OMA IPR Declarations” list at <http://www.openmobilealliance.org/ipr.html>. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE “OMA IPR DECLARATIONS” LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.

THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.

© 2015 Open Mobile Alliance Ltd. All Rights Reserved.

Used with the permission of the Open Mobile Alliance Ltd. under the terms set forth above.

Contents

- 1. SCOPE.....4
- 2. REFERENCES5
 - 2.1 NORMATIVE REFERENCES.....5
 - 2.2 INFORMATIVE REFERENCES.....5
- 3. TERMINOLOGY AND CONVENTIONS6
 - 3.1 CONVENTIONS.....6
 - 3.2 DEFINITIONS.....6
 - 3.3 ABBREVIATIONS6
- 4. INTRODUCTION7
 - 4.1 VERSION 1.07
- 5. LWM2M OBJECT: CELLULAR NETWORK CONNECTIVITY8
- 6. LWM2M OBJECT: APN CONNECTION PROFILE.....9
- 7. LWM2M OBJECT: WLAN CONNECTIVITY12
- 8. LWM2M OBJECT: BEARER SELECTION16
- APPENDIX A. CHANGE HISTORY (INFORMATIVE).....18
 - A.1 APPROVED VERSION HISTORY18
 - A.2 DRAFT/CANDIDATE VERSION 1.0 HISTORY18
- APPENDIX B. EXAMPLE OBJECTS AND RESOURCES FOR LWM2M CLIENT19

Figures

No table of figures entries found.

Tables

- Table 1: Object Instances of the Example19
- Table 2: Cellular Network Connectivity Object19
- Table 3: APN Connection Profile Object [0]20
- Table 4: APN Connection Profile Object [1]20
- Table 5: WLAN Connectivity Object.....20
- Table 6: Bearer Selection Object.....21

1. Scope

This document defines a set of Objects to be used in conjunction with the Lightweight M2M enabler in order to manage connectivity at the device.

2. References

2.1 Normative References

- [3GPP-TS_23.203] 3GPP TS 23.203 “Policy and charging control architecture”
[URL:http://www.3gpp.org](http://www.3gpp.org)
- [RFC2119] “Key words for use in RFCs to Indicate Requirement Levels”, S. Bradner, March 1997,
[URL:http://www.ietf.org/rfc/rfc2119.txt](http://www.ietf.org/rfc/rfc2119.txt)

2.2 Informative References

- [OMADICT] “Dictionary for OMA Specifications”, Open Mobile Alliance™,
OMA-ORG-Dictionary-Vx_y, [URL:http://www.openmobilealliance.org/](http://www.openmobilealliance.org/)

3. Terminology and Conventions

3.1 Conventions

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

3.2 Definitions

No new definitions are introduced in this document.

3.3 Abbreviations

APN	Access Point Name
CS	Circuit switched
OMA	Open Mobile Alliance
PDN	Packet data network
PS	Packet switched
RSCP	Received Signal Code Power
RSRP	Reference Signal Received Power
RSSI	Received Signal Strength Indicator

4. Introduction

This specification enables remote configuration of connectivity parameters in M2M devices.

4.1 Version 1.0

V1.0 of the specification covers:

- (1) WAN connectivity for 3GPP or 3GPP2 bearers (GPRS, EDGE, UMTS, LTE, SMS)
- (2) LAN connectivity for WLAN

5. LWM2M Object: Cellular network connectivity

This object specifies resources to enable a device to connect to a 3GPP or 3GPP2 bearer, including GPRS/EDGE, UMTS, LTE, SMS. For cellular connectivity, this object focuses on Packet Switched (PS) connectivity and doesn't aim to provide comprehensive Circuit Switched (CS) connectivity management.

Object definition

Name	Object ID	Instances	Mandatory	Object URN
Cellular connectivity	10	Single	Optional	urn:oma:lwm2m:oma:10

Resource definitions

ID	Name	Operations	Instances	Mandatory	Type	Range	Units	Description
4000	Activated Profile Names	R	Multiple	Mandatory	ObjInk			Links to instances of the "APN connection profile" object representing every APN connection profile that has an activate connection to a PDN.
0	SMSC address	RW	Single	Optional	String			E.164 address of SMSC. Applicable for 3GPP2 networks where SMSC is not available from a smart card, or for 3GPP/3GPP2 networks to provide the application with a customer specific SMSC. The application decides how to use this parameter, e.g. precedence over UICC based SMSC address.
1	Disable radio period	RW	Single	Optional	Integer	0-86400	s	Time period for which device shall disconnect from cellular radio (PS detach, CS detach if applicable). Can be used to handle network overload situations.
2	Module activation code	RW	Single	Optional	String			Configurable in case the application needs to issue a code (e.g. via AT command) to activate the module. e.g. <code>"*98"</code> .
3	Vendor specific extensions	R	Single	Optional	ObjInk			Links to a vendor specific object.

6. LWM2M Object: APN connection profile

Description

This object specifies resources to enable a device to connect to an APN.

Object definition

Name	Object ID	Instances	Mandatory	Object URN
APN connection profile	11	Multiple	Optional	urn:oma:lwm2m:oma:11

Resource definitions

ID	Name	Operations	Instances	Mandatory	Type	Range	Units	Description
0	Profile name	RW	Single	Mandatory	String			Human-readable identifier. Multiple connection profiles can share the same APN value but e.g. have different credentials.
1	APN	RW	Single	Optional	String			Presented to network during connection to PDN e.g. 'internet.15.234'. This resource is not included in case 'Auto select APN by device' resource has the value TRUE. If the APN resource is present but contains an empty string, then the device shall not provide an APN in the connection request (invoking default APN procedures in the network).
2	Auto select APN by device	RW	Single	Optional	Boolean			If this resource is present for a connection profile, it enables the device to choose an APN according to a device specific algorithm. It provides a fall-back mechanism e.g. for some MVNO SIMs the configured APN may not work. Resource not included in case the 'APN' resource is specified.
3	Enable status	RW	Single	Optional	Boolean			True: connection is activated False: connection is de-activated. Allows the profile to be remotely activated or deactivated.
4	Authentication Type	RW	Single	Mandatory	Integer			Enumerated type: 0: PAP 1: CHAP
5	User Name	RW	Single	Optional	String			Used with e.g. PAP.

6	Secret	RW	Single	Optional	String			Used with e.g. PAP.
7	Reconnect Schedule	RW	Single	Optional	String			Comma separated list of retry delay values in seconds to be used in case of unsuccessful connection establishment attempts. e.g. "10,60,600,3600,86400"
8	Validity (MCC, MNC)	RW	Multiple	Optional	String			Coma separated mobile country code, then mobile network code – for which this APN is valid.
9	Connection establishment time (1)	R	Multiple	Optional	Time			UTC time of connection request. See note (1)
10	Connection establishment result (1)	R	Multiple	Optional	Integer			0 = accepted 1 = rejected
11	Connection establishment reject cause (1)	R	Multiple	Optional	Integer	0-111		Reject cause (3GPP TS 24.008)
12	Connection end time (1)	R	Multiple	Optional	Time			UTC time of connection end.
13	TotalBytesSent	R	Single	Optional	Integer			Rolling counter for total number of bytes sent via this interface since last device reset.
14	TotalBytesReceived	R	Single	Optional	Integer			Rolling counter for total number of bytes received via this interface since last device reset.
15	IP address (2)	RW	Multiple	Optional	String			May be IPv4 or IPv6 address.
16	Prefix length(2)	RW	Multiple	Optional	String			Associated with IPv6 address.
17	Subnet mask (2)	RW	Multiple	Optional	String			Subnet mask.
18	Gateway (2)	RW	Multiple	Optional	String			Gateway.
19	Primary DNS address (2)	RW	Multiple	Optional	String			Primary DNS address.
20	Secondary DNS address (2)	RW	Multiple	Optional	String			Secondary DNS address.
21	QCI (3)	RW	Single	Optional	Integer	1-9		For LTE only QCI=Quality of service Class Identifier This resource enables the LWM2M server to signal the LWM2M client which QCI it shall request from the network. See [3GPP-TS_23.203] for a description of QCI values.
22	Vendor specific extensions	R	Single	Optional	ObjInk			Links to a vendor specific object.

Notes:

- (1) For each activated PDP context request, the device may store at least one value of 'Connection establishment time', 'connection establishment result', 'Connection end time' and if activation is

unsuccessful then a 'connection establishment reject cause'. It is a device decision how many instances to keep.

- (2) These resources are used in case IP related parameters are defined statically, and are also set with the IP related parameters in case of dynamic IP address assignment. The normal use case would be to have one IPv4 and one IPv6 address which have each associated a prefix length (IPv6 only), a subnet mask, a gateway, and a primary and secondary DNS address.
- (3) For LTE a higher QoS may be established by setting up an additional bearer ("dedicated bearer") in addition to the default bearer which is established to the default APN. A dedicated bearer which is set up by the network on request by the device containing a requested QCI value can either be established to the same APN as the default bearer or to another APN. The QoS of a dedicated bearer may be modified on request by the device. The association of QoS values and APNs for a subscriber is stored in the network and checked during the establishment of a bearer.

7. LWM2M Object: WLAN connectivity

Description

This object specifies resources to enable a device to connect to a WLAN bearer.

Object definition

Name	Object ID	Instances	Mandatory	Object URN
WLAN connectivity	12	Multiple	Optional	urn:oma:lwm2m:oma:12

Resource definitions

ID	Name	Operations	Instances	Mandatory	Type	Range	Units	Description
0	Interface name	RW	Single	Mandatory	String			Human-readable identifier eg. wlan0
1	Enable	RW	Single	Mandatory	Boolean			0: Disabled 1: Enabled Enable / Disable interface When disabled radio must also be disabled
2	Radio Enabled	RW	Single	Mandatory	Integer			0: Disabled 1: 2.4 GHz 2: 5 GHz
3	Status	R	Single	Mandatory	Integer			0: Disabled 1: UP (OK) 2: Error
4	BSSID	R	Single	Mandatory	String	12 bytes		The MAC address of the interface, in hexadecimal form.
5	SSID	RW	Single	Mandatory	String	1-32 Bytes		The Service Set Identifier for this interface.
6	Broadcast SSID	RW	Single	Optional	Boolean			0: Do not broadcast SSID 1: Broadcast SSID
7	Beacon Enabled	RW	Single	Optional	Boolean			0: Do not broadcast beacons 1: Broadcast beacons
8	Mode	RW	Single	Mandatory	Integer			0: Access Point 1: Client (Station) 2: Bridge 3: Repeater
9	Channel	RW	Single	Mandatory	Integer	0-255		The current radio channel in use by this interface.
10	Auto Channel	RW	Single	Optional	Boolean			0: Disabled 1: Enabled

11	Supported Channels	RW	Multiple	Optional	Integer			Array of supported radio channels.
12	Channels In Use	RW	Multiple	Optional	Integer			Array of channels which the access point has determined are 'in use'. Including any channels in-use by access point itself.
13	Regulatory Domain	RW	Single	Optional	String	3 Bytes		802.11d Regulatory Domain String. First two octets are ISO/IEC 3166-1 two-character country code. The third octet is either " " (all environments), "O" (outside) or "I" (inside).
14	Standard	RW	Single	Mandatory	Integer			0: 802.11a 1: 802.11b 2: 802.11bg 3: 802.11g 4: 802.11n 5: 802.11bgn 6: 802.11ac 7: 802.11ah
15	Authentication Mode	RW	Single	Mandatory	Integer			0: None (Open) 1: PSK 2: EAP 3: EAP+PSK 4: EAPSIM
16	Encryption Mode	RW	Single	Optional	Integer			0: AES (WPA2) 1: TKIP (WPA) 2: WEP (1)
17	WPA Pre Shared Key	W	Single	Optional	String	64 Bytes		WPA/WPA2 Key expressed as a hex string. Write – Only.
18	WPA Key Phrase	W	Single	Optional	String	1-64 Bytes		WPA/WPA2 Key Phrase. Write Only.
19	WEP Encryption Type	RW	Single	Optional	Integer			0: None 1: 40-bit 2: 104-bit
20	WEP Key Index	RW	Single	Optional	Integer	[1:4]		Index of the default WEP key.
21	WEP Key Phrase	W	Single	Optional	String	1-64 Bytes		WPA/WPA2 Key Phrase. Write Only.
22	WEP Key 1	W	Single	Optional	String	10 or 26 Bytes		WEP Key 1 expressed as a hexadecimal string. 10 Bytes for a 40 Bit key 26 Bytes for a 104 Bit key
23	WEP Key 2	W	Single	Optional	String	10 or 26 Bytes		WEP Key 2 expressed as a hexadecimal string. 10 Bytes for a 40 Bit key 26 Bytes for a 104 Bit key
24	WEP Key 3	W	Single	Optional	String	10 or 26 Bytes		WEP Key 3 expressed as a hexadecimal string. 10 Bytes for a 40 Bit key

								26 Bytes for a 104 Bit key
25	WEP Key 4	W	Single	Optional	String	10 or 26 Bytes		WEP Key 4 expressed as a hexadecimal string. 10 Bytes for a 40 Bit key 26 Bytes for a 104 Bit key
26	RADIUS Server	RW	Single	Optional	String	1-256 Bytes		RADIUS Authentication Server Address
27	RADIUS Server Port	RW	Single	Optional	Integer			RADIUS Authentication Server Port Number
28	RADIUS Secret	W	Single	Optional	String	1-256 Bytes		RADIUS Shared Secret
29	WMM Supported	R	Single	Optional	Boolean			0: WMM NOT Supported 1: WMM Wupported
30	WMM Enabled	RW	Single	Optional	Boolean			0: Disabled 1: Enabled
31	MAC Control Enabled	RW	Single	Optional	Boolean			0: Any Client MAC Address accepted 1: Client MAC address must exist in MACAddressList
32	MAC Address List	RW	Multiple	Optional	String	12 Bytes		Array of allowed client MAC addresses, in hexadecimal form.
33	Total Bytes Sent	R	Single	Optional	Integer			Total number of bytes sent via this interface
34	Total Bytes Received	R	Single	Optional	Integer			Total number of bytes received via this interface
35	Total Packets Sent	R	Single	Optional	Integer			Total packets sent via this interface
36	Total Packets Received	R	Single	Optional	Integer			Total packets received via this interface
37	Transmit Errors	R	Single	Optional	Integer			Total number of packets which could not be transmitted because of errors.
38	Receive Errors	R	Single	Optional	Integer			Total number of packets received with errors which prevented those packets from being delivered.
39	Unicast Packets Sent	R	Single	Optional	Integer			Count of Unicast Packets Sent
40	Unicast Packets Received	R	Single	Optional	Integer			Count of Unicast Packets Received
41	Multicast Packets Sent	R	Single	Optional	Integer			Count of Multicast Packets Sent
42	Multicast Packets Received	R	Single	Optional	Integer			Count of Multicast Packets Received
43	Broadcast Packets Sent	R	Single	Optional	Integer			Count of Broadcast Packets Sent
44	Broadcast Packets Received	R	Single	Optional	Integer			Count of Broadcast Packets Received
45	Discard Packets Sent	R	Single	Optional	Integer			Count of valid outbound packets intentionally discarded without transmission, for example a packet may be discarded to manage buffer space.
46	Discard Packets Received	R	Single	Optional	Integer			Count of valid packets received and intentionally discarded without devlivery to the system, for example a packet may be discarded to manage buffer space.

47	Unknown Packets Received	R	Single	Optional	Integer			Count of Unknown Packets Received
48	Vendor specific extensions	R	Single	Optional	Objlink			Links to a vendor specific object.

Notes:

- (1) WEP is supported by this object for legacy devices. All encryption parameter resources are optional e.g. a Wifi Alliance “HotSpot 2.0” device would not support WEP related resources.

8. LWM2M Object: Bearer selection

Description

This object specifies resources to enable a device to choose a communications bearer on which to connect.

This object allows via remote bearer and network configuration to overwrite automatic network and bearer selection e.g. as supported by the UICC. An equivalent example for overwriting automatic selection is a user doing manual network and bearer selection on a smart phone.

Object definition

Name	Object ID	Instances	Mandatory	Object URN
Bearer selection	13	Single	Optional	urn:oma:lwm2m:oma:13

Resource definitions

ID	Name	Operations	Instances	Mandatory	Type	Range	Units	Description
0	Preferred Communications Bearer	RW	Multiple	Optional	Integer	8-bit		<p>Used in network selection:</p> <p>0: auto connect</p> <p>1: 3GPP PS preferred</p> <p>2: 3GPP PS GSM (GPRS) preferred</p> <p>3: 3GPP PS UMTS preferred</p> <p>4: 3GPP PS LTE preferred</p> <p>5: 1xEV-DO preferred (1)</p> <p>6: 3GPP CS preferred (1)</p> <p>7: WLAN preferred</p> <p>8: Ethernet preferred (1)</p> <p>9: DSL preferred (1)</p> <p>10: Bluetooth preferred (1)</p> <p>11: WIMAX preferred (1)</p> <p>12-100: Reserved for future use</p> <p>The Preferred Communications Bearer resource specifies the preferred communications bearer that the LWM2M Client is requested to use for connecting to the LWM2M Server. If multiple preferred communications bearers are specified, the priority order is reflected by the resource instance order. E.g. the bearer which appears first in the list of resource instances is to have higher priority over the rest of available</p>

								bearers. The LWM2M Client SHOULD use the preferred bearers with higher priority first if they are available. If none of indicated preferred bearers is available, the LWM2M Client SHOULD wait until one of them becomes available.
1	Acceptable RSSI (GSM)	RW	Single	Optional	Integer			Provides guide to the application when performing manual network selection.
2	Acceptable RSCP (UMTS)	RW	Single	Optional	Integer			Provides guide to the application when performing manual network selection.
3	Acceptable RSRP (LTE)	RW	Single	Optional	Integer			Provides guide to the application when performing manual network selection.
4	Acceptable RSSI (1xEV-DO)	RW	Single	Optional	Integer			Provides guide to the application when performing manual network selection.
5	Cell lock list	RW	Single	Optional	String			Comma separated list of allowed Global Cell Identities.
6	Operator list	RW	Single	Optional	String			Comma separated list of MCC+MNC of operators, in priority order. Resource "operator list mode" indicates how to process this list.
7	Operator list mode	RW	Single	Optional	Boolean			Indicates whether resource "operator list" represents the allowed operator list (white list), or, the preferred operator list. 0=preferred 1=allowed
8	List of available PLMNs	R	Single	Optional	String			Allows server to see results of network scan (e.g. result of AT+COPS=?)
9	Vendor specific extensions	R	Single	Optional	ObjInk			Links to a vendor specific object.

Notes:

- (1) Remote management of this communications bearer via LWM2M is currently not supported.

Appendix A. Change History

(Informative)

A.1 Approved Version History

Reference	Date	Description
n/a	n/a	No prior version

A.2 Draft/Candidate Version 1.0 History

Document Identifier	Date	Sections	Description
Draft Versions OMA-TS-LWM2M_ConnMgmt-V1_0	04 Jun 2014	All	Document baseline agreed by DM WG OMA-DM-LightweightM2M-2014-0015R01- INP_Skeleton_TS_for_ConnMgmt
	03 Sep 2014	All	OMA-DM-LightweightM2M-2014-0030- CR_connectivity_management_object OMA-DM-LightweightM2M-2014-0034- CR_CR_WLAN_connectivity_object
	22 Sep 2014	5, 6, 7, 8	OMA-DM-LightweightM2M-2014-0038R01- CR_QoS_and_other_changes
	08 Oct 2014	8	OMA-DM-LightweightM2M-2014-0044R01- CR_connectivity_management_bearer_selection
	12 Nov 2014	5, 6, 7, 8	OMA-DM-LightweightM2M-2014-0058R03- CR_addressing_CONNMGMT_comments_part1
	01 Dec 2014	5, 6, 7, 8	OMA-DM-LightweightM2M-2014-0063R01- CR_addressing_CONNMGMT_comments_part2
	08 Dec 2014	4, 5, App B	OMA-DM-LightweightM2M-2014-0065R01- CR_addressing_CONNMGMT_comments_part3
Candidate Version OMA-TS-LWM2M_ConnMgmt-V1_0	13 Jan 2015	n/a	Status changed to Candidate by TP TP Ref # OMA-TP-2014-0281- INP_LWM2M_CONNMGMT_V1_0_RRP_for_Candidate_Approval

Appendix B. Example objects and resources for LWM2M client

Object name	Object ID	Object Instance ID
Cellular network connectivity	10	-
APN connection profile	11	0
APN connection profile	11	1
WLAN connectivity	12	0
Network selection	13	-

Table 1: Object Instances of the Example

Resource Name	Resource ID	Resource Instance ID	Value	Notes
Activated Profile Names	4000	0	11:0	Only profile „Operator1 internet“ is active.
SMSC address	0		+61415011501	
Module activation code	2		*98	Application will prefix this to first AT command to module for activation of module.

Table 2: Cellular Network Connectivity Object

Resource Name	Resource ID	Resource Instance ID	Value	Notes
Profile name	0		Operator1 internet	
APN	1		Internet.15.234	
Enable status	3		True	
Authentication Type	4		0	PAP
User Name	5		Internet	
Secret	6		Internet	
Reconnect Schedule	7		10,60,600,3600,86400	
Connection establishment time	9	0	1416924000	25 Nov 2014, 1400 UTC
Connection establishment result	10	0	1	Establishment request was rejected
Connection establishment reject cause	11	0	15	Reason: PLMN not allowed
Connection establishment time	12	0	1416924010	
Connection establishment time	9	1	1416924020	Subsequent establishment started 10 seconds after previous attempt failed (according to Reconnect schedule)
Connection establishment result	10	1	0	

Connection end time	12	1	1416931200	25 Nov 2014, 1600 UTC
Total Bytes Send	13		1288490188	1.2Gbyte sent since last reset
Total Bytes Received	14		1572864	1.5Mbyte received since last reset
IP address	15	0	192.168.0.100	IPv4 address
IP address	15	1	0:0:0:0:ffff:c0a8:64	IPv6 address
Subnet mask	17		255.255.255.0	
Gateway	18		192.168.0.1	
Primary DNS address	19		192.168.0.1	
QCI	21		6	QCI 6 represents priority 6, 300ms packet delay budget, 10 ⁻⁶ packet error loss rate.

Table 3: APN Connection Profile Object [0]

Resource Name	Resource ID	Resource Instance D	Value	Notes
Profile name	0		specific_country network	
Auto select APN by device	2		true	
Enable status	3		false	
Validity (MCC, MNC)	8	0	604,0	This APN is applicable for networks in a specific country only.
Validity (MCC, MNC)	8	1	604,1	

Table 4: APN Connection Profile Object [1]

Resource Name	Resource ID	Resource Instance D	Value	Notes
Interface name	0		omawlan	
Enable	1		0	currently disabled
Radio Enabled	2		0	currently disabled
Status	3		0	currently disabled
BSSID	4		50:7E:5D:31:67:78	
SSID	5		oma	
Mode	8		1	client
Channel	9		8	
Standard	14		4	802.11n
Authentication Mode	15		4	EAPSIM
Encryption Mode	16		0	AES (WPA2)
WPA Key Phrase	18		omakeyphrase	

Table 5: WLAN Connectivity Object

Resource Name	Resource ID	Resource Instance D	Value	Notes
Preferred Communications Bearer	0	0	4	LTE preferred

Preferred Communications Bearer	0	1	3	UMTS preferred
Preferred Communications Bearer	0	2	2	GSM preferred
Acceptable RSCP (UMTS)	2		20	
Acceptable RSRP (LTE)	3		30	

Table 6: Bearer Selection Object