

Push to Communicate for Public Safety Document Management

Approved Version 1.0 – 24 Jan 2017

Open Mobile Alliance OMA-PCPS-TS-Document_Management-V1_0-20170124-A

Use of this document is subject to all of the terms and conditions of the Use Agreement located at http://www.openmobilealliance.org/UseAgreement.html.

Unless this document is clearly designated as an approved specification, this document is a work in process, is not an approved Open Mobile AllianceTM specification, and is subject to revision or removal without notice.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. Information contained in this document may be used, at your sole risk, for any purposes. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance. The Open Mobile Alliance authorizes you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services. The Open Mobile Alliance assumes no responsibility for errors or omissions in this document.

Each Open Mobile Alliance member has agreed to use reasonable endeavors to inform the Open Mobile Alliance in a timely manner of Essential IPR as it becomes aware that the Essential IPR is related to the prepared or published specification. However, the members do not have an obligation to conduct IPR searches. The declared Essential IPR is publicly available to members and non-members of the Open Mobile Alliance and may be found on the "OMA IPR Declarations" list at http://www.openmobilealliance.org/ipr.html. The Open Mobile Alliance has not conducted an independent IPR review of this document and the information contained herein, and makes no representations or warranties regarding third party IPR, including without limitation patents, copyrights or trade secret rights. This document may contain inventions for which you must obtain licenses from third parties before making, using or selling the inventions. Defined terms above are set forth in the schedule to the Open Mobile Alliance Application Form.

NO REPRESENTATIONS OR WARRANTIES (WHETHER EXPRESS OR IMPLIED) ARE MADE BY THE OPEN MOBILE ALLIANCE OR ANY OPEN MOBILE ALLIANCE MEMBER OR ITS AFFILIATES REGARDING ANY OF THE IPR'S REPRESENTED ON THE "OMA IPR DECLARATIONS" LIST, INCLUDING, BUT NOT LIMITED TO THE ACCURACY, COMPLETENESS, VALIDITY OR RELEVANCE OF THE INFORMATION OR WHETHER OR NOT SUCH RIGHTS ARE ESSENTIAL OR NON-ESSENTIAL.

THE OPEN MOBILE ALLIANCE IS NOT LIABLE FOR AND HEREBY DISCLAIMS ANY DIRECT, INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF DOCUMENTS AND THE INFORMATION CONTAINED IN THE DOCUMENTS.

© 2017 Open Mobile Alliance All Rights Reserved.

Used with the permission of the Open Mobile Alliance under the terms set forth above.

Contents

1.	SCO	PE	5
2.	REF	ERENCES	6
		NORMATIVE REFERENCES	
		INFORMATIVE REFERENCES	
		MINOLOGY AND CONVENTIONS	
		CONVENTIONS	
		DEFINITIONS	
		ABBREVIATIONS	
		RODUCTION	
		Version 1.0	
		XDM APPLICATION USAGES	
		POC GROUP	
•	5.1.1	Structure	
	5.1.2	Application Unique ID	
	5.1.3	XML schema	
	5.1.4	Default namespace	
	5.1.5	MIME type	
	5.1.6	Validation constraints	
	5.1.7	Data semantics	16
	5.1.8	Naming conventions	16
	5.1.9	Global Documents	16
	5.1.10		
	5.1.1	F	
5		POC USER ACCESS POLICY	
	5.2.1	Structure	
	5.2.2	Application Unique ID	
	5.2.3	XML schema	
	5.2.4	Default namespace	
	5.2.5	MIME type	
	5.2.6 5.2.7	Validation constraints	
	5.2.7	Naming conventions	
	5.2.9	Global Documents	
	5.2.10		
	5.2.1	1	
6.		EXTENSIONS TO SHARED XDM APPLICATION USAGES	
		GROUP USAGE LIST	
•	6.1.1	Structure	
	6.1.2	Application Unique ID	
	6.1.3	XML schema	
	6.1.4	Validation constraints	
	6.1.5	Data semantics	
6	5.2	POC EXTENSIONS TO GROUP	21
	6.2.1	Structure	
	6.2.2	XML schema	
	6.2.3	Validation constraints	
	6.2.4	Data semantics	
6	5.3 1	POC EXTENSIONS TO USER ACCESS POLICY	
	6.3.1	Structure	
	6.3.2	XML schema	
	6.3.3	Validation constraints	24

6.3.4 Data semantics	24
7. GROUP ADVERTISEMENT	25
7.1 STRUCTURE	25
7.2 XML SCHEMA	
7.3 MIME TYPE	
7.4 VALIDATION CONSTRAINTS	
7.5 DATA SEMANTICS	
8. POC EXTENSIONS TO GROUP ADVERTISEMENT	27
8.1 STRUCTURE	27
8.2 XML SCHEMA	27
8.3 VALIDATION CONSTRAINTS	27
8.4 DATA SEMANTICS	27
9. POC SPECIFIC APPLICATION USAGES	28
9.1 POC SESSIONS	28
9.1.1 Structure	28
9.1.2 Application Unique ID	28
9.1.3 XML Schema	28
9.1.4 Default Namespace	
9.1.5 MIME Type	
9.1.6 Validation constraints	28
9.1.7 Data Semantics	
9.1.8 Naming conventions	
9.1.9 Global documents	
9.1.10 Resource interdependencies	
9.1.11 Authorization policies	30
APPENDIX A. CHANGE HISTORY (INFORMATIVE)	31
A.1 APPROVED VERSION HISTORY	31
APPENDIX B. STATIC CONFORMANCE REQUIREMENTS (NORMATIVE).	32
B.1 POC GROUP (XGP)	33
B.1.1 PoC XDM Client	33
B.2 POC USER ACCESS POLICY (XAP)	33
B.2.1 PoC XDM Client	
B.3 GROUP USAGE LIST (XUL)	
B.3.1 PoC XDM Client	
B.4 POC SESSION-UNRELATED FEATURES (SUF)	
B.4.1 PoC XDM Client	34
APPENDIX C. XML DOCUMENTS EXAMPLES (INFORMATIVE)	35
C.1 GROUP ADVERTISEMENT DOCUMENT	35
C 2 GROUP ADVERTISEMENT DOCUMENT WITH DISPATCH	35

Figures

No table of figures entries found

Tables

No table of figures entries found.

1. Scope

This specification describes the documents used by the PCPS Enabler, including description of PCPS Enabler specific usage of data formats and XCAP Application Usages defined in the XDM Enabler. Additionally, this document specifies PCPS Enabler specific deviations and extensions to the XDM Enabler documents. This document also specifies the PCPS specific XCAP Application Usages.

2. References

2.1 Normative References

[OMA PoC V1.0 XDM] "PoC XDM Specification", Version 1.0, Open Mobile Alliance™,

OMA-TS-PoC_XDM-V1_0,

URL: http://www.openmobilealliance.org/

[OMA_IM_TS_ "OMA PoC Endorsement of OMA IM TS", Version 2.1, Open Mobile AllianceTM,

Endorsement] OMA-TS-PoC_Endorsement_OMA_IM_TS-V2_1,

URL: http://www.openmobilealliance.org/

[OMA SCR Rules] "SCR Rules and Procedures", V1_0, Open Mobile AllianceTM,

OMA-ORG-SCR_Rules_and_Procedures-V1_0, URL: http://www.openmobilealliance.org/

[OMA-PCPS-CP] "Push to Communicate for Public Safety Control Plane", Version 1.0, Open Mobile AllianceTM, OMA-

TS-PCPS ControlPlane-V1 0

URL: http://www.openmobilealliance.org/

[OMA-PCPS-UP] "Push to Communicate for Public Safety User Plane", Version 1.0, Open Mobile Alliance™, OMA-TS-

PCPS_UserPlane-V1_0

URL: http://www.openmobilealliance.org/

[OMA-PoC-Document "OMA PoC Document Management", Version 2.1, Open Mobile AllianceTM,

Mgmt] OMA-TS-PoC_Document_Management-V2_1, URL: http://www.openmobilealliance.org/

[RFC2119] IETF RFC 2119: "Key words for use in RFCs to Indicate Requirement Levels", March 1997.

URL: http://www.ietf.org/rfc/rfc2119.txt

[RFC3261] IETF RFC 3261: "SIP: Session Initiation Protocol", June 2002.

URL: http://www.ietf.org/rfc/rfc3261.txt

[RFC3840] IETF RFC 3840 "Indicating User Agent Capabilities in the Session Initiation Protocol (SIP)", J.

Rosenberg, H. Schulzrinne, P. Kyzivat, August 2004,

URL: http://www.ietf.org/rfc/rfc3840.txt

[RFC4745] IETF RFC 4745: "Common Policy: A Document Format for Expressing Privacy Preferences", February

2007.

URL: http://www.ietf.org/rfc/rfc4745.txt

[RFC4825] IETF RFC 4825: "The Extensible Markup Language (XML) Configuration Access protocol (XCAP)",

May, 2007.

URL: http://www.ietf.org/rfc/rfc4825.txt

[RFC4826] IETF RFC 4826 "The Extensible Markup Language (XML) Formats for Representing Resource Lists", J.

Rosenberg, May 2007,

URL: http://www.ietf.org/rfc/rfc4826.txt

[RFC4975] IETF RFC 4975"The Message Session Relay Protocol (MSRP)", B. Campbell, R. Mahy, C. Jennings,

September 2007,

URL: http://www.ietf.org/rfc/rfc4975.txt

[SHARED_GROUP_XD "Shared Group XDM Specification", Version 2.0, Open Mobile AllianceTM,

OMA-TS-XDM_Shared_Group-V2_0, URL: http://www.openmobilealliance.org/

[XDM _LIST] "List XDM Specification", Version 2.1, Open Mobile AllianceTM, OMA-TS-XDM _List-V2_1,

URL: http://www.openmobilealliance.org/

[XDM _POLICY] "Policy XDM Specification", Version 1.1, Open Mobile AllianceTM,

OMA-TS-XDM_Policy_Group-V1_1, URL: http://www.openmobilealliance.org/

M]

[XDM_GROUP] "Group XDM Specification", Version 1.1, Open Mobile AllianceTM,

OMA-TS-XDM_Group-V1_1,

URL: http://www.openmobilealliance.org/

[XDMSPEC] "XML Document Management (XDM) Specification", Version 2.1, Open Mobile AllianceTM,

OMA-TS-XDM_Core-V2_1,

URL: http://www.openmobilealliance.org/

[XSD_XDM2_EXT] "XDM2 Extensions", Candidate Version 1.0, Open Mobile Alliance™,

OMA-SUP-XSD_xdm_extensions-V1_0, URL: http://www.openmobilealliance.org/

[XSD-1_POCUSAGE] "PCPS – PoC usage", Version 1.0, Open Mobile Alliance™,

OMA-SUP-XSD_pcps_pocusage-V1_0, <u>URL: http://www.openmobilealliance.org/</u>

[XSD-2_1_GROUP

"PCPS – PoC Group extensions", Version 1.0, XDM2.1 Extensions" Open Mobile Alliance™, OMA-

_EXT] SUP-XSD_pcps_poc2_1SharedGroupExt-V1_0,

URL: http://www.openmobilealliance.org/

[XSD-2_1- "PCPS – PoC Sessions", Version 1.0, Open Mobile Alliance™,

POCSESSIONS] OMA_SUP_XSD_pcps_poc_sessions-V1_0, URL: http://www.openmobilealliance.org/

[XSD-2_POCRULES] "PCPS – PoC Rules", Version 1.0, Open Mobile Alliance™,

OMA-SUP-XSD_pcps_poc2_0Rules-V1_0, URL: http://www.openmobilealliance.org/

[XSD- "PCPS − Shared Group extensions", Version 1.0, Open Mobile Alliance™,

2_SHARED_GROUP_E OMA-SUP-XSD_pcps_poc2_0SharedGroupExt-V1_0,

XT] URL: http://www.openmobilealliance.org/

[XSD-2- "PCPS - Group Advertisement Dispatch Attribute", Version 1.0, Open Mobile Alliance™,

POCDISPATCH] OMA-SUP-XSD_pcps_dispatchInd-V1_0,

URL: http://www.openmobilealliance.org/

2.2 Informative References

[OMA Dictionary] "Dictionary for OMA Specifications", Version 2.9, Open Mobile AllianceTM,

OMA-ORG-Dictionary-V2_9,

URL: http://www.openmobilealliance.org/

3. Terminology and Conventions

3.1 **Conventions**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

All sections and appendixes, except "Scope" and "Introduction", are normative, unless they are explicitly indicated to be informative.

3.2 Definitions

For the purposes of the PoC specifications, the terms and definitions given in [OMA Dictionary] and the following terms and definitions apply.

Active PoC Dispatcher PoC User currently taking the role of PoC Dispatcher for all the Dispatch PoC Sessions of a Dispatch PoC Group. The Active PoC Dispatcher can change along time between PoC Users that are allowed the role of PoC Dispatcher for the Dispatch PoC Group (e.g. through role transfer mechanisms). Ad-hoc PoC Group A PoC Group Session established by a PoC User to PoC Users listed on the invitation. The list includes PoC Users or PoC Groups or both. Session Application Unique ID A unique identifier that differentiates XCAP resources accessed by one application from XCAP resources accessed by another application. (Source: [RFC4825]) Application Usage Detailed information on the interaction of an application with an XCAP Server. (Source: [RFC4825]) Audio General communication of sound with the exception of PoC Speech. Chat PoC Group A persistent PoC Group in which a PoC User individually joins to have a PoC Session with other joined PoC Users, i.e., the establishment of a PoC Session to a Chat PoC Group does not result in other PoC Users being invited. NOTE: A Chat PoC Group is a persistent PoC Group where the <invite-members> element is set to "false". Chat PoC Group Session A PoC Session established to a Chat PoC Group. A function implemented in a PoC Server, providing centralized PoC Session handling, which includes Controlling PoC Function Media distribution, Talk Burst Control, Media Burst Control, policy enforcement for participation in the PoC Group Sessions, and the Participant information. Discrete Media Media that itself does not contain an element of time (e.g. images, text).

Dispatch PoC Group A Pre-arranged PoC Group in which one member is assigned the role of PoC Dispatcher and the other

member(s) are assigned the role of PoC Fleet Members.

Dispatch PoC Session The PoC Session of a Dispatch PoC Group, or a subset of the Dispatch PoC Group, in which the 1-many-

1 communication method is used.

Global Document A document placed under the XCAP Global Tree that applies to all users of that application usage.

Global Tree A URI that represents the parent for all Global Documents for a particular application usage within a

particular XCAP Root.

Group A predefined set of Users together with its policies and attributes. A Group is identified by a SIP URI.

A feature that provides the capability to inform other PoC Users of the existence of a PoC Group. Group Advertisement

Group Usage List A list of group names or service URIs that are known by the XDM Client

Media Forms of information that are exchanged between Participants. Media may come in different forms,

which are referred to as Media Types.

Media Burst Control Media Burst Control is a control mechanism that arbitrates requests from the PoC Clients, for the right to

send Media and Multimedia.

Media Burst Control Schemes Way of using Media Burst Control according to predefined rules and procedures.

Media Streaming Control

A Media Type allowing Participants to control a Continuous Media stream using RTSP in a PoC Session.

Media Type

Media Types share a characteristic of human perception. Media Types are either realtime or non-realtime, like:

- PoC Speech
- Audio (e.g. music)
- Video
- Discrete Media (e.g. still image, formatted and non-formatted text, file)
- Media Streaming Control (RTSP)

Multimedia Multimedia is the simultaneous existence of multiple Media Types like

- audiovisual
- · video plus subtitles

Multimedia from a single source that involves real-time Media Types are assumed to be synchronized.

NW PoC Box A PoC functional entity in the PoC Network where PoC Session Data and PoC Session Control Data can

be stored

Participant A Participant is a PoC User in a PoC Session.

Participant Information Information about the PoC Session and its Participants.

Participating PoC Function A function implemented in a PoC Server, which provides PoC Session handling, which includes policy

enforcement for incoming PoC Sessions and relays Talk Burst Control and Media Burst Control messages between the PoC Client and the PoC Server performing the Controlling PoC Function. The Participating PoC Function may also relay RTP Media between the PoC Client and the PoC Server

performing the Controlling PoC Function.

PoC Box A PoC functional entity where PoC Session Data and PoC Session Control Data can be stored. It can be a

NW PoC Box or a UE PoC Box.

PoC Client A functional entity that resides on the User Equipment that supports the PoC service.

PoC Crisis Event Handling

Entity

A functional Entity in the PoC Network authorizing PoC Users to initiate or join Crisis PoC Sessions. The PoC Crisis Event Handling Entity enforces the local policy for National Security, Public Safety and Private Safety applications within a country or a sub-division of a country.

NOTE: The PoC Crisis Event Handling Entity complements the emergency service.

PoC Dispatcher The Participant in a Dispatch PoC Session that sends Media to all PoC Fleet Members and that receives

Media from any PoC Fleet Member.

NOTE: The PoC Dispatcher is an enhancement to the PoC 1 Distinguished Participant.

PoC Fleet Member A Participant in a Dispatch PoC Session that is only able to send Media to the PoC Dispatcher, and that

likewise is only able to receive Media from the PoC Dispatcher.

NOTE: PoC Fleet Member is the same as Ordinary Participant in PoC 1.

PoC Group A Group supporting the PoC service. PoC User uses PoC Groups e.g. to establish PoC Group Sessions.

PoC Group Identity A SIP URI identifying a Pre-arranged PoC Group or a Chat PoC Group. A PoC Group Identity is used by

the PoC Client e.g. to establish PoC Group Sessions to the Pre-arranged PoC Groups and Chat PoC

Groups.

PoC Group Name Indicates the name of the PoC Group that can be presented to the PoC User.

PoC Group Session A Pre-arranged PoC Group Session, Ad-hoc PoC Group Session or Chat PoC Group Session.

PoC Network Network comprising of a SIP/IP Core and PoC Server(s), which provide PoC capabilities to the

associated PoC capable User Equipments which are compliant with OMA PoC Service Enabler

specifications.

PoC Session A PoC Session is a SIP Session established by the procedures of this specification. This specification

supports the following types of PoC Sessions: 1-1 PoC Session, Ad-hoc PoC Group Session, Pre-

arranged PoC Group Session, or Chat PoC Group Session.

PoC Session Control Data Information about PoC Session Data e.g. time and date, PoC Session initiator.

PoC Session Data Media Burst and Media Burst Control information exchanged during a PoC Session e.g. Video frames,

an image or Talk Burst.

PoC Session Identity SIP URI, which identifies the PoC Session and which can be used for routing initial SIP requests. It is

received by the PoC Client during the PoC Session establishment in the Contact header and/or in the

MBCP Connect message in case of using Pre-established Session.

PoC Speech Communication of speech as defined by PoC version 1.0.

PoC Subscriber Is one whose service subscription includes the PoC service. A PoC Subscriber can be the same person as

a PoC User.

PoC User A User of the PoC service. A PoC User can be the same person as a PoC Subscriber. A PoC User uses the

PoC features through the User Equipment.

PoC User Access Policy A rule-based plan of actions that defines the criteria for access to the PoC User. The plan describes the

expected pattern of behaviour of the PoC User at access attempts from other PoC Users.

Pre-arranged PoC Group A persistent PoC Group. The establishment of a PoC Session to a Pre-arranged PoC Group results in the

members being invited.

NOTE: A Pre-arranged PoC Group is a persistent PoC Group, where the <invite-members>

element is set to "true".

Pre-arranged PoC Group

Session

A PoC Session established by a PoC User to a Pre-arranged PoC Group.

RTP Media The Media carried in an RTP payload.

SIP Session A SIP dialog. From [RFC3261], a SIP dialog is defined as follows: A dialog is a peer-to-peer SIP

relationship between two UAs that persists for some time. A dialog is established by SIP messages, such as a 2xx response to an INVITE request. A dialog is identified by a call identifier, local tag, and a remote

tag. A dialog was formerly known as a call leg in [RFC2543].

SIP URI From RFC 3261: "A SIP or SIPS URI identifies a communications resource" and "follows the guidelines

in RFC 2396 [5]". PoC uses SIP URIs to identify PoC Clients, PoC Servers, and PoC Sessions, resource

lists that point to URI Lists, etc.

Talk Burst A flow of PoC Speech from a PoC Client having the permission to send PoC Speech as specified in OMA

PoC V1.0.

Talk Burst Control A control mechanism that arbitrates requests from the PoC Clients for the right to send PoC Speech as

specified in OMA PoC V1.0.

UE PoC Box A functional entity co-located with the PoC Client in the User Equipment where PoC Session Data and

PoC Session Control Data can be stored.

URI List A list of URIs.

User Any entity that uses the described features through the User Equipment.

User Equipment A hardware device that supports a PoC Client e.g., a wireless phone.

Video Communication of live-streamed pictures without any Audio component.

XCAP Application Usage Detailed information on the interaction of an XCAP Client with an XCAP Server. (Source: [RFC4825])

XCAP Client An HTTP client that understands how to follow the naming and validation constraints defined in this

specification.

XCAP Root A context that includes all of the documents across all application usages and users that are managed by a

server.

XCAP Server An HTTP server that understands how to follow the naming and validation constraints defined in this

specification.

3.3 Abbreviations

AUID Application Unique ID

HTTP Hypertext Transfer Protocol

MIME Multipurpose Internet Mail Extensions

NW Network

OMA Open Mobile Alliance

PCPS Push to Communicate for Public Safety

PoC Push to talk over Cellular

UE User Equipment

URI Uniform Resource Identifier

XCAP XML Configuration Access Protocol

XDM XML Document Management

XDMC XDM Client
XDMS XDM Server

XML Extensible Markup Language

XUI XCAP User Identifier

4. Introduction

The PCPS Enabler is intended to deliver a complete set of Push-to-Communicate for Public Safety application and service layer standards (for voice and data), hence the PCPS acronym. This enabler is an update from the PoC V2.1 Enabler.

This specification describes the usage of documents used by the PCPS Enabler. The specific usages include the usage of the XML schemas and Application Usages for Group documents, User Access Policy documents and Group Usage List documents and PoC Session documents. XDM Application Usages include that for PoC Groups and PoC User Access Policy, which are specified in details in [XDM_POLICY] as User Access Policy and in [XDM_GROUP] as Group. The specific Application Usages include that for PoC Sessions. Additionally, this specification describes the usage of the XML schema for the Group Advertisement, which is specified in [XDM_GROUP] as Extended Group Advertisement. This specification also defines the specific deviations and extensions to the XML schemas for the Group, the User Access Policy, Group Usage List, and Extended Group Advertisement documents.

Clients use the AUIDs and the protocol specified in [OMA PoC V1.0 XDM], if the PoC Enabler Release 1 is indicated by the provisioning.

In addition to above the backward compatibility towards PoC V1.0 is ensured by appropriate configuration of the Aggregation Proxy and the special handling of PoCv1.0 level requests in the Shared XDMS.

Clienst use the AUIDs and the protocol specified in [OMA-PoC-V2.0-Document-Mgmt] if the PoC Enabler Release 2.0 is indicated by the provisioning.

Clients use the AUIDs and the protocol specified in [OMA-PoC-V2.1-Document-Mgmt] if the PoC Enabler Release 2.1 is indicated by the provisioning.

Informational Note: Usage of all PoCv2.1 functionalities requires XDMv2.1 functionalities.

Clients use the AUIDs and the protocol specified in this document, if the PCPS V1.0 Enabler is indicated by the provisioning.

4.1 **Version 1.0**

PCPS V1.0 has a limited scope, serving as a limited OMA PoC Enabler Update from the current version of PoC V2.1.

PCPS V1.0 updates PoC V2.1 to support 3GPP Release 12 LTE and relevant key features based upon completed 3GPP requirements up through Release 12.

PCPS V1.0 is synchronized to 3GPP Release 12, specifically excluding the following in progress Release 12 work:

- Group Communication System Enablers for LTE (GCSE_LTE)
- Proximity Services (ProSe)

PCPS V1.0 is synchronized to 3GPP Release 12, to specifically include the following:

- Adapt PoC V2.1 Multicast (currently using MBMS over UTRA) to use eMBMS over LTE
- Update PoC V2.1 SIP/IP Core operations to align with 3GPP Release 12 LTE architecture

PCPS V1.0 describes usage of PoC specific Application Usages for PoC Sessions documents. PCPS V1.0 also describes usage of XDM specific Application Usages for Group documents, User Access Policy documents and Group Usage List documents.

The PCPS V1.0 enabler summarizes the usage of documents for:

- Group
- User Access Policy
- Group Usage List
- Type of PoC Group

- Extended Group Advertisement
- PoC Box
- Active PoC Dispatcher
- Media Burst Control Schemes
- Dispatch PoC Group
- PoC Sessions
- Media Burst Control Schemes
- PoC Group specific releasing rules
- PoC Crisis Event Handling
- Moderator

5. PoC XDM Application Usages

5.1 PoC Group

NOTE: In PCPS version 1.0 the Group definitions are described in the [XDM_GROUP]. PoC Groups are still available for network elements and XDM Clients, that are compliant with PoC 1.0 Enabler Release by using the AUID specified in the PoC 1.0 as specified in [OMA PoC V1.0 XDM].

PoC Group is described in the [XDM_GROUP] "*Group*". The use of the elements of PoC Groups is described in [OMA-PCPS-CP].

5.1.1 Structure

The general Group structure is described in the [XDM_GROUP] "Structure" with the PoC Enabler specific clarifications and deviations specified in this subclause and the additional, PoC specific structure, in the subclause 6.2.1 "Structure".

The following elements and attributes of the service> element together with their usage are used by PoC Enabler as specified in [XDM GROUP]:

- a) a "uri" attribute containing the PoC Group Identity;
- b) other attributes from any other namespaces for the purpose of extensibility;
- c) a <display-name> element containing a PoC Group Name;
- d) a element containing the PoC Group Members;
- e) an <invite-members> element;
- f) a <max-participant-count> element containing a maximum number of allowed PoC Users in a Pre-arranged PoC Group Session and a Chat PoC Group Session;
- g) a <ruleset> element representing the authorization policy associated with this PoC Group;
- h) a <subject> element containing a topic or description of the Group;
- i) a <supported-services> element containing supported services of the PoC Group;
- i) a <qoe> element indicating the Quality of Experience Profile assigned to the PoC Group.
- k) <min-participant-count> element representing the minimum number of participants needed for a PoC Group Session to become active or remain active
- 1) <required-participants> element representing who must participate for a PoC Group Session to become active or remain active
- m) <max-duration> element representing the maximum allowed time duration of a Group Session

NOTE: When the PoC Group is created, the <automatic-group-advertisement> element can be used in the Group definition, as defined in the [XDM_GROUP], if Group Advertisement is desired to be sent automatically to the PoC Group members as specified in the [XDM_GROUP].

The following elements and attributes of the element together with their usage are used by PoC Enabler as specified in [XDM_GROUP]:

- a) an <entry> element;
- b) an <external> element.

The following elements and attributes of the <ruleset> element together with their usage are used by PoC Enabler as specified in [XDM_GROUP]:

a) an <rule> element.

The following elements and attributes of the <conditions> child element of any <rule> element together with their usage are used by PoC Enabler as specified in [XDM_GROUP]:

- a) the <identity> element;
- b) the <external-list> element;
- c) the <other-identity> element;
- d) the <is-list-member> element.

The following elements and attributes of the <actions> child element of any <rule> element together with their usage are used by PoC Enabler as specified in [XDM_GROUP]:

- a) the <allow-conference-state> element;
- b) the <allow-invite-users-dynamically> element;
- c) the <join-handling> element;
- d) the <allow-initiate-conference> element;
- e) the <allow-anonymity> element;
- f) the <is-key-participant> element;
- g) the <allow-subconf> element;
- h) the <allow-media-handling> element;
- i) the <remove-media-handling> element;
- j) the <allow-expelling> element;
- k) the <block-group-advertisement-sending> element.

5.1.2 Application Unique ID

Application Unique ID is described in the [XDM_GROUP] "Application Unique ID".

5.1.3 XML schema

XML schema is described in the [XDM_GROUP] "XML Schema". The PoC specific XML schema extensions are described in subclause 6.2.2 "XML schema".

5.1.4 Default namespace

Default namespace is described in the [XDM_GROUP] "Default Namespace".

5.1.5 MIME type

MIME type is described in the [XDM_GROUP] "MIME Type".

5.1.6 Validation constraints

Validation constraints are described in the [XDM_GROUP] "Validation Constraints".

5.1.7 Data semantics

Data semantics are described in the [XDM_GROUP] "Data Semantics" with the PoC specific clarifications specified in this subclause. The data semantics for PoC specific extensions are described in subclause 6.2.4 "Data semantics".

A group data is applicable to PoC service only if the condition element <supported-services> is present, and

- 1. the child element <service> includes the "enabler" attribute value "poc"; or,
- 2. the child element <all-services-except> does not include a <service> child element with "enabler" attribute value "poc".

The <group-media> element, which is a child element of <service>:

The sub-element <full-duplex> is not applicable for Audio and Video in PoC Service.

Group documents including elements with "must-understand" attribute and not used by PoC Enabler SHALL be regarded as not applicable to PoC service.

The <invite-members> element:

"true" represents the Pre-arranged PoC Group.

"false" represents the Chat PoC Group. This value is used when the element is not present.

A <group-media> element with a list of media elements is used to specify allowed media types. List of possible media elements defined in PoC are:

- 1) The <message-session> media element indicating session based messaging as defined in [RFC4975];
- The <file-transfer> media element indicating file transfer as defined in [OMA_IM_TS_ Endorsement];
- 3) The <audio> media element indicating a streaming media type as defined in [RFC3840];
- 4) The <video> media element indicating a streaming media type as defined in [RFC3840];
- 5) The <poc-speech> media element indicating a PoC speech media type as defined in [OMA-PCPS-CP];
- 6) The <group-advertisement> media element indicating a group advertisement as defined in [XDM_GROUP] "Extended Group Advertisements".

NOTE: All other media elements not listed in the list above are ignored by the PoC Server.

5.1.8 Naming conventions

Naming conventions are described in the [XDM_GROUP] "Naming conventions".

5.1.9 Global Documents

Global Documents are described in the [XDM_GROUP] "Global Documents".

5.1.10 Resource interdependencies

 $Resource\ interdependencies\ are\ described\ in\ the\ [XDM_GROUP]\ "\textit{Resource\ interdependencies}".$

5.1.11 Authorization policies

Authorization policies are described in the [XDM GROUP] "Authorization policies".

5.2 PoC User Access Policy

NOTE: In PCPS 1.0 the User Access Policy is described in the [XDM_POLICY]. PoC User Access Policies are still available for network elements and XDM Clients, that are compliant with PoC 1.0 Enabler Release by using the AUID specified in the PoC 1.0 as specified in [OMA PoC V1.0 XDM].

PoC User Access Policy is described in the [XDM_POLICY] "User Access Policy". The use of the elements of PoC User Access Policy is described in [OMA-PCPS-CP].

5.2.1 Structure

The general User Access Policy structure is described in the [XDM_POLICY] "Structure" with the PoC Enabler specific clarifications and deviations specified in this subclause and the additional, PoC specific structure in the subclause 6.3.1"Structure".

The following elements and attributes of the <rule> element together with their usage are used by PoC Enabler as specified in [XDM POLICY]:

- a) the <conditions> element;
- b) the <actions> element.

NOTE 1: This specification does not define any value for the <transformations> element defined as a child of the <rule> element in [RFC4745]. This means that, if present, the PoC Server ignores this element.

The following elements and attributes of the <conditions> element together with their usage are used by PoC Enabler as specified in [XDM_POLICY]:

- a) the <identity> element;
- b) the <external-list> element;
- c) the <other-identity> element;
- d) the <sphere> element;
- e) the <validity> element;
- NOTE 2: This specification does not define any value for those elements defined as a part of the <conditions> element in [RFC4745], but which are not explicitly identified in the list above. This means that, if present, the PoC Server ignores such elements.
- f) the <anonymous-request> element;
- g) the <media-list> element;
- h) the <service-list> element, as defined in [XDMSPEC] "Common Extensions";
- i) the <goe> element;
- j) the <invited-identities> element;
- k) the <activities> element;
- 1) the <country-region-list> element;
- m) the <location-list> element.

The following elements and attributes of the <actions> element together with their usage are used by PoC Enabler as specified in [XDM_POLICY]:

- a) the <allow-auto-answermode> element;
- b) the <allow-reject-invite> element;
- c) the <allow-offline-storage> element;
- d) the <allow-manual-answer-override> element;
- e) the <allow-barring-media-content> element;
- f) the <allow-barring-media-stream> element;
- g) the <allow-reject-outgoing-invite> element.

5.2.2 Application Unique ID

Application Unique ID is described in the [XDM_POLICY] "Application Unique ID".

5.2.3 XML schema

XML schema is described in the [XDM_POLICY] "XML Schema". The PoC specific XML schema extensions are described in subclause 6.3.2 "XML schema".

5.2.4 Default namespace

Default namespace is described in the [XDM_POLICY] "Default Namespace".

5.2.5 MIME type

MIME type is described in the [XDM_POLICY] "MIME Type".

5.2.6 Validation constraints

Validation constraints are described in the [XDM_POLICY] "Validation constraints".

5.2.7 Data semantics

Data semantics are described in the [XDM_POLICY] "Data Semantics" with the PoC specific clarifications specified in this subclause. The data semantics for PoC specific extensions are described in subclause 6.3.4 "Data semantics".

An authorization rule is applicable to PoC service only if the condition element <service-list> is not present, or if present the child element <service> includes the "enabler" attribute value "poc" or the child element <all-services-except> does not include a <service> child element with "enabler" attribute value "poc".

The sub-element <full-duplex> is not applicable for Audio and Video in the PoC service.

The action <allow-reject-invite> element value "true" is not applicable for the following elements in the PoC service:

- a) the <country-region-list> element;
- b) the <location-list> element.

The action element <allow-barring-media-content> is applicable to the following elements for barring/not barring incoming Media content:

- a) the <audio> media element;
- b) the <video> media element;

- c) the <text> media element;
- d) the <image> media element;
- e) the <binary-data> media element;
- f) the <group-advertisement> media element.

The action element <allow-barring-media-stream> is applicable to the following elements for barring/not barring incoming Media streams:

- a) the <message-session> media element;
- b) the <file-transfer> media element;
- c) the <audio> media element;
- d) the <video> media element;
- e) the <poc-speech> media element;
- f) the < media-streaming-control> media element.

A <media-list> element with a list of media elements is used to specify allowed media types. List of possible media elements defined in PoC are:

- a) The <message-session> media element indicating session based messaging as defined in [RFC4975];
- The <file-transfer> media element indicating file transfer as defined in [OMA_IM_TS_ Endorsement];
- c) The <audio> media element indicating a streaming media type as defined in [RFC3840];
- d) The <video> media element indicating a streaming media type as defined in [RFC3840];
- e) The <poc-speech> media element indicating a PoC speech media type as defined in [OMA-PCPS-CP];
- f) The <group-advertisement> media element indicating a group advertisement as defined in [XDM_GROUP] "Extended Group Advertisements".

NOTE: All other media elements not listed in the list above are ignored by the PoC Server.

A <sphere> element is used to specify the User defined conditions profile to be used by Incoming and Outgoing Condition Based PoC Session Barring. Possible values defined in PoC are:

- a) "none";
- b) "private";
- c) "business".

The action <allow-reject-outgoing-invite> element value "true" is applicable for the following elements in the PoC service:

- a) the <media-list> element;
- b) the <qoe> element;
- c) the <sphere> element;
- d) the <validity> element;
- e) the <invited-identities> element;
- f) the <activities> element;

- g) the <country-region-list> element;
- h) the <location-list> element.

5.2.8 Naming conventions

Naming conventions are described in the [XDM_POLICY] "Naming conventions".

5.2.9 Global Documents

Global Documents are described in the [XDM_POLICY] "Global Documents".

5.2.10 Resource interdependencies

Resource interdependencies are described in the [XDM_POLICY] "Resource interdependencies".

5.2.11 Authorization policies

Authorization policies are described in the [XDM_POLICY] "Authorization policies".

6. PoC extensions to Shared XDM Application Usages

6.1 Group Usage List

6.1.1 Structure

A PoC specific URI usage SHALL be used in a Group Usage List stored in the List XDMS.

The PoC URI usage, <pocusage> element, is defined to substitute <uriusage> element and is used within the <uriusages> element as specified in [XDM_LIST].

6.1.2 Application Unique ID

Application Unique ID is described in the [XDM_LIST] "Group Usage List".

6.1.3 XML schema

The cusage> element SHALL conform to the XML schema described in [XSD-1_POCUSAGE].

6.1.4 Validation constraints

None.

6.1.5 Data semantics

The cousage> element, if present in any <uriusages> element, SHALL indicate the type of PoC Group URI. The possible values are:

"chat" the PoC Group URI is a Chat PoC Group.

"prearranged" the PoC Group URI is a Pre-arranged PoC Group.

6.2 PoC extensions to Group

6.2.1 Structure

In addition to the child elements that the <actions> child element of any <rule> element MAY include according to [XDM_GROUP], the <actions> child element of any <rule> element MAY include the following PoC Specific child elements:

- a) the <allow-dispatch> element:
 - SHALL include an "allow" attribute indicating whether the PoC User is allowed to adopt the PoC Dispatcher role;
 - MAY include an <allow-dispatcher-role-transfer> element indicating whether the PoC User is allowed to transfer the PoC Dispatcher role;
- b) the <mbc_scheme> element;
- c) the <auto-release> element
- d) the <crisis-event-entity-address>
 - SHALL include a "ref" attribute giving the address to the PoC Crisis Event Handling Entity to be used for a Pre-arranged PoC Group or a Chat PoC Group.n "allow" attribute indicating whether the PoC User is allowed to adopt the Moderator role.

- e) the <allow-moderator> element
 - SHALL include an "allow" attribute indicating whether the PoC User is allowed to be a Moderator;
- f) the <allowed-media-inactivity> element
 - SHALL include a "release-when-poc-speech-inactive" attribute indicating whether the PoC Session is released when the PoC Speech Media Type has been inactive for <allowed-media-inactivity> seconds or if inactivity for all Media Types needs to be inactive before releasing the PoC Session.

6.2.2 XML schema

The <allow-dispatch>, <allow-dispatcher-role-transfer> and <mbc_scheme> elements SHALL conform to the XML schema which namespace name is "urn:oma:xml:pcps:poc2.0-shared-group-ext" and is described in [XSD-2_SHARED_GROUP_EXT].

The <crisis-event-entity-address> element SHALL conform XML schema which namespace name is "urn:oma:xml:pcps:poc2.1-shared-group-ext" and is described in [XSD-2_1_GROUP_EXT]. The "allow" attribute SHALL conform to the XML schema described in [XSD_XDM2_EXT].

The "ref" attribute<allow-moderator> elements SHALL conform to the XML schema described in [XSD_XDM2_EXT].

The <auto-release> and <allowed-media-inactivity> elements SHALL conform to the XML schema which namespace name is defined by [XSD-2_1_GROUP_EXT].

The "release-when-poc-speech-inactive" attribute SHALL conform to the XML schema described by [XSD-2_1_GROUP _EXT].

6.2.3 Validation constraints

The Group actions SHALL conform to the XML schema described in subclause 6.2.2 "XML schema", with the clarifications given in this subclause.

If the XDMC adds in the <actions> child element of a <rule> element an <allow-dispatch> element with the "allow" attribute set to the value "false" and the child element <allow-dispatcher-role-transfer> set to the value "true", the Group XDMS SHALL return an HTTP "409 Conflict" including the error element <constraint-failure>. If included, the "phrase" attribute SHOULD be set to "Conflict in PoC Dispatcher actions".

6.2.4 Data semantics

The <allow-dispatch> element SHALL be used to indicate whether the identity matching this rule is allowed to perform the PoC Dispatcher role related actions, as defined in [OMA-PCPS-CP].

The possible values for the "allow" attribute are:

"false" instructs the PoC Server performing the Controlling PoC Function to deny the PoC User to adopt the PoC Dispatcher role. This SHALL be the default value taken in the absence of the element.

"true" instructs the PoC Server performing the Controlling PoC Function to allow the PoC User to adopt the PoC Dispatcher role.

The absence of the element <allow-dispatch> is equal as if there is <allow-dispatch> element with "allow" attribute equal "false".

If multiple rules with the action <allow-dispatch> apply for an identity, the identity is allowed to adopt the PoC Dispatcher role if the attribute "allow" in at least one of the actions equals "true".

The <allow-dispatcher-role-transfer> element SHALL be used to indicate that the identity matching this rule is allowed to request the transfer of an Active PoC Dispatcher role to another Participant, as defined in [OMA-PCPS-CP]. The possible values are:

"false" instructs the PoC Server performing the Controlling PoC Function to block the role transfer request. This SHALL be the default value taken in the absence of the element.

"true" instructs the PoC Server performing the Controlling PoC Function to accept the role transfer request.

The <mbc_scheme> "action" SHALL be used to indicate that the identity matching this rule is allowed to initiate the PoC Group Session with the indicated Media Burst Control Scheme. The possible values are of string type limited to 12 characters.

NOTE: Typically the standardised Media Burst Control procedure is used if <mbc_scheme> is not listed.

If multiple rules with the action <mbc_scheme> apply for an identity, the identity is allowed to initiate the PoC Group Session with any of the indicated Media Burst Control Schemes.

The <crisis-event-entity-address><allow-moderator> element SHALL be used to indicate that a special PoC Crisis Event Handling Entitywhether the identity matching this rule is invitedallowed to perform the Moderator role related actions, as defined in [OMA-PCPS-CP].

"false" instructs the PoC Session when a Pre-arrangedServer performing the Controlling PoC Group Session or a ChatFunction to deny the PoC Group Session is initiated. User to adopt the PoC Moderator role. This SHALL be the default value taken in the absence of the element.

"true" instructs the PoC Server performing the Controlling PoC Function to allow the PoC User to adopt the PoC Moderator role.

The possible valuesabsence of the <crisis-event-entity-address> element <allow-moderator> is a SIP URL giving the address to the PoC Crisis Event Handling Entity.equal as if there is <allow-moderator> element with "allow" attribute equal "false".

If multiple rules with the action <allow-moderator> apply for an identity, the identity is allowed to adopt the Moderator role if the attribute "allow" in at least one of the actions equals "true".

The <auto-release > element SHALL be used to indicate whether a PoC Session SHALL be released when the initiator of a Pre-arranged PoC Session leaves the PoC Session. The possible values for the <auto-release> element are:

"false" instructs the PoC Server to not release the PoC Session when the initiator leaves the PoC Session. In the absence of the element this SHALL be the default value.

"true" instructs the PoC Server to release the PoC Session when the initiator leaves the PoC Session.

The <allowed-media-inactivity> element includes the time in seconds the PoC Server SHALL allow inactivity in a Media-floor Control Entity in a Chat PoC Group Session or in a Pre-arranged PoC Group Session before taking a decision whether to release the PoC Session or not. The possible values are:

"0" instructs the PoC Server to allow infinitive inactivity in Media-floor Control Entities.

Greater than "0" instructs the PoC Server to start a timer using the value in <allowed-media-inactivity> element in seconds when there is no activity within a Media-floor Control Entity as defined in the [OMA-PCPS-UP].

The <release-when-poc-speech-inactive> attribute SHALL be used to indicate whether a Chat PoC Group Session or a Prearranged PoC Group Session is released when the time in the <allowed-media-inactivity> element expires.

The possible values for <release-when-poc-speech-inactive> attribute are:

"false" instructs the PoC Server to not release the PoC Session when the time in the <allowed-media-inactivity> element expires. In the absence of the attribute this SHALL be the default value.

"true" instructs the PoC Server to release the PoC Session when the time in the <allowed-media-inactivity> element expires.

6.3 PoC extensions to User Access Policy

6.3.1 Structure

In addition to the child elements that the <actions> child element of any <rule> element MAY include according to [XDM_POLICY], the <actions> child element of any <rule> element MAY include the following PoC Specific child elements:

a) the <pocbox-type> element, as defined in sub-clauses 6.3.2 "XML schema" and 6.3.4 "Data semantics".

6.3.2 XML schema

The <pocbox-type> element SHALL conform to the XML schema described in [XSD-2_POCRULES].

The XML schema described in [XSD-2_POCRULES] SHALL be used as an extension to the XML schema described in [RFC4745], if any of the following functionalities are supported:

a) the PoC Box function.

6.3.3 Validation constraints

None.

6.3.4 Data semantics

The <pocbox-type> element indicates which type of PoC Box will be connected when the incoming PoC Session invitation is routed to a PoC Box. This element has one of the following two values, whose use is described in [OMA-PCPS-CP]. The value is of an enumerated integer type:

"nwpocbox" instructs the NW PoC Box to be connected. This is the lowest value for this action, and also the value used when no match happens, according to [RFC4745]. This value is assigned the numeric value of 0.

"uepocbox" instructs the UE PoC Box to be connected. This value is assigned the numeric value of 1.

7. Group Advertisement

Group Advertisement is described in the [XDM_GROUP] "*Extended Group Advertisement*". The use of the Group Advertisement is described in [OMA-PCPS-CP].

7.1 Structure

The general Group Advertisement structure is described in the [XDM_GROUP] "Structure and Data Semantics" with the PoC Enabler specific clarifications and deviations specified in this subclause and the additional, PoC specific structure, in the subclause 8.1 "Structure".

The following elements and attributes of the <group-advertisement> element together with their usage are used by PoC Enabler as specified in [XDM_GROUP]:

a) the <group> element;

NOTE 1: In PoC service only one <group> element is sent in a Group Advertisement.

b) the <note> element.

The following elements and attributes of the <group> element together with their usage are used by PoC Enabler as specified in [XDM_GROUP]:

a) the "type" attribute indicating the type of the PoC Group;

NOTE 2: In PoC service only the values of "dialed-in" and "dialed-out" are used.

- b) the <uri>element with the value set to the PoC Group Identity of the PoC Group;
- c) the <display-name> element with the value set to PoC Group Name of the PoC Group;
- d) the <supported-services> element with the value indicating at least usage for the PoC Enabler;
- e) any other elements or attributes from any other namespaces for the purposes of extensibility.

NOTE 3: The <supported services> element can also indicate usage by other Enablers (e.g. IM) as specified in [XDM_GROUP] "Extended Group Advertisement".

7.2 XML schema

XML schema is described in the [XDM_GROUP] "XML Schema". The PoC specific XML schema extensions are described in subclause 8.2 "XML schema".

7.3 MIME type

MIME type is described in the [XDM GROUP] "MIME Type".

7.4 Validation constraints

None.

7.5 Data semantics

Data semantics are described in the [XDM_GROUP] "Structure and Data Semantics" with the PoC specific clarifications specified in this subclause. The data semantics for PoC specific extensions are described in subclause 8.4 "Data semantics".

The "type" attribute SHALL include one of the following values:

"dialed-in" in the case of a Chat PoC Group;

"dialed-out" in case of a Pre-arranged PoC Group.

8. PoC extensions to Group Advertisement

8.1 Structure

In addition to the child elements and attributes that the <group> child element of any <group-advertisement> element MAY include according to [XDM_GROUP], the <group> child element of any <group-advertisement> element MAY include the following PoC Specific child elements and attributes:

a) the "dispatch" attribute, as defined in sub-clauses 8.2 "XML schema" and 8.4 "Data semantics".

8.2 XML schema

The "dispatch" attribute SHALL conform to the XML schema described in [XSD-2-POCDISPATCH].

8.3 Validation constraints

None.

8.4 Data semantics

The "dispatch" attribute indicates whether or not the PoC Group is a Dispatch PoC Group.

The "dispatch" attribute SHALL include one of the following values:

"true" the PoC Group is a Dispatch PoC Group;

"false" the PoC Group is not a Dispatch PoC Group.

9. PoC Specific Application Usages

9.1 PoC Sessions

This subclause describes the PoC Sessions Application Usage. The use of the elements of PoC Sessions is described in [OMA-PCPS-CP].

9.1.1 Structure

The PoC Sessions document SHALL conform to the structure of the resource lists document described in [RFC4826] Section 3 with the following clarifications:

- 1) A A selement in the content of the <resource-lists> element SHALL NOT include a , <external> or <entry-ref> element;
- 2) An <entry> element in a list> element in the content of the <resource-lists> element MAY include a element containing PoC Addresses;
- 3) An <entry> element in a ist> element in the content of the <resource-lists> element MAY include a <subject> element;
- 4) An <entry> element in a list> element in the content of the <resource-lists> element SHALL include a <session-type> element;
- 5) An <entry> element in a st> element in the content of the <resource-lists> element SHALL include a <used-media-types> element.
- 6) An <entry> element in a ist> element in the content of the <resource-lists> element SHALL include a <number-of-participants> element.
- 7) An <entry> element in a ist> element in the content of the <resource-lists> element MAY include a <group-id> element.

9.1.2 Application Unique ID

The AUID SHALL be org.openmobilealliance.poc-sessions.

9.1.3 XML Schema

The elements st>, <subject>, <session-type> and <used-media-types> SHALL conform to the XML schema described in [XSD-2_1-POCSESSIONS].

The XML schema described in [XSD-2_1-POCSESSIONS] SHALL be used as an extension to the XML schema described in [RFC4826], if any of the following functionalities are supported:

a) PoC Session Search.

9.1.4 Default Namespace

The default namespace used in expanding URIs SHALL be "urn:ietf:params:xml:ns:resource-lists" defined in [RFC4826].

9.1.5 MIME Type

The MIME type SHALL be "application/resource-lists+xml".

9.1.6 Validation constraints

In addition to the XML schema, the validation constraints on a URI list of PoC Session Identities SHALL conform to those described in [RFC4826] Section 3.4.5, with the following clarifications.

If the XDMC uses or adds an <entry-ref> or an <external> child element (specified in [RFC4826]) to the list> element, the PoC Server SHALL return a "409 Conflict" response which includes the XCAP error element <constraint-failure>. If included, the "phrase" attribute SHOULD be set to "Not allowed".

9.1.7 Data Semantics

The data semantics for a URI list of PoC Session Identities SHALL conform to those described in [RFC4826] Section 3.4.6 with the following extensions:

The "uri" attribute of an <entry> element in a s> element in the content of the <resource-lists> element SHALL be the PoC Session Identity of a PoC Session being described by the PoC Sessions document.

If a list> element is included in an <entry> element then the element SHALL contain PoC Adresses of PoC Users that are allowed to join the PoC Session.

NOTE 1: If no st> element is included in an <entry> element then this means that any PoC User is allowed to join the PoC Session.

The <subject> element MAY be used to store subject information received about the PoC Session. A typical example of subject information received about the PoC Session is the <subject> element contained in a Group document as defined by [XDM GROUP].

NOTE 2: If no <subject> element is included in an <entry> element then this means that the corresponding PoC Session can not be part of a search result with any required <subject> value.

The <session-type> element in an <entry> element SHALL contain the type of the PoC Session. The possible value are:

"adhoc" represents an Ad-hoc PoC Group Session.

"prearranged" represents a Pre-arranged PoC Group Session.

"chat" represents a Chat PoC Group Session.

The <used-media-types> element in an <entry> element SHALL contain a list of the Media Types being used in the PoC Session. The possible values are:

"speech" represents PoC Speech.

"audio" represents Audio.

"video" represents Video.

"discrete" represents Discrete Media.

"streaming" represents Media Streaming Control.

The <number-of-participants> element in an <entry> element SHALL contain the current number of participants of the PoC Session.

If a PoC Group Identity is associated with the PoC Session then the <group-id> element in an <entry> element SHALL contain the PoC Group Identity.

NOTE: If no <group-id> element is included in an <entry> element then this means that the corresponding PoC Session can not be part of a search result with any required <group-id> value.

9.1.8 Naming conventions

The naming conventions for a URI list of PoC Session Identities SHALL conform to those described in [RFC4826] Section 3.4.7.

The PoC Server SHALL use a single document for all ongoing PoC Sessions hosted by the PoC Server. The filename SHALL be "index".

9.1.9 Global documents

The PoC Sessions document SHALL be a Global Document.

9.1.10 Resource interdependencies

The resource interdependencies SHALL conform to those described in [RFC4826] Section 3.4.8.

9.1.11 Authorization policies

The authorization policies SHALL conform to those described in [XDMSPEC] "Authorization".

Appendix A. Change History

(Informative)

A.1 Approved Version History

Reference	Date	Description
OMA-PCPS-TS-Document_Management-	24 Jan 2017	Status changed to Approved by TP
V1_0-20170124-A		TP Ref # OMA-TP-2017-0001-INP_PCPS-V1_0_ERP_for_Final_Approval

Appendix B. Static Conformance Requirements

(Normative)

NOTE: This section is unchanged for PCPS V1.0. It contains the SCR from PoC v2.1.

The SCRs defined in the following tables include SCRs for:

The PoC XDM Client.

The SCRs are defined as described in [OMA_SCR_Rules].

Each SCR table identifies a list of supported features as:

• Item: Identifier for a feature. It MUST be of type ScrItem.

• Function: Short description of the feature.

• Reference: Section(s) of the specification(s) with more details on the feature.

• Requirement: Other features required by this feature, independent of whether those other features are mandatory or

optional. The notation in the dependency grammar MUST be used for this column when other features

are required, else the column MUST be left empty.

Dependency grammar used in this section is specified in [OMA_SCR_Rules]:

```
TerminalExpression = ScrReference
```

/ NOT TerminalExpression

/ TerminalExpression LogicalOperator TerminalExpression

/ "(" TerminalExpression ")"

ScrReference = ScrItem

/ ScrGroup

ScrItem = SpecScrName "-" GroupType "-" DeviceType "-" NumericId "-" Status

/ SpecScrName "-" DeviceType "-" NumericId "-" Status

ScrGroup = SpecScrName ":" FeatureType

/ SpecScrName "-" GroupType "-" DeviceType "-" FeatureType

SpecScrName = 1*Character;

GroupType = 1*Character;

DeviceType = "C" / "S"; C - client, S - server

NumericId = Number Number Number

Status = "M" / "O"; M - Mandatory, O - Optional

LogicalOperator = "AND" / "OR"; AND has higher precedence than OR and OR is inclusive

FeatureType = "MCF" / "OCF" / "MSF" / "OSF";

Character = % x41-5A;

The following markers are used below to describe the SCRs:

- o PoCv1.0 SCR Item that is the same in PoCv2.0 and PoC v2.1 as it is in PoCv1.0
- o PoCv2.0 SCR Item that is the same in PoCv2.1 as it is in PoCv2.0
- o PoCv2.1 SCR Item that is new in PoCv2.1.
- o PoCv1.0mod SCR Item that exists in PoCv1.0, but is modified in PoCv2.0 or in PoC v2.1 or in both.
- o PoCv2.0mod SCR Item that exists in PoCv2.0, but is modified in PoC v2.1

B.1 PoC Group (XGP)

This subclause describes the SCRs for functions needed to support PoC Groups.

B.1.1 PoC XDM Client

Item	Function	Reference	Requirement
POC_XDM-XGP-C-001-M	XDM Client generating PoC Group documents in conformance with the Group document rules PoCv1.0	5.1 [XDM_GROUP]: 5.1	XDM_Group-XOP: MCF
POC_XDM-XGP-C-002-M	XDM Client handling of HTTP "409 Conflict" response from the Group XDMS PoCv1.0	5.1.6 [XDM_GROUP]: 5.1.6	XDM_Group-ERR-C-001-M
POC_XDM-XGP-C-003-O	XDM Client conforming to PoC specific Group extensions: PoC Dispatcher elements and attributes PoCv2.0	6.2	
POC_XDM-XGP-C-004-O	XDM Client conforming to PoC specific Group extensions: Media Burst Control Scheme elements and attributes PoCv2.0	6.2	
POC_XDM-XGP-C-005-O	XDM Client conforming to PoC specific Group extensions: Moderated PoC Crisis Event HandlingGroups elements and attributes and attributes	6.2	

B.2 PoC User Access Policy (XAP)

This subclause describes the SCRs for functions needed to support PoC User Access Policy.

B.2.1 PoC XDM Client

Item	Function	Reference	Requirement
POC_XDM-XAP-C-001-M	XDM Client generating PoC User Access Policy document in conformance with the User Access Policy rules	5.2 [XDM_POLICY]: 5.1	XDM_Policy-XOP: OCF
	PoCv1.0		
POC_XDM-XAP-C-002-M	XDM Client handling of HTTP "409 Conflict" response from the Policy XDMS PoCv1.0	5.2.6 [XDM_POLICY]: 5.1.6	XDM_Policy-ERR-C-001-O
POC_XDM-XAP-C-003-M	XDM Client conforming to PoC specific User Access Policy extensions: PoC Box elements and attributes PoCv2.0	6.3	

B.3 Group Usage List (XUL)

This subclause describes the SCRs for functions needed to support PoC Group Usage List.

B.3.1 PoC XDM Client

Item	Function	Reference	Requirement
POC_XDM-XUL-C-001-M	XDM Client generating PoC URI List document in conformance with the Group Usage List rules PoCv1.0	6.1 [XDM_LIST]: 5.2	XDM_List-XOP: OCF
POC_XDM-XUL-C-002-O	XDM Client handling of HTTP "409 Conflict" response from the List XDMS PoCv2.0	[XDM_LIST]:5.2.6	

B.4 PoC Session-unrelated Features (SUF)

This subclause describes the SCRs for functions needed to support PoC Session-unrelated features, including: Group Advertisement and PoC Session Search.

B.4.1 PoC XDM Client

Item	Function	Reference	Requirement
POC_XDM-SUF-C-001-O	PoC Client generating Group Advertisement document in conformance with the Extended Group Advertisement rules PoCv1.0	7 [XDM_GROUP]: 7.1	
POC_XDM-SUF-C-002-O	XDM Client conforming to PoC specific Group Advertisement extensions: PoC Dispatcher elements and attributes PoCv2.0	8	
POC_XDM-SUF-C-003-O	XDM Client generating search request for searching PoC Sessions documents	9.1	
POC_XDM-SUF-C-004-O	XDM Client handling of HTTP "409 Conflict" response from the PoC Server	9.1.6	POC_XDM-SUF-C-003-O

Appendix C. XML documents examples

(Informative)

C.1 Group Advertisement document

```
<?xml version="1.0" encoding="UTF-8"?>
<group-advertisement</pre>
     xmlns="urn:oma:xml:pcps:group-advertisement"
     xmlns:oxe="urn:oma:xml:xdm:xdm2-extensions">
     <note>Ice Hockey Discussion Forum</note>
     <group type="dialed-in">
          <display-name>Ice Hockey Club</display-name>
          <uri>sip:ice-hockey-club@example.com</uri>
          <oxe:group-media>
               <oxe:audio/>
               <oxe:message-session>
                    <oxe:half-duplex/>
               <oxe:message-session/>
               <oxe:group-advertisement/>
          </oxe:group-media>
     </group>
</group-advertisement>
```

C.2 Group Advertisement document with Dispatch