



SyncML Implementation Conformance Statement Proforma

Version 1.0

Abstract

The SyncML Implementation Conformance Statement is designed to be used by vendors to show their level of conformance with SyncML specifications.

Note that if your product can perform as both a client and a server, you will need to fill out both sets of forms.



SyncML Initiative

The following companies are Sponsors of the SyncML Initiative:

Ericsson
IBM
Lotus
Matsushita Communications Industrial Co., Ltd.
Motorola
Nokia
Openwave
Palm, Inc.
Psion
Starfish Software
Symbian

Revision History

Revision	Date	Comments
1.0	2001-11-02	Finalized for release.



Copyright Notice

Copyright (c) **Ericsson, IBM, Lotus, Matsushita Communication Industrial Co., LTD, Motorola, Nokia, Openwave, Palm, Inc., Psion, Starfish Software, Symbian** (2000-2001).

All Rights Reserved.

Implementation of all or part of any Specification may require licenses under third party intellectual property rights, including without limitation, patent rights (such a third party may or may not be a Supporter). The Sponsors of the Specification are not responsible and shall not be held responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE PROVIDED ON AN "AS IS" BASIS WITHOUT WARRANTY OF ANY KIND AND ERICSSON, IBM, LOTUS, MATSUSHITA COMMUNICATION INDUSTRIAL CO. LTD, MOTOROLA, NOKIA, PALM INC., PSION, STARFISH SOFTWARE AND ALL OTHER SYNCML SPONSORS DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ERICSSON, IBM, LOTUS, MATSUSHITA COMMUNICATION INDUSTRIAL CO., LTD, MOTOROLA, NOKIA, PALM INC., PSION, STARFISH SOFTWARE OR ANY OTHER SYNCML SPONSOR BE LIABLE TO ANY PARTY FOR ANY LOSS OF PROFITS, LOSS OF BUSINESS, LOSS OF USE OF DATA, INTERRUPTION OF BUSINESS, OR FOR DIRECT, INDIRECT, SPECIAL OR EXEMPLARY, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY KIND IN CONNECTION WITH THIS DOCUMENT OR THE INFORMATION CONTAINED HEREIN, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The above notice and this paragraph must be included on all copies of this document that are made.



Table of Contents

1	Introduction.....	5
2	Product Information.....	6
2.1	Device and Contact Information.....	6
2.2	Content Formats Supported.....	6
3	Server Conformance Tables.....	7
3.1	Representation Common Use Elements.....	7
3.2	Representation Message container elements.....	7
3.3	Data description elements.....	7
3.4	Representation Protocol command elements	8
3.5	Device Info	8
3.6	Meta Info	9
3.7	Protocol.....	9
3.8	Authentication.....	10
3.9	MIME header types	10
4	Client Conformance Tables.....	11
4.1	Representation Common Use Elements.....	11
4.2	Representation Message container elements.....	11
4.3	Data description elements.....	11
4.4	Representation Protocol command elements	12
4.5	Device Info	12
4.6	Meta Info	13
4.7	Protocol.....	13
4.8	Authentication.....	14
4.9	MIME header types	14
5	Transport Conformance.....	15
5.1	HTTP Transport	15
5.2	OBEX Transport.....	15
5.3	WSP Transport.....	16
6	References.....	17



1 Introduction

The purpose of this statement is to define a methodology for showing conformance with the SyncML Representation protocol [1], SyncML Sync Protocol [2] and appropriate transport. Vendors filling in this form will mark the items with either YES or NO, indicating whether the items are implemented or not. Mandatory items marked NO MUST have explanatory text.

NOTE: Server must be able to deal with with the two cases or packages 1 & 3 being sent separately and combined.



2 Product Information

2.1 Device and Contact Information

Device Name & Version	MiSync-SE Client 1.0
Company	MIENGINE Corp.
Contact Name	Kiwon Seo
Contact Phone	+82 2 568 1006 ext. 517
Contact Email	kwseo@miengine.com
Transports supported	OBEX [] WSP [] HTTP [X]
Product is	Client [x] Server []

2.2 Content Formats Supported

NOTE: If a server supports a data type listed below, it must also support the associated content format.

Data Type	Content Format	Supported (Y/N)
Contact	vCard 2.1	Y
	vCard 3.0 (optional)	Y
Calendar	vCalendar 1.0	N
	iCalendar 2.0 (optional)	N
Memos	text/plain	N
Tasks	vTodo 1.0	N
Email	message/rfc822	N
	message/rfc2822	N
	Message/rfc2045	N



3 Server Conformance Tables

NOTE: Server SHOULD be able to log the XML and WBXML documents sent between the server and a client.

3.1 Representation Common Use Elements

Command	Required of Server		Implemented in Server	
	Sending	Receiving	Sending	Receiving
Archive	MAY	MUST	NO	YES
Chal	MUST	MUST	YES	YES
Cmd	MUST	MUST	YES	YES
CmdID	MUST	MUST	YES	YES
CmdRef	MUST	MUST	YES	YES
Cred	MUST	MUST	YES	YES
Final	MUST	MUST	YES	YES
Lang	MAY	MAY	NO	NO
LocName	MAY	MAY	NO	NO
LocURI	MUST	MUST	YES	YES
MsgID	MUST	MUST	YES	YES
MsgRef	MUST	MUST	YES	YES
NoResp	MAY	MUST	NO	YES
NoResults	MAY	MAY	NO	NO
RespURI	MAY	MUST	NO	YES
SessionID*	MUST	MUST	YES	YES
SftDel	MAY	MAY	NO	NO
Source	MUST	MUST	YES	YES
SourceRef	MUST	MUST	YES	YES
Target	MUST	MUST	YES	YES
TargetRef	MUST	MUST	YES	YES
VerDTD	MUST	MUST	YES	YES
VerProto	MUST	MUST	YES	YES

*The maximum length of a SessionID is 4 bytes. Note that a client having an 8 bit incrementing SessionID counter is enough for practical implementations.

3.2 Representation Message container elements

Command	Required of Server		Implemented in Server	
	Sending	Receiving	Sending	Receiving
SyncML	MUST	MUST	YES	YES
SyncHdr	MUST	MUST	YES	YES
SyncBody	MUST	MUST	YES	YES

3.3 Data description elements

Command	Required of Server		Implemented in Server	
	Sending	Receiving	Sending	Receiving



Data	MUST	MUST	YES	YES
Item	MUST	MUST	YES	YES
Meta	MUST	MUST	YES	YES

3.4 Representation Protocol command elements

Command	Required of Server		Implemented in Server	
	Sending	Receiving	Sending	Receiving
Add	MUST	MUST	YES	YES
Alert	MUST	MUST	YES	YES
Atomic	MAY	MAY	NO	NO
Copy	MAY	MUST	NO	YES
Delete	MUST	MUST	YES	YES
Exec	MAY	SHOULD	NO	NO
Get*	MUST	MUST	YES	YES
Map	MAY	MUST	NO	YES
MapItem	MAY	MUST	NO	YES
Put*	MUST	MUST	YES	YES
Replace	MUST	MUST	YES	YES
Result*	MUST	MUST	YES	YES
Search	MAY	MAY	NO	NO
Sequence	MAY	MUST	NO	YES
Status	MUST	MUST	YES	YES
Sync	MUST	MUST	YES	YES

*Minimum requirement for a SyncML device is to support Put, Get, and Result when exchanging device information.

3.5 Device Info

Element Type	Required of Server		Implemented in Server	
	Sending	Receiving	Sending	Receiving
CTCap	SHOULD	MUST	NO	YES
CTType	MUST	MUST	YES	YES
DataStore	MUST	MUST	YES	YES
DataType	MAY	MUST	NO	YES
DevID	MUST	MUST	YES	YES
DevInf	MUST	MUST	YES	YES
DevTyp	MUST	MUST	YES	YES
DisplayName	MAY	MAY	NO	NO
DSMem	MAY	SHOULD	NO	NO
Ext	MAY	MAY	NO	NO
FwV	MAY	SHOULD	NO	NO
HwV	MAY	SHOULD	NO	NO
Man	MAY	SHOULD	NO	NO
MaxGUIDSize	MUST NOT	MUST	NO	YES
MaxID	MAY	SHOULD	NO	NO
MaxMem	MAY	SHOULD	NO	NO
Mod	MAY	MAY	NO	NO
OEM	MAY	MAY	NO	NO



ParamName	SHOULD	MUST	NO	YES
PropName	SHOULD	MUST	NO	YES
Rx	MAY	MUST	NO	YES
Rx-Pref	MUST	MUST	YES	YES
SharedMem	SHOULD	MAY	NO	NO
Size	MAY	MUST	NO	YES
SourceRef	MUST	MUST	NO	YES
SwV	MAY	SHOULD	NO	NO
SyncCap	MUST	MUST	YES	YES
SyncType	MUST	MUST	YES	YES
Tx	MAY	MUST	NO	YES
Tx-Pref	MUST	MUST	YES	YES
ValEnum	SHOULD	MUST	NO	YES
VerCT	MUST	MUST	YES	YES
VerDTD	MUST	MUST	YES	YES
Xnam	MAY	MAY	NO	NO
Xval	MAY	MAY	NO	NO

3.6 Meta Info

Element Type	Required of Server		Implemented in Server	
	Sending	Receiving	Sending	Receiving
Anchor	MUST	MUST	YES	YES
EMI	MAY	MAY	NO	NO
Format	MUST	MUST	YES	YES
FreeID	MAY	MUST	NO	YES
FreeMem	MAY	MUST	NO	YES
Last	MUST	MUST	YES	YES
Mark	MAY	MAY	NO	NO
MaxMsgSize	MAY	MUST	NO	YES
Mem	MAY	MUST	NO	YES
MetInf	MUST	MUST	YES	YES
Next	MUST	MUST	YES	YES
NextNonce	MUST	MUST	YES	YES
SharedMem	MAY	MUST	NO	YES
Size	MAY	MAY	NO	NO
Type	MUST	MUST	YES	YES
Version	MUST	MUST	YES	YES

3.7 Protocol

Element Type	Server Requirements	
	Required	Implemented
Support of 'two-way sync'	MUST	YES
Support of 'slow two-way sync'	MUST	YES
Support of 'one-way sync from client only'	MAY	NO
Support of 'refresh sync from client only'	MAY	NO



Support of 'one-way sync from server only'	MAY	NO
Support of 'refresh sync from server only'	MAY	NO
Support of 'sync alert'	MAY	NO
Support of multiple messages per package	MUST	YES
Support of combined package 1 and 3	MUST	YES

3.8 Authentication

Authentication Type	Server Requirements	
	Required	Implemented
Basic (name and password)	MUST	YES
MD5	MUST	YES

3.9 MIME header types

MIME Header Type	Server Requirements	
	Required	Implemented
"application/vnd.syncml+xml"	MUST	YES
"application/vnd.syncml+wbxml"	MUST	YES



4 Client Conformance Tables

4.1 Representation Common Use Elements

Command	Required of Client		Implemented in Client	
	Sending	Receiving	Sending	Receiving
Archive	MAY	MAY	NO	NO
Chal	MAY	MUST	NO	YES
Cmd	MUST	MUST	YES	YES
CmdID	MUST	MUST	YES	YES
CmdRef	MUST	MUST	YES	YES
Cred	MUST	MUST	YES	YES
Final	MUST	MUST	YES	YES
Lang	MAY	MAY	NO	NO
LocName	MAY	MAY	NO	NO
LocURI	MUST	MUST	YES	YES
MsgID	MUST	MUST	YES	YES
MsgRef	MUST	MUST	YES	YES
NoResp	MAY	MUST	NO	YES
NoResults	MAY	MAY	NO	NO
RespURI	MAY	MUST	NO	YES
SessionID*	MUST	MUST	YES	YES
SftDel	MAY	MAY	NO	NO
Source	MUST	MUST	YES	YES
SourceRef	MUST	MUST	YES	YES
Target	MUST	MUST	YES	YES
TargetRef	MUST	MUST	YES	YES
VerDTD	MUST	MUST	YES	YES
VerProto	MUST	MUST	YES	YES

*The maximum length of a SessionID is 4 bytes. Note that a client having an 8 bit incrementing SessionID counter is enough for practical implementations.

4.2 Representation Message container elements

Command	Required of Client		Implemented in Client	
	Sending	Receiving	Sending	Receiving
SyncML	MUST	MUST	YES	YES
SyncHdr	MUST	MUST	YES	YES
SyncBody	MUST	MUST	YES	YES

4.3 Data description elements

Command	Required of Client		Implemented in Client	
	Sending	Receiving	Sending	Receiving
Data	MUST	MUST	YES	YES
Item	MUST	MUST	YES	YES
Meta	MUST	MUST	YES	YES



4.4 Representation Protocol command elements

Command	Required of Client		Implemented in Client	
	Sending	Receiving	Sending	Receiving
Add	SHOULD	MUST	NO	YES
Alert	MUST	MUST	YES	YES
Atomic	MAY	MAY	NO	NO
Copy	MAY	MAY	NO	NO
Delete	MUST	MUST	YES	YES
Exec	MAY	MAY	NO	NO
Get*	SHOULD	MUST	NO	YES
Map	MUST	MAY	YES	NO
MapItem	MUST	MAY	YES	NO
Put*	MUST	MUST	YES	YES
Replace	MUST	MUST	YES	YES
Result*	MUST	SHOULD	YES	NO
Search	MAY	MAY	NO	NO
Sequence	MAY	MAY	NO	NO
Status	MUST	MUST	YES	YES
Sync	MUST	MUST	YES	YES

*Minimum requirement for a SyncML device is to support Put, Get, and Result when exchanging device information.

4.5 Device Info

Element Type	Required of Client		Implemented in Client	
	Sending	Receiving	Sending	Receiving
CTCap	MUST	SHOULD	YES	NO
CTType	MUST	MUST	YES	YES
DataStore	MUST	MUST	YES	YES
DataType	MAY	MAY	NO	NO
DevId	MUST	MUST	YES	YES
DevInf	MUST	MUST	YES	YES
DevTyp	MUST	MUST	YES	YES
DisplayName	MAY	MAY	NO	NO
DSMem	SHOULD	MAY	NO	NO
Ext	MAY	MAY	NO	NO
FwV	SHOULD	MAY	NO	NO
HwV	SHOULD	MAY	NO	NO
Man	SHOULD	MAY	NO	NO
MaxGUIDSize	MUST	MUST NOT	YES	NO
MaxID	SHOULD	MAY	NO	NO
MaxMem	SHOULD	MAY	NO	NO
Mod	MAY	MAY	NO	NO
OEM	MAY	MAY	NO	NO
ParamName	SHOULD	SHOULD	NO	NO
PropName	MUST	SHOULD	YES	NO
Rx	MAY	MUST	NO	YES



Rx-Pref	MUST	MUST	YES	YES
SharedMem	SHOULD	MAY	NO	NO
Size	MAY	MAY	NO	NO
SourceRef	MUST	MUST	YES	YES
SwV	SHOULD	MAY	NO	NO
SyncCap	MUST	MUST	YES	YES
SyncType	MUST	MUST	YES	YES
Tx	MAY	MUST	NO	YES
Tx-Pref	MUST	MUST	YES	YES
ValEnum	MUST	SHOULD	YES	NO
VerCT	MUST	MUST	YES	YES
VerDTD	MUST	MUST	YES	YES
Xnam	MAY	MAY	NO	NO
Xval	MAY	MAY	NO	NO

4.6 Meta Info

Element Type	Required of Client		Implemented in Client	
	Sending	Receiving	Sending	Receiving
Anchor	MUST	MUST	YES	YES
EMI	MAY	MAY	NO	NO
Format	MUST	MUST	YES	YES
FreeID	SHOULD	MAY	NO	NO
FreeMem	SHOULD	MAY	NO	NO
Last	MUST	MUST	YES	YES
Mark	MAY	MAY	NO	NO
MaxMsgSize	MAY	MUST	NO	YES
Mem	SHOULD	MAY	NO	NO
MetInf	MUST	MUST	YES	YES
Next	MUST	MUST	YES	YES
NextNonce	MAY	MUST	NO	YES
SharedMem	SHOULD	MAY	NO	NO
Size	MAY	MAY	NO	NO
Type	MUST	MUST	YES	YES
Version	MAY	MAY	NO	NO

4.7 Protocol

Element Type	Client Requirements	
	Required	Implemented
Support of 'two-way sync'	MUST	YES
Support of 'slow two-way sync'	MUST	YES
Support of 'one-way sync from client only'	MAY	NO
Support of 'refresh sync from client only'	MAY	NO
Support of 'one-way sync from server only'	MAY	NO
Support of 'refresh sync from server only'	MAY	NO
Support of 'sync alert'	MAY	NO



Support of multiple messages per package	MUST	YES
Support of combined package 1 and 3	MAY	NO

4.8 Authentication

Note that authentication is only required for SyncHdr, optional for datastore.

Authentication Type	Client Requirements	
	Required	Implemented
Basic (name and password)	MUST	YES
MD5	MUST	YES

4.9 MIME header types

NOTE: the client MUST support one of the two MIME header types.

MIME Header Type	Client Requirements	
	Required	Implemented
"application/vnd.syncml+xml"	MUST if no wbxml	YES
"application/vnd.syncml+wbxml"	MUST if no xml	NO



5 Transport Conformance

5.1 HTTP Transport

Vendors should fill this section out ONLY if their product uses the HTTP Transport. The specification for HTTP Transport is fully described in 0.

NOTE that the tables only indicate the required data.

Method	Requirements	
	Required	Implemented
POST	MUST	

General Headers	Requirements	
	Required	Implemented
Cache-Control: no-store, private	MUST	
Transfer-Encoding: chunked	MUST	

Request Headers	Requirements	
	Required	Implemented
Accept	MUST	
Accept-Charset	MUST	
Authorization	MUST	
Proxy-Authorization	MUST if a proxy client	
User-Agent	MUST	

Response Headers	Requirements	
	Required	Implemented
Authentication-Info	MUST	
Proxy-Authenticate	MUST if proxy client	
WWW-Authenticate	MUST	

5.2 OBEX Transport

Vendors should fill this section out ONLY if their product uses the OBEX Transport. The specification for OBEX Transport is fully described in 0. Note that these definitions of client and server are the OBEX definition, not the SyncML definition.

NOTE that the tables only indicate the required data.

Method	OBEX Server Requirements	
	Required	Implemented
GET	MUST	



PUT	MUST	
CONNECT	MUST	
DISCONNECT	MUST	
ABORT	MUST	

Method	OBEX Client Requirements	
	Required	Implemented
GET	MUST	
PUT	MUST	
CONNECT	MUST	
DISCONNECT	MUST	

5.3 WSP Transport

Vendors should fill this section out ONLY if their product uses the WSP Transport. The specification for WSP Transport is fully described in 0.

NOTE that the tables only indicate the required data.

Method	Requirements	
	Required	Implemented
POST	MUST	



6 References

- [1] SyncML Representation Protocol Specification
- [2] SyncML Sync Protocol
- [3] Meta Information Specification and DTD
- [4] Device Information Specification and DTD
- [5] SyncML HTTP Binding
- [6] SyncML OBEX Binding
- [7] SyncML WSP Binding